

# SikaFiber® Force-60

Revision Date 07/04/2024 Print Date 10/12/2024

#### **SECTION 1. IDENTIFICATION**

Product name : SikaFiber® Force-60

Other means of identification : No data available

Company name : www.sika.ca

Canada

Pointe-Claire, QC H9R 4A9

601, avenue Delmar Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the

chemical and restrictions on

use

: For further information, refer to product data sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

## GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

### **GHS label elements**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

### **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### Components

No hazardous ingredients

### **SECTION 4. FIRST AID MEASURES**



# SikaFiber® Force-60

Revision Date 07/04/2024 Print Date 10/12/2024

General advice No hazards which require special first aid measures.

If inhaled Move to fresh air.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No known significant effects or hazards.

No information available.

Notes to physician Treat symptomatically.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Local authorities should be advised if significant spillages **Environmental precautions** 

cannot be contained.

Methods and materials for

containment and cleaning up

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

according to the Hazardous Products Regulations



# SikaFiber® Force-60

Revision Date 07/04/2024 Print Date 10/12/2024

Advice on safe handling : For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

Materials to avoid : No special restrictions on storage with other products.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

# Safety Data Sheet

according to the Hazardous Products Regulations



# SikaFiber® Force-60

Revision Date 07/04/2024 Print Date 10/12/2024

before entering eating areas. Avoid breathing dust.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : fibers

Color : clear, gray, white

Odor : odorless

Odor Threshold : No data available

pH : Not applicable

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Flash point : 383 °C (721 °F)

Evaporation rate : No data available

Flammability (solid, gas) : May form combustible dust concentrations in air during pro-

cessing, handling or other means.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 0.91 g/cm3

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : 404 °C (759 °F)



# SikaFiber® Force-60

Revision Date 07/04/2024 Print Date 10/12/2024

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

Not applicable

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

Not classified due to lack of data.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

according to the Hazardous Products Regulations



# SikaFiber® Force-60

Revision Date 07/04/2024 Print Date 10/12/2024

Carcinogenicity

Not classified due to lack of data. **IARC** Not applicable

**OSHA** Not applicable

NTP Not applicable

Reproductive toxicity

Not classified due to lack of data.

**STOT-single exposure** 

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

**Aspiration toxicity** 

Not classified due to lack of data.

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

according to the Hazardous Products Regulations



# SikaFiber® Force-60

Revision Date 07/04/2024 Print Date 10/12/2024

### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

### **TDG**

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

### **SECTION 16. OTHER INFORMATION**

### Full text of other abbreviations

ADR	Accord européen relatif au transport international des
	Accord Europeen relatii au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

# Safety Data Sheet according to the Hazardous Products Regulations



# SikaFiber® Force-60

Revision Date 07/04/2024 Print Date 10/12/2024

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 07/04/2024 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 637.496

CA / Z8