

SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

SECTION 1. IDENTIFICATION

Product name : SikaThorocoat-400 smooth pastel fact tb Formerly MProtect

HB 400 SM Ser P

Product code : 00000000051717123

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Carcinogenicity (Inhalation) : 1A

- repeated exposure

2 (Kidney)

Short-term (acute) aquatic

Specific target organ toxicity

hazard

. ၁

Long-term (chronic) aquatic

hazard

: 3

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H350 May cause cancer.

H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P273 Avoid release to the environment. P260 Do not breathe dust or mist.

Response:

P314 Get medical advice/ attention if you feel unwell. P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 10 - < 25
Titanium dioxide	13463-67-7	>= 5 - < 20
Isobutyric acid, monoester with 2,2,4-	25265-77-4	>= 0 - < 3
trimethylpentane-1,3-diol		
ethyleneglycol	107-21-1	>= 1 - < 3
Quartz (SiO2)	14808-60-7	>= 0.1 - < 0.3
Poly(oxy-1,2-ethanediyl), .alpha [(1,1,3,3-tetramethylbutyl)phenyl]- .omegahydroxy-	9036-19-5	>= 0.1 - < 0.3
diuron	330-54-1	>= 0 - < 0.1
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate	55406-53-6	>= 0 - < 0.1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version SDS Number: Date of last issue: -Revision Date:

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

In case of skin contact After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact Flush eyes with water as a precaution.

> Remove contact lenses. Protect unharmed eve.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May cause cancer.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec: Use personal protective equipment.



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : No applicable information available.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
ethyleneglycol	107-21-1	TWA value	25 ppm	ACGIHTLV
		(Vapor frac-		
		tion)		
		STEL value	50 ppm	ACGIHTLV
		(Vapor frac-		



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

		tion)	1	1
		STÉL value	10 mg/m3	ACGIHTLV
		(Aerosol, inhalable.)		
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Va- por)	50 ppm	ACGIH
		STEL (Inhal- able fraction, Aerosol only)	10 mg/m3	ACGIH
		С	50 ppm 125 mg/m3	OSHA P0
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Res- pirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

		PEL (Total dust) TWA value (Total dust) TWA (total dust)	15 mg/m3 10 mg/m3 15 mg/m3	29 CFR 1910.1000 (Table Z-1) 29 CFR 1910.1000 (Table Z-1-A) OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respir- able)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) respirator as neces-

sary.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : white

pH : 9 - 10

Boiling point : 379 - 471 °F / 193 - 244 °C

Flash point : $> 200 \, ^{\circ}\text{F} \, / > 93 \, ^{\circ}\text{C}$

Method: Standard Method of Test for Flash Point by Setaflash

Closed Tester

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : 1.41 g/cm3 (73 °F / 23 °C)



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

Solubility(ies)

Water solubility : dispersible

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : not determined

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Based on the water content the product has no explosive

properties.

Oxidizing properties : Not an oxidizer.

Sublimation point : No applicable information available.

Molecular weight : No data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

Persistence and degradability

Components:

Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:

Biodegradability : aerobic

Inoculum: activated sludge, domestic, non-adapted

Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

Method: Modified OECD-Screening-Test.

Bioaccumulative potential

Components:

Titanium dioxide:

Partition coefficient: n-

octanol/water

Remarks: not applicable

Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol:

Partition coefficient: n- : log Pow: 3.2 (77 °F / 25 °C)

octanol/water pH: 7

Method: Partition coefficient (n-octanol/water), HPLC method.

GLP: no

ethyleneglycol:

Partition coefficient: n- : log Pow: approx. -1.36 (73 °F / 23 °C) octanol/water : Method: Calculation Hansch/Leo

GLP: no data

Remarks: Information taken from reference works and the

literature.

Quartz (SiO2):

Partition coefficient: n-

octanol/water

Remarks: not applicable

Bioaccumulation : Remarks: Accumulation in organisms is not to be expected.

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate:

Partition coefficient: n- : log Pow: 2.81 (77 °F / 25 °C)

octanol/water Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: yes



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

ethyleneglycol 107-21-1



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

US State Regulations

Pennsylvania Right To Know

ethyleneglycol	107-21-1
Limestone	1317-65-3
Titanium dioxide	13463-67-7
ethylene oxide	75-21-8
propylene oxide	75-56-9
1.4-dioxane	123-91-1

New Jersey Right To Know

ethyleneglycol	107-21-1
Limestone	1317-65-3
Titanium dioxide	13463-67-7
Quartz (SiO2)	14808-60-7
Quartz (SiO2)	14808-60-7
Distillates (netroleum), hydrotreated heavy nanhthenic	64742-52-5

Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains relatively few normal paraffins.]

California Prop. 65

WARNING: This product can expose you to chemicals including ethylene oxide, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

Further information




SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -


1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average

OSHA P0 / C : Ceiling limit

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 07/17/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.



SikaThorocoat-400 smooth pastel fact tb Formerly MProtect HB 400 SM Ser P

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/17/2020 000000265113 Date of first issue: 07/17/2020

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN