



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikadur ATP PART A**REVISION DATE: February 1st, 2015

USAGE: Rapid setting, high strength repair mortar for concrete

MANUFACTURER/SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666**TDG CLASSIFICATION: Not Regulated
UN NUMBER: Not Applicable
Packaging Group: Not ApplicableWHMIS Classification: D1A, D2A, D2B
Class: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
4,4-DIPHENYLMETHANE DIISOCYANATE (4.4MDI)	30-60	ACGIH TWA 0.005 ppm	101-68-8	31 600 (rat, oral)	369 mg/m ³ /4H (rat)
AROMATIC HYDROCARBON MIXTURE	15-40	Not available	MIXTURE	Not available	Not available

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid
Appearance and Odor: Amber to brown liquid, slightly
musty
Odor Threshold: 0.4ppm (4.4MDI)
Evaporation Rate: Not established
Vapor Density: 8.5 (Air=1)
Vapor Pressure: <0.0003 mmHgBoiling Point: Decomposes @ 200°C
Freezing Point: Not established
Density: 1.24 g/ml
Water Solubility: Reacts with water
pH: Not established
% volatility: Not established
Water/Oil Distribution: Not established

PRODUCT: **Sikadur ATP**

PART A

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions	No But avoid Flames and sparks.	TDG Flammability Class: Flammable upper limits (% vol.): Flammable lower limits (% vol.): Flash Point (method used): Auto-ignition temperature:	Not regulated Not established Not established > 160°C Not established
Extinguishing methods:	Foam, dry chemical products, CO ₂ , water spray for larges fires.	Dangerous Combustion Products:	Carbon oxides, Nitrogen oxides
Special Methods:	Firefighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.	Protect from mechanical impact: Protect from static discharge:	No No

SECTION V: REACTIVITY DATA

Chemical stability: If not, under what conditions	Yes, under recommended storage conditions	Dangerous decomposition products:	Carbon oxides, Aliphatic fragments, NH ₃
Incompatibility with other material: If Yes, which ones:	Yes Water, acid, bases, metal compounds and surface active materials.	Polymerization Risks:	May occur with incomplete reactants. Especially strong bases, water or temperatures over 190°C.



PRODUCT: Sikadur ATP

PART A

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations. May cause severe burns. May cause blindness.

Skin: May be irritating to the skin, may cause severe burns, can be absorbed by skin. Contact may cause necrosis, dermatitis, allergic reactions, and sensitization.

Inhalation: Vapors or mist of this product may cause irritation.

Ingestion: May cause severe burns to the mouth, throat, stomach. May cause vomiting, nausea, fainting, diarrhea, damages to the lungs, bleeding of the gastro-intestinal system and death.

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting. May aggravate respiratory, skin, eye, lung problems and allergies.

If the product is applied according to the manufacturer, none of these symptoms should be encountered.

A person who is sensitized to isocyanate may have a reaction with a level of isocyanate well below the T.L.V.

Carcinogenicity: Not established

Toxic effects on reproduction: Not established

Teratogenicity: Not established

Mutagenicity: Not established

Product with synergistic effects: Not known

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: Sikadur ATP

PART A

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: NIOSH/MSHA approved air supplied respirator if there is no sufficient ventilation.

Eyes: Safety glasses

Shoes: Leather

Clothing: Rubber apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand or other absorbent material. Residue may be removed with steam or hot water and soap. All precautions should be taken when cleaning the spill with solvent.

Handling and Equipment Methods: Avoid skin, eye and clothing contact.

Warehouse Requirements: Keep all containers closed in a cool, dry area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class.

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikadur ATP PART A

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of soap and water.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water for at least 15 minutes to ensure a proper wash.
Consult a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikadur ATP PART B** REVISION DATE: February 1st, 2015

USAGE: Rapid setting, high strength repair mortar for concrete

MANUFACTURER/SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not Regulated WHMIS Classification: B3, D2B
UN NUMBER: Not Applicable Class: Not Applicable
Packaging Group Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
EPOXY RESIN	10-30	Not available	25085-99-8	> 5000 (oral, rat)	Not available
ISOPARAFFINIC HYDROCARBON	10-30	Not available	64742-48-9	10 000 (oral, rat)	>2 000ppm/4h (rat)

SECTION III: PHYSICAL CHARACTERISTICS

Physical State:	Liquid	Boiling Point:	210-288°C
Appearance and Odor:	Amber to dark brown liquid, faint acetic-like odor	Freezing Point:	Not established
		Density:	1.2 g/ml
Odor Threshold:	Not established	Water Solubility:	Partial (Greater than 50%)
Evaporation Rate:	Not established	pH:	Not established
Vapor Density:	Not established	% volatility:	0
Vapor Pressure:	0.14 mmHg	Water/Oil Distribution:	Not established



PRODUCT: Sikadur ATP

PART B

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: Combustible
 If Yes, under what conditions: Avoid Flames and sparks.

Extinguishing methods: Foam, dry chemical products, CO₂, water hose.

Special Methods: Fire fighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.

TDG Flammability Class: Not Regulated
 Flammable upper limits (% vol.): Not established
 Flammable lower limits (% vol.): Not established
 Flash Point (method used): 82°C (PMCC)
 Auto-ignition temperature: 488°C
 Dangerous Combustion Products: Carbon oxides, nitrogen oxides.

Protect from mechanical impact: No
 Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes
 If not, under what conditions

Incompatibility with other material: Yes
 If Yes, which ones Oxidizing materials, isocyanates, acids and alkali or alkaline earth.

Dangerous decomposition products: Carbon oxides, NH₃.

Polymerization Risks: No



PRODUCT: Sikadur ATP

PART B

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations.

Skin: May be irritating to the skin after prolonged contact. Some individuals may be more sensitive to exposure.

Inhalation: May cause irritation to the throat and respiratory passages, but at room temperature, vapor inhalation is not considered hazardous.

Ingestion: This is not considered a common occupational route of exposure, and no observable effects have been demonstrated.

Carcinogenicity: Not established

Toxic effects on reproduction: Not established

Teratogenicity: Not established

Mutagenicity: Not established

Product with synergistic effects: Not known

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: Sikadur ATP

PART B

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes Full face mask or safety glasses

Shoes: Leather

Clothing: Rubber apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case Of leaks: Absorb with sand or other absorbent material.

Handling and Equipment Methods: Avoid skin, eye and clothing contact.

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class.

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikadur ATP

PART B

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of soap and water.
Throw away shoes that were soiled on the inside.
Wash clothing before re-wearing.
Consult a physician if necessary.

Eyes: Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.
The eye rinse within the first minute is essential to ensure maximum protection.
Consult a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.