

Revision Date 12/07/2023 Print Date 10/12/2024

#### **SECTION 1. IDENTIFICATION**

Product name : SikaTack® MOVE Global 30

Other means of identification : No data available

Company name : www.sika.ca

Canada

Pointe-Claire, QC H9R 4A9

601, avenue Delmar Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

Respiratory sensitization : Category 1

Skin sensitization : Category 1

**GHS** label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing should not be allowed out of

the workplace.



Revision Date 12/07/2023 Print Date 10/12/2024

P280 Wear protective gloves.

P284 In case of inadequate ventilation wear respiratory protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

# **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

# Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
aliphatic prepolymer (t-polyether based)	138626-39-8	Skin Sens. 1; H317	>= 1 - < 5
aliphatic prepolymer (d-polyether based)	39323-37-0	Skin Sens. 1; H317	>= 1 - < 5
4,4'-methylenediphenyl diisocyanate	101-68-8	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 0.1 - < 1
Aliphatic polyisocyanate	28182-81-2	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335	>= 0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**



Revision Date 12/07/2023 Print Date 10/12/2024

General advice Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

: Remove contact lenses. In case of eye contact

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

sensitizing effects Asthmatic appearance Allergic reactions

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

Treat symptomatically. Notes to physician

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Deny access to unprotected persons.

according to the Hazardous Products Regulations



# SikaTack® MOVE Global 30

Print Date 10/12/2024 Revision Date 12/07/2023

Do not flush into surface water or sanitary sewer system. **Environmental precautions** 

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.005 ppm	CA BC OEL
		С	0.01 ppm	CA BC OEL
		TWA	0.005 ppm	CA ON OEL
		С	0.02 ppm	CA ON OEL
		TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
		TWA	0.005 ppm	ACGIH
Aliphatic polyisocyanate	28182-81-2	TWA	0.005 ppm	CA BC OEL
		С	0.01 ppm	CA BC OEL

**Engineering measures** Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this according to the Hazardous Products Regulations



# SikaTack® MOVE Global 30

Revision Date 12/07/2023 Print Date 10/12/2024

product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

# Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : black

Odor : very faint

Odor Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)



Revision Date 12/07/2023 Print Date 10/12/2024

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point :  $> 101 \, ^{\circ}\text{C} (214 \, ^{\circ}\text{F})$ 

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : 0.01 hpa

Relative vapor density : No data available

Density : ca. 1.26 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

5 g/l

# **SECTION 10. STABILITY AND REACTIVITY**



Revision Date 12/07/2023 Print Date 10/12/2024

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Acute toxicity**

Not classified due to lack of data.

# **Components:**

# 4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

Aliphatic polyisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 2,500 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

#### Skin corrosion/irritation

Not classified due to lack of data.

#### Serious eye damage/eye irritation

Not classified due to lack of data.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

# Safety Data Sheet

according to the Hazardous Products Regulations



# SikaTack® MOVE Global 30

Revision Date 12/07/2023 Print Date 10/12/2024

#### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# Germ cell mutagenicity

Not classified due to lack of data.

# Carcinogenicity

Not classified due to lack of data.

IARC Group 2B: Possibly carcinogenic to humans

Carbon black, amorphous 1333-86-4

**OSHA** Not applicable

NTP Not applicable

#### Reproductive toxicity

Not classified due to lack of data.

#### STOT-single exposure

Not classified due to lack of data.

# STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

# **Aspiration toxicity**

Not classified due to lack of data.

# **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### Components:

# aliphatic prepolymer (t-polyether based):

Toxicity to algae/aquatic : EC50 (algae): 100 mg/l

plants

NOEC (algae): 100 mg/l

#### aliphatic prepolymer (d-polyether based):

Toxicity to daphnia and other : EC50 (Daphnia): > 100 mg/l

aquatic invertebrates

NOEC (Daphnia): > 100 mg/l

Toxicity to algae/aquatic :

plants

: EC50 (algae): > 100 mg/l



Revision Date 12/07/2023 Print Date 10/12/2024

# Persistence and degradability

No data available

# Bioaccumulative potential

No data available

# Mobility in soil

No data available

# Other adverse effects

# **Product:**

Additional ecological infor-

mation

: Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

# **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

# **IMDG-Code**

Not regulated as a dangerous good

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

#### TDG

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

# **Canadian lists**

No substances are subject to a Significant New Activity Notification.

according to the Hazardous Products Regulations



# SikaTack® MOVE Global 30

Revision Date 12/07/2023 Print Date 10/12/2024

# **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average CA BC OEL / TWA : 8-hour time weighted average

CA BC OEL / C : ceiling limit
CA ON OEL / C : Ceiling Limit (C)

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### Notice to Reader:

# Safety Data Sheet according to the Hazardous Products Regulations



# SikaTack® MOVE Global 30

Revision Date 12/07/2023 Print Date 10/12/2024

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 12/07/2023 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 570,145

CA / Z8