

PRODUCT DATA SHEET

SikalInject® TX-21

Thixotropic agent (formerly TPH.® PUR-O-STOP-FS TX)

PRODUCT DESCRIPTION

SikalInject® TX-21 is a thixotropic agent suitable for use with SikalInject®-210 DE.

WHERE TO USE

SikalInject® TX-21 may only be used by experienced professionals.

- To stop fast-flowing water when using SikalInject®-210 DE
- To increase the viscosity of the base resin

CHARACTERISTICS / ADVANTAGES

- Thickens the resin
- Reduces wash-out
- Increases efficiency

Contact Sika Canada for more information on compatibility with other polyurethane injection resins from the SikalInject® range.

PRODUCT INFORMATION

Packaging	4.5 kg	
Appearance / Colour	Liquid / Transparent, yellowish	
Shelf Life	12 months from date of production	
Storage Conditions	Store in original, unopened and undamaged sealed packaging, in dry conditions, at temperatures between 15 °C and 25 °C.	
Density	~0.92 kg/L	(DIN EN ISO 2811-1)
Viscosity	~21 cps	(DIN EN ISO 2555)

BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

ENVIRONMENT, HEALTH & SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

MIXING

Add 7 % of SikalInject® TX-21 to part A of SikalInject®-210 DE and mix homogeneously. After mixing with part B of SikalInject®-210 DE, the product shows a highly-viscous consistency.

Wash-out of this thixotropic injection resin by fast-flowing water is more difficult.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca

Sika Canada Inc.
Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9
1-800-933-SIKA
www.sika.ca

Other locations
Boisbriand (Quebec)
Brantford; Cambridge;
Sudbury; Toronto (Ontario)
Edmonton (Alberta)
Surrey (British Columbia)

Product Data Sheet
SikalInject® TX-21
February 2026, Version 01.01
020707010020000058

SikalInjectTX-21-en-CA-(02-2026)-1-1.pdf

**BUILDING TRUST
CONSTRUIRE LA CONFIANCE**

