


**SECTION 1. IDENTIFICATION**

Product name	:	Sikagard® Duroplast® EE Part B
Other means of identification	:	No data available
Company name	:	www.sika.ca Canada Pointe-Claire, QC H9R 4A9 601, avenue Delmar Sika Canada Inc.
Telephone	:	(514) 697-2610 / 1 (800) 933-7452
Telefax	:	(514) 694-2792
E-mail address	:	ehs@ca.sika.com
Emergency telephone	:	CANUTEC (collect) (613) 996-6666 (24 hours)
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Skin irritation	:	Category 2
Eye irritation	:	Category 2A
Skin sensitization	:	Category 1
Carcinogenicity (Inhalation)	:	Category 1A
Specific target organ toxicity - repeated exposure (Inhalation)	:	Category 1 (Central nervous system)

**GHS label elements**

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.



H350 May cause cancer by inhalation.  
 H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

## Precautionary Statements :

**Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe mist or vapors.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
bisphenol-A-(epichlorhydrin) epoxy resin	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	$\geq 10 - < 30$



Stoddard solvent	8052-41-3	Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 1; H372 Asp. Tox. 1; H304	>= 1 - < 5
Quartz (SiO2) >5µm	14808-60-7	Carc. 1A; H350i STOT RE 1; H372 STOT SE 3; H335	>= 0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitizing effects  
Allergic reactions  
Excessive lachrymation  
Erythema  
Dermatitis  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-



- cumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Prevent unauthorized access. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations. Protect from frost.



Store in original container.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Observe label precautions.  
 Store in accordance with local regulations.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Stoddard solvent	8052-41-3	TWA	100 ppm 572 mg/m3	CA AB OEL
		TWA	290 mg/m3	CA BC OEL
		STEL	580 mg/m3	CA BC OEL
		TWAEV	100 ppm 525 mg/m3	CA QC OEL
		TWA	525 mg/m3	CA ON OEL
		TWA	100 ppm	ACGIH
Quartz (SiO2) >5µm	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable)	0.025 mg/m3	CA BC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH



**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : white

Odor : epoxy-like

Odor Threshold : No data available

pH : ca. 9.5



Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 100 °C (212 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	23 hpa
Relative vapor density	:	No data available
Density	:	1.561 g/ml (23 °C (73 °F))
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	65 g/l A+B Combined

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No dangerous reaction known under conditions of normal use.
------------	---	---



- Chemical stability : The product is chemically stable.
- Possibility of hazardous reactions : Stable under recommended storage conditions.
- Conditions to avoid : No data available
- Incompatible materials : No data available
- Hazardous decomposition products : No decomposition if stored and applied as directed.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

Not classified based on available information.

**Components:**

**bisphenol-A-(epichlorhydrin) epoxy resin:**

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization**

**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer by inhalation.

<b>IARC</b>	Group 1: Carcinogenic to humans Quartz (SiO <sub>2</sub> ) >5µm (Silica dust, crystalline)	14808-60-7
<b>OSHA</b>	OSHA specifically regulated carcinogen Quartz (SiO <sub>2</sub> ) >5µm (crystalline silica)	14808-60-7
<b>NTP</b>	Known to be human carcinogen Quartz (SiO <sub>2</sub> ) >5µm	14808-60-7





(Silica, Crystalline (Respirable Size))

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

**Product:**

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Components:**

**bisphenol-A-(epichlorhydrin) epoxy resin:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
aquatic invertebrates Exposure time: 48 h

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

##### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### TDG

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

#### Canadian lists

No substances are subject to a Significant New Activity Notification.

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
- CA BC OEL : Canada. British Columbia OEL
- CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
- CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
- ACGIH / TWA : 8-hour, time-weighted average
- CA AB OEL / TWA : 8-hour Occupational exposure limit



CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

**Sikagard® Duroplast® EE Part B**



Revision Date 06/08/2022

Print Date 10/12/2024

---

Revision Date : 06/08/2022  
Date format : mm/dd/yyyy  
Prepared by : R & D of Sika Canada Inc.  
Material number : 457,156

CA / Z8