according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

SECTION 1. IDENTIFICATION

Product name : SENERFLEX TERSUS F1.0 COL DK

Product code : 00000000050304259

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Sika MBCC Canada, Inc.

Address : 601 DELMAR AVE

Pointe-Claire QC H9R 4A9

Emergency telephone : ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Acrylic polymer

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
crystalline silica	Quartz (SiO2)	14808-60-7	>= 30 - < 50
Mica-group minerals	Mica	12001-26-2	>= 1 - < 5
Kieselguhr, soda ash flux-calcined	Flux calcined diatomaceous earth	68855-54-9	>= 1 - < 5
Cellulose	Microcrystalline cellulose	9004-34-6	>= 1 - < 5
Titanium dioxide	C.I. Pigment White 6	13463-67-7	>= 0.1 - < 1
1,3,5-Triazine- 1,3,5(2H,4H,6H)- triethanol	2,2',2"- (hexahydro- 1,3,5-triazine-	4719-04-4	>= 0.1 - < 1

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

1,3,5-|triyl)triethanol

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Remove contact lenses, if present.

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention. Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod: :

ucts

: harmful vapours nitrogen oxides fumes/smoke

fumes/smoke carbon black carbon oxides

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment :

for fire-fighters

Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact.

Avoid contact with eyes.

Conditions for safe storage : Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Recommended storage tem-

perature

> 4 °C

Further information on stor-

age stability

PROTECT FROM FREEZING DURING THE COLD-SEASON

(BELOW 40°F / 5°C).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

		/F	tana / Damaia silala	
		(Form of	ters / Permissible	
am atallia a silia a	44000.00.7	exposure)	concentration	OA AD OEL
crystalline silica	14808-60-7	TWA (Res-	0.025 mg/m3	CA AB OEL
		pirable par-		
		ticulates)	0.4/0	04 011 051
		TWA (Res-	0.1 mg/m3	CA ON OEL
		pirable frac-		
		tion) TWAEV	0.4	CA QC OEL
			0.1 mg/m3	CA QC OEL
		(respirable		
		dust)	0.005/0	CA BC OEL
		TWA (Res-	0.025 mg/m3	CA BC OEL
		pirable)	(Silica)	ACGIH
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par- ticulate mat-	(Silica)	
		ter)		
Mica-group minerals	12001-26-2	TWA (Res-	3 mg/m3	CA AB OEL
iviica-group minerais	12001-20-2	pirable)	3 mg/m3	CA AB OEL
		TWA (Res-	3 mg/m3	CA BC OEL
		pirable)	3 mg/m3	OA BO OLL
		TWAEV	3 mg/m3	CA QC OEL
		(respirable	3 mg/m3	OA QU OLL
		dust)		
		TWA (Res-	0.1 mg/m3	ACGIH
		pirable par-	o. i mg/mo	7.00
		ticulate mat-		
		ter)		
Cellulose	9004-34-6	TWA value	10 mg/m3	ACGIHTLV
		PEL (Respir-	5 mg/m3	29 CFR
		able fraction)	3	1910.1000
		′		(Table Z-1)
		PEL (Total	15 mg/m3	29 CFR
		dust)		1910.1000
		,		(Table Z-1)
		TWA	10 mg/m3	CA AB OEL
		TWA (Total	10 mg/m3	CA BC OEL
		dust) `		
		TWA (respir-	3 mg/m3	CA BC OEL
		able dust		
		fraction)		
		TWAEV (to-	10 mg/m3	CA QC OEL
		tal dust)		
		TWA	10 mg/m3	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen depending on activity and

possible exposure, e.g. head protection, apron, protective

boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : off-white

Odor : mild, acrylic-like

Odor Threshold : not determined

pH : 8.5 - 9.8 (23 °C)

Melting point/freezing point : No data available

Boiling point : No data available

Flash point : > 94 °C

Method: Standard Method of Test for Flash Point by Setaflash

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

Closed Tester

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Self-ignition : Based on the water content the product does not ignite.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.85 g/cm3 (23 °C)

Solubility(ies)

Water solubility : partly miscible (15 °C)

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

not applicable for mixtures

Autoignition temperature : Based on the water content the product does not ignite.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

Metal corrosion rate : No corrosive effect on metal.

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

crystalline silica 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1) 1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

09/22/2023 000000540425 Date of first issue: 09/22/2023 1.0

the Occupational Health and Safety Act.

CA QC OEL Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

29 CFR 1910.1000 (Table Z- :

1) / PEL

Permissible exposure limit

ACGIH / TWA 8-hour, time-weighted average ACGIHTLV / TWA value Time Weighted Average (TWA): 8-hour Occupational exposure limit CA AB OEL / TWA CA BC OEL / TWA 8-hour time weighted average

CA ON OEL / TWA Time-Weighted Average Limit (TWA) Time-weighted average exposure value CA QC OEL / TWAEV

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date 09/22/2023 Date format mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

according to the Hazardous Products Regulations



SENERFLEX TERSUS F1.0 COL DK

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/22/2023 000000540425 Date of first issue: 09/22/2023

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN