



Sikafloor®-1620

LOW PERMEABILITY, MOISTURE VAPOUR CONTROL EPOXY PRIMER

Sikafloor®-1620 is a two-component, high solids, low viscosity, moisture tolerant epoxy primer. It is designed to treat high moisture content concrete floors to be covered with a Sikafloor®, Sikagard® or Sikalastic® resin system to be applied to substrates with a moisture content of 6 % or less (as measured with a Tramex® CME CMExpert® concrete moisture meter).



TO LEARN MORE



ADVANTAGES

- Economical single coat application
- Low permeability ~0.06 perms (15 mil d.f.t) ASTM E96
- Cured resin resists high moisture vapour emission rates (MVER) up to 25 lb as per ASTM F1869, 100 % R.H. as per ASTM F2170
- Resists high alkalinity to pH 14
- Low viscosity provides superior penetration and stabilization of cementitious substrates
- Resistant to substrate out gas bubbling
- Low odour and low VOC
- 15.12 L (4.0 US gal) kit

Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

Sika Canada Inc.
Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9

Other locations
Boisbriand (QC)
Brantford; Cambridge;
Sudbury; Toronto (ON)
Edmonton (AB) Surrey (BC)

1-800-933-SIKA
www.sika.ca

© Sika Canada Inc. / 09.2024

BUILDING TRUST
CONSTRUIRE LA CONFIANCE

