

SikaLevel®-115 Skim Coat

RAPID-SETTING CEMENTITIOUS SKIMCOATING COMPOUND



4.5 kg (10 lb) plastic bag

TO LEARN MORE



Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

Sika Canada Inc. Head Office 601, avenue Delmar Pointe-Claire, Quebec H9R 4A9 Other locations
Boisbriand (QC)
Brantford; Cambridge;
Sudbury; Toronto (ON)
Edmonton (AB) Surrey (BC)

1-800-933-SIKA www.sika.ca SikaLevel®-115 Skim Coat is a 1-component, easy to use and fast drying, cementitious skimcoating compound ideal for the repair or preparation of concrete, approved wood underlayments. SikaLevel®-115 Skim Coat can be installed as a true featheredge as well as filling voids and minor levelling defects up to 13 mm (1/2 in) in depth.

ADVANTAGES

- Only needs to be mixed with water. Easy to mix and quick to apply
- Creamy consistency helps to achieve a smooth surface with minimal trowel passes
- Good adhesion to substrates and approved underlayments
- Rapid setting; When applied as a skim coat, resilient flooring can be installed as soon as spreading the adhesive with a notched trowel does not damage the surface (generally after 20 minutes)

WHERE TO USE

- Can be used to pre-fill holes or non-active cracks in concrete and seams in industry approved wood underlayments
- Can be used to smooth out rough surfaces and correct minor defects in concrete and industry approved wood underlayments prior to applying floor coverings

