

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wh



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex HY 100 white Formerly MSeal NP 100 Wh
Product code : 000000000050363508

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization : Category 1A
Serious eye damage/eye irritation : Category 2A
Carcinogenicity : Category 1A
Reproductive toxicity : Category 1B
Short-term (acute) aquatic hazard : Category 3
Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black exclamation mark inside. The second is a red diamond with a black silhouette of a person's head and shoulders, with a starburst symbol on the forehead, indicating a health hazard.

Signal Word : Danger

Hazard Statements : H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H350 May cause cancer.

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wht



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

H360 May damage fertility or the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P201 Obtain special instructions before use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Sealant

Components

Chemical name	CAS-No.	Concentration (% w/w)
dibutyltin dilaurate	77-58-7	>= 0 - < 1
Quartz (SiO ₂)	14808-60-7	>= 0 - < 1
2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol	25973-55-1	>= 0.2 - < 3
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	>= 0 - < 3
bis(2,2,6,6-tetramethyl-4-	52829-07-9	>= 0.2 - < 3

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Whit



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

piperidyl)sebacate		
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	$\geq 0 - < 1$
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	$\geq 0.2 - < 3$
Trimethoxyvinylsilane	2768-02-7	$\geq 0.3 - < 3$
Dibutylbis(pentane-2,4-dionato-O,O')tin	22673-19-4	$\geq 0 - < 1$
calcium carbonate	471-34-1	$\geq 3 - < 50$
Limestone	1317-65-3	$\geq 3 - < 50$
stearic acid	57-11-4	$\geq 0.1 - < 7$
Titanium dioxide	13463-67-7	$\geq 0 - < 15$

SECTION 4. FIRST AID MEASURES

- General advice : Remove contaminated clothing.
- Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Keep patient calm, remove to fresh air, seek medical attention.
Immediately administer a corticosteroid from a controlled/metered dose inhaler.
- If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.
- If on skin, rinse well with water.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
- Induce vomiting immediately and call a physician.
Keep respiratory tract clear.

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wht



Version	Revision Date:	SDS Number:	Date of last issue: 06/03/2020
1.1	01/08/2021	000000586258	Date of first issue: 06/03/2020

Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye irritation.
May cause cancer.
May damage fertility or the unborn child.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wh



Version 1.1 Revision Date: 01/08/2021 SDS Number: 00000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

is formed.

- Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Materials to avoid : Observe TRGS 509/510 storage rules.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
stearic acid	57-11-4	TWA value (Inhalable fraction)	10 mg/m ³	ACGIHTLV
		TWA value (Respirable fraction)	3 mg/m ³	ACGIHTLV
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wht



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m3 (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m3 (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m3 (tin (Sn))	NIOSH
		PEL	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Whit



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Dibutylbis(pentane-2,4-dionato-O,O')tin	22673-19-4	TWA value	0.1 mg/m3 (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m3 (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m3 (tin (Sn))	NIOSH
		PEL	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wh



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

- problems.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Avoid inhalation of dusts.
Wearing of closed work clothing is required additionally to the stated personal protection equipment.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : solid (68 °F / 20 °C)
- Color : white
- Odor : faint odour
- pH : No data available
- Melting point : No applicable information available.
- Boiling point : No applicable information available.
- Flash point : > 253 °F / > 123 °C
Method: Standard Method of Test for Flash Point by Setaflash Closed Tester
does not flash
- Evaporation rate : No applicable information available.
- Flammability (solid, gas) : not determined
- Self-ignition : not self-igniting
- Upper explosion limit / Upper flammability limit : No applicable information available.
- Lower explosion limit / Lower flammability limit : No applicable information available.
- Vapor pressure : No applicable information available.

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wh



Version 1.1	Revision Date: 01/08/2021	SDS Number: 000000586258	Date of last issue: 06/03/2020 Date of first issue: 06/03/2020
----------------	------------------------------	-----------------------------	---

Relative vapor density	:	No applicable information available.
Relative density	:	No applicable information available.
Density	:	11.65 lb/USg (73 - 77 °F / 23 - 25 °C)
Solubility(ies)	:	
Water solubility	:	insoluble (59 °F / 15 °C)
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No applicable information available.
Autoignition temperature	:	No applicable information available.
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive
Oxidizing properties	:	Not an oxidizer.
Self-heating substances	:	No data available
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	Avoid moisture. See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong bases Strong oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wht



Version 1.1	Revision Date: 01/08/2021	SDS Number: 000000586258	Date of last issue: 06/03/2020 Date of first issue: 06/03/2020
----------------	------------------------------	-----------------------------	---

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : ATE: > 5,000 mg/kg

Acute dermal toxicity : ATE: > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Components:

2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol:

Not applicable

bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate:

Not applicable

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wh



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

Trimethoxyvinylsilane:

Not applicable

Dibutylbis(pentane-2,4-dionato-O,O')tin:

Not applicable

stearic acid:

Not applicable

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

dibutyltin dilaurate:

M-Factor (Acute aquatic toxicity) : 1

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability

No data available

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wh



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

Bioaccumulative potential

Components:

dibutyltin dilaurate:

Partition coefficient: n-octanol/water : log Pow: 3.17 (69.4 °F / 20.8 °C)
pH: 6.1 - 6.3
Method: Partition coefficient (n-octanol/water), Shake-flask method
GLP: yes

2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol:

Partition coefficient: n-octanol/water : log Pow: > 6.5 (73 °F / 23 °C)
pH: 6.4
Method: Partition coefficient (n-octanol/water), HPLC method.

log Pow: 7.3 (77 °F / 25 °C)
Method: other (calculated)

bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate:

Partition coefficient: n-octanol/water : log Pow: 0.35 (77 °F / 25 °C)
pH: 7
Method: Partition coefficient (n-octanol/water), Shake-flask method

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Partition coefficient: n-octanol/water : log Pow: -0.82
Method: other (calculated)

Trimethoxyvinylsilane:

Partition coefficient: n-octanol/water : log Pow: 1.1 (68 °F / 20 °C)

Dibutylbis(pentane-2,4-dionato-O,O')tin:

Partition coefficient: n-octanol/water : Remarks: Study technically not feasible.

stearic acid:

Partition coefficient: n-octanol/water : Remarks: No data available.

log Pow: 8.23
Method: other (measured)

Mobility in soil

No data available

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wht



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

calcium carbonate
Limestone

471-34-1
1317-65-3

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wh



Version 1.1 Revision Date: 01/08/2021 SDS Number: 000000586258 Date of last issue: 06/03/2020
Date of first issue: 06/03/2020

Titanium dioxide 13463-67-7
Di-isononylphthalate 28553-12-0
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich 68515-48-0

New Jersey Right To Know

Limestone 1317-65-3
Titanium dioxide 13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including lead, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL
TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV : American Conference of Governmental Industrial Hygienists -

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wht



Version	Revision Date:	SDS Number:	Date of last issue: 06/03/2020
1.1	01/08/2021	000000586258	Date of first issue: 06/03/2020

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
1910.1000
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-
its for Air Contaminants
29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):
1-A) / TWA value
29 CFR 1910.1000 (Table Z- : Permissible exposure limit
1) / PEL
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

Sikaflex HY 100 white Formerly MSeal NP 100 Wht



Version	Revision Date:	SDS Number:	Date of last issue: 06/03/2020
1.1	01/08/2021	000000586258	Date of first issue: 06/03/2020

Revision Date : 01/08/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN