

PRODUCT DATA SHEET

Sable Marco® Dry Sand

High-quality dry sand

DESCRIPTION

Sable Marco® Dry Sand is a high-quality, well-graded, dry natural sand designed for consistent performance and easy handling. It is ideal for a variety of construction, landscaping, and traction applications where moisture control and workability are essential.

FEATURES

- Dry and ready to use
- Cleaned and screened for consistent grain size
- Easy to handle and spread
- Excellent flowability
- Well-graded for stability and compaction

USES

Sable Marco® Dry Sand is suitable for a variety of applications, including mixing with cement or mortar, backfilling, leveling surfaces, general landscaping, and providing traction on icy walkways or driveways. It can also be used for filling joints between pavers and other general-purpose construction needs where dry material is preferred.

PRODUCT INFORMATION

Packaging	20 kg (44 lb) bag 30 kg (66 lb) bag
Colour	Natural beige
Shelf life	3 years
Storage conditions	Store in a cool, dry place. Keep bags sealed to prevent moisture exposure. Avoid contact with soil or debris.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling,

APPLICATION INSTRUCTIONS

Ensure the surface or area is clean and properly prepared before applying the sand. Spread the Sable Marco® Dry Sand evenly using a shovel, rake, or other suitable tools to achieve the desired coverage. For masonry applications, mix the sand with cement or other binders according to the required ratio to prepare mortar or concrete. For filling joints or leveling surfaces, work the sand into place and compact lightly as needed. In traction applications, apply a thin, even layer to walkways, driveways, or other icy surfaces.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sable Marco Inc
26 Chemin de la Pêche
Pont-Rouge
QC G3H 1C3

PRODUCT DATA SHEET
Sable Marco® Dry Sand
September 2025, Version 01.01
020302040080000044