



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

SECTION 1. IDENTIFICATION

Product name : Sikaflex®-2c NS EZ Mix+ Part B

Other means of identification : No data available

Company name : www.sika.ca
Canada
Pointe-Claire, QC H9R 4A9
601, avenue Delmar
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 4

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 2

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

GHS label elements



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H227 Combustible liquid.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351 Suspected of causing cancer if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
P284 In case of inadequate ventilation wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
xylylene	1330-20-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	$\geq 5 - < 10$
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Acute Tox. 1; H330 Skin Corr. 1C; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335	$\geq 1 - < 5$
ethylbenzene	100-41-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Carc. 2; H351 Eye Irrit. 2A; H319	$\geq 1 - < 5$
4,4'-methylenediphenyl diisocyanate	101-68-8	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317	$\geq 1 - < 5$



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

		STOT SE 3; H335 STOT RE 2; H373	
--	--	------------------------------------	--

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	: irritant effects sensitizing effects Asthmatic appearance Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer if inhaled. May cause damage to organs through prolonged or repeated exposure if inhaled.
Notes to physician	: Treat symptomatically.



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)
- Unsuitable extinguishing media : Water
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid formation of aerosol.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Follow standard hygiene measures when handling chemical products.



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid : Explosives
Oxidizing agents
Poisonous gases
Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	20 ppm	ACGIH
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	TWA	0.005 ppm 0.05 mg/m3	CA AB OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWAEV	0.005 ppm 0.045 mg/m3	CA QC OEL
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	125 ppm 543 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWAEV	0.005 ppm 0.051 mg/m ³	CA QC OEL
		TWA	0.005 ppm	ACGIH

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

Color	:	transparent
Odor	:	aromatic
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/ range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	71 °C (160 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	7.9993 hpa
Relative vapor density	:	No data available
Density	:	1.0193 g/ml (23.3 °C (73.9 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

Volatile organic compounds : 45 g/l
(VOC) content A+B Combined

54 g/l
Sikaflex®-2c NS EZ Mix+ Part A/B + Sikaflex-2c NS TG+
Combined.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4,814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.031 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer if inhaled.

IARC	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
-------------	---	----------

OSHA	Not applicable
-------------	----------------

NTP	Not applicable
------------	----------------

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

xylene:

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia): 1.17 mg/l
Exposure time: 7 d

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA BC OEL / C	:	ceiling limit
CA ON OEL / C	:	Ceiling Limit (C)
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date	:	08/08/2025
Date format	:	mm/dd/yyyy
Person who prepared the SDS	:	R & D of Sika Canada Inc.



Sikaflex®-2c NS EZ Mix+ Part B

Revision Date 08/08/2025

Print Date 08/08/2025

Material number : 597,470

CA / Z8