

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex NP 125 white Formerly MSeal NP
Product code : 000000000050515310

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2B
Carcinogenicity : Category 1B
Specific target organ toxicity - single exposure : Category 3
Specific target organ toxicity - repeated exposure : Category 2 (Auditory organ)
Short-term (acute) aquatic hazard : Category 2
Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black exclamation mark inside, representing a general hazard. The second is a red diamond with a black silhouette of a person and a flame over their head, representing a health hazard.

Signal Word : Danger
Hazard Statements : H320 Causes eye irritation.

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

H315 Causes skin irritation.
H335 May cause respiratory irritation.
H350 May cause cancer.
H373 May cause damage to organs (Auditory organ) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
H401 Toxic to aquatic life.

Precautionary Statements

:

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P201 Obtain special instructions before use.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust or mist.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : adhesive

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
 Date of first issue: 09/22/2020

Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	$\geq 15 - < 20$
ethylbenzene	100-41-4	$\geq 10 - < 15$
Titanium dioxide	13463-67-7	$\geq 5 - < 7$
Silicon dioxide	7631-86-9	$\geq 3 - < 5$
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 oC. It contains a relatively large proportion of saturated hydrocarbons.]	72623-87-1	$\geq 0.3 - < 1$
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 oC. It contains a relatively large proportion of saturated hydrocabons.]	72623-86-0	$\geq 0.3 - < 1$
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	64742-55-8	$\geq 0.3 - < 1$

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
 Date of first issue: 09/22/2020

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	64742-54-7	>= 0.3 - < 1
Distillates (petroleum), hydrotreated light naphthenic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains relatively few normal paraffins.]	64742-53-6	>= 0.3 - < 1
Distillates (petroleum), hydrotreated middle; Gasoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately; 205oC to 400oC (401 oF to 752 oF).]	64742-46-7	>= 0.3 - < 1
bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate	52829-07-9	>= 0.1 - < 0.2

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : After inhalation of dust. Keep patient calm, remove to fresh air, seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : Causes skin and eye irritation.
May cause respiratory irritation.
May cause cancer.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO2)
Dry powder
Foam
Water spray
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Do not breathe dust.
Wear eye/face protection.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Avoid raising dust.
-

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
 Date of first issue: 09/22/2020

- Advice on protection against fire and explosion : Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Keep away from sources of ignition - No smoking. Dust can form an explosive mixture with air.
- Advice on safe handling : Avoid dust formation. Wear suitable protective clothing and eye/face protection. Avoid inhalation of dusts/mists/vapours. Breathing must be protected when large quantities are decanted without local exhaust ventilation.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.
- Materials to avoid : Observe VCI storage rules.
- Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethylbenzene	100-41-4	TWA value	20 ppm	ACGIHTLV
		STEL value	125 ppm 545 mg/m ³	NIOSH
		REL value	100 ppm 435 mg/m ³	NIOSH
		PEL	100 ppm 435 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 435 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	125 ppm 545 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	NIOSH REL
		ST	125 ppm 545 mg/m ³	NIOSH REL
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA P0
		STEL	125 ppm 545 mg/m ³	OSHA P0
		TWA value	100 ppm	ACGIHTLV

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
 Date of first issue: 09/22/2020

		STEL value	150 ppm	ACGIHTLV
		PEL	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 655 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	100 ppm 435 mg/m3	NIOSH
		STEL value	150 ppm 655 mg/m3	NIOSH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
Silicon dioxide	7631-86-9	REL value	6 mg/m3	NIOSH
		TWA value	6 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA value	0.8 mg/m3	29 CFR 1910.1000 (Table Z-3)
		TWA (Dust)	20 Million parti- cles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA (Res- pirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA	6 mg/m3 (Silica)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3	ACGIH

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
 Date of first issue: 09/22/2020

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately; 205oC to 400oC (401 oF to 752 oF).]	64742-46-7		(Titanium dioxide)	
		TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		STEL value (Mist)	10 mg/m3	NIOSH
		REL value (Mist)	5 mg/m3	NIOSH
		PEL (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated light naphthenic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains relatively few normal paraffins.]	64742-53-6	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified; [A	64742-54-7	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
 Date of first issue: 09/22/2020

complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]				
		REL value (Mist)	5 mg/m3	NIOSH
		STEL value (Mist)	10 mg/m3	NIOSH
		PEL (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	64742-55-8	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		STEL value (Mist)	10 mg/m3	NIOSH
		REL value (Mist)	5 mg/m3	NIOSH
		PEL (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
 Date of first issue: 09/22/2020

		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 oC. It contains a relatively large proportion of saturated hydrocabons.]	72623-86-0	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 oC. It contains a relatively large propor-	72623-87-1	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

tion of saturated hydrocarbons.]				
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear a NIOSH approved (or equivalent) particulate respirator if ventilation is inadequate to control dust.

Hand protection

Remarks : Chemical resistant protective gloves Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

Protective measures : Avoid inhalation of dusts.
Wearing of closed work clothing is required additionally to the stated personal protection equipment.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : various colours

Odor : solvent

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

Odor Threshold : No data available

pH : Not relevant of very low solubility

Melting point : No applicable information available.

Boiling point : No applicable information available.

Flash point : does not flash

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Will not burn

Upper explosion limit / Upper flammability limit : No applicable information available.

Lower explosion limit / Lower flammability limit : No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : Heavier than air.

Relative density : 0.98

Density : approx. 8.15 lb/USg (68 °F / 20 °C)

Solubility(ies)

 Water solubility : slightly soluble

 Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : not applicable for mixtures

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

 Viscosity, dynamic : not applicable

 Viscosity, kinematic : not applicable

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

xylene:

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (77 °F / 25 °C)
Method: other (calculated)
GLP: no
Remarks: Information taken from reference works and the literature.

ethylbenzene:

Partition coefficient: n-octanol/water : Pow: 4,170 (68 °F / 20 °C)
log Pow: 3.6 (68 °F / 20 °C)
pH: 7.8
Method: Partition coefficient
GLP: yes

Titanium dioxide:

Partition coefficient: n-octanol/water : Remarks: not applicable

Silicon dioxide:

Partition coefficient: n-octanol/water : Remarks: not applicable

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 oC. It contains a relatively large proportion of saturated hydrocarbons.]:

Partition coefficient: n- : log Pow: 7.868
octanol/water Method: other (calculated)

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]:

Partition coefficient: n- : Pow: > 3.5
octanol/water

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]:

Partition coefficient: n- : log Pow: approx. 7 - 25
octanol/water Method: other (calculated)

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately; 205oC to 400oC (401 oF to 752 oF).]:

Partition coefficient: n- : Remarks: No data available.
octanol/water

bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate:

Partition coefficient: n- : log Pow: 0.35 (77 °F / 25 °C)
octanol/water pH: 7
Method: Partition coefficient (n-octanol/water), Shake-flask method

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemical or used container.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

xylene 1330-20-7

The following components are subject to reporting levels established by SARA Title III, Section 313:

ethylbenzene 100-41-4

US State Regulations

Pennsylvania Right To Know

ethylbenzene	100-41-4
xylene	1330-20-7
Silicon dioxide	7631-86-9
Titanium dioxide	13463-67-7

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

New Jersey Right To Know

ethylbenzene	100-41-4
xylene	1330-20-7
Titanium dioxide	13463-67-7
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	64742-54-7

California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer, and ethyleneglycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version 1.0 Revision Date: 09/22/2020 SDS Number: 000000261034 Date of last issue: -
Date of first issue: 09/22/2020

29 CFR 1910.1000 (Table Z-3)	:	OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	:	American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	:	NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / STEL value	:	Short Term Exposure Limit (STEL):
29 CFR 1910.1000 (Table Z-1-A) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	:	Permissible exposure limit
29 CFR 1910.1000 (Table Z-3) / TWA value	:	Time Weighted Average (TWA):
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIHTLV / STEL value	:	Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
NIOSH / REL value	:	Recommended exposure limit (REL):
NIOSH / STEL value	:	Short Term Exposure Limit (STEL):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC

SAFETY DATA SHEET

Sikaflex NP 125 white Formerly MSeal NP



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/22/2020	000000261034	Date of first issue: 09/22/2020

- No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/22/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN