

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

---

### SECTION 1. IDENTIFICATION

Product name : Sikalastic-631 Formerly MSeal 631  
Product code : 000000000056255673

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC  
Address : 201 POLITO AVE  
Lyndhurst NJ 07071  
Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

No need for classification according to GHS criteria for this product.

#### GHS label elements

The product does not require a hazard warning label in accordance with GHS criteria.

#### Other hazards

No data available.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Asphalt	8052-42-4	>= 25 - < 50
Kaolin	1332-58-7	>= 15 - < 20

---

### SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.  
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).  
Immediately remove contaminated clothing.  
Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical attention.

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

---

- If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Immediately wash thoroughly with soap and water, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
- Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray  
Foam
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
sulfur oxides
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.  
Wear eye/face protection.  
If exposed to high vapour concentration, leave area immediately.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid aerosol formation.  
Avoid inhalation of mists/vapours.  
Avoid skin contact.  
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.  
  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep container tightly closed in a cool, well-ventilated place.  
Avoid all sources of ignition: heat, sparks, open flame.
- Materials to avoid : No applicable information available.  
  
No materials to be especially mentioned.
- Recommended storage temperature : 41 °F / 5 °C
- Further information on storage stability : Minimum storage temperature:

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Kaolin	1332-58-7	TWA value	2 mg/m <sup>3</sup>	ACGIHTLV

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
 Date of first issue: 09/21/2020

		(Respirable fraction)		
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Asphalt	8052-42-4	TWA value (Inhalable fraction)	0.5 mg/m3 (benzene solubles)	ACGIHTLV
		Ceil_Time (fumes/smoke)	5 mg/m3	NIOSH
		TWA value (Inhalable fume)	0.5 mg/m3 (benzene solubles)	ACGIHTLV
		TWA (Fume, inhalable fraction)	0.5 mg/m3 (benzene soluble aerosol)	ACGIH
		C (Fumes)	5 mg/m3	NIOSH REL

**Engineering measures** : No applicable information available.

**Personal protective equipment**

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Hand protection

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

---

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Protective measures : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : General industrial hygiene practice.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous, liquid

Color : brown

Odor : of hydrocarbons

Odor Threshold : No data available

pH : 5.0 - 7.0

Melting point : No applicable information available.

Boiling point : 212 °F / 100 °C

Flash point : > 212 °F / > 100 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper flammability limit : not applicable

Lower explosion limit / Lower flammability limit : not applicable

Vapor pressure : 60 mmHg (100 °F / 38 °C)

Relative vapor density : No data available.

---

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

---

Density : 1.0 - 1.2 g/cm<sup>3</sup> (68 °F / 20 °C)

Bulk density : not applicable

Solubility(ies)  
Water solubility : No data available

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No data available.

Autoignition temperature : > 400 °F / > 204 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic :

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive  
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Stable under recommended storage conditions.  
No hazards to be specially mentioned.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon oxides  
Sulfur compounds

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

---

**Product:**

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization**

**Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

**Product:**

Remarks : No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

---

### Bioaccumulative potential

#### Components:

##### Asphalt:

Partition coefficient: n-octanol/water : Remarks: not applicable

##### Kaolin:

Partition coefficient: n-octanol/water : Remarks: not applicable

#### Mobility in soil

No data available

#### Other adverse effects

#### Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

## SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

---



# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

### US State Regulations

#### Pennsylvania Right To Know

Kaolin 1332-58-7  
Asphalt 8052-42-4

#### New Jersey Right To Know

Kaolin 1332-58-7  
Asphalt 8052-42-4

#### California Prop. 65

WARNING: This product can expose you to chemicals including Asphalt, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


#### The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory


## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000 1-A)

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version 1.0      Revision Date: 09/21/2020      SDS Number: 000000298958      Date of last issue: -  
Date of first issue: 09/21/2020

29 CFR 1910.1000 (Table Z-1)	:	OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	:	American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	:	NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	:	Permissible exposure limit
ACGIH / TWA	:	8-hour, time-weighted average
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
NIOSH / Ceil_Time	:	Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	:	Recommended exposure limit (REL):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;

# SAFETY DATA SHEET

## Sikalastic-631 Formerly MSeal 631



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/21/2020	000000298958	Date of first issue: 09/21/2020

---

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/21/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN