

PRODUCT DATA SHEET

Sable Marco® Screening

Fine limestone screening for leveling and joint filling

DESCRIPTION

Sable Marco® Screening is a finely crushed limestone screening, with a uniform particle size that provides excellent compaction. It is ideal for creating a solid, level base under interlocking pavers, patio slabs, and driveways. Sable Marco® Screening also helps minimize weed growth and the establishment of ants between paving units, ensuring a stable and low-maintenance surface.

USES

Sable Marco® Screening is used to create a stable, level base for interlocking pavers, patio slabs, and driveways. It can also be used as a joint filler between paving units to improve stability and reduce the growth of weeds or the presence of ants.

FEATURES

- High-quality, finely crushed limestone screening
- Uniform particle size for excellent compaction
- Ideal for creating a level, stable base under pavers, patio slabs, and driveways
- Helps reduce weed growth and ant colonies between paving units
- Easy to spread and compact for consistent results

PRODUCT INFORMATION

Packaging	20 kg (44 lb) bag / 30 kg (66 lb) bag
Shelf life	3 years
Storage conditions	Store in a cool, dry place. Keep bags sealed to prevent moisture exposure and surface discoloration. Avoid contact with soil or debris.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Base preparation for pavers, patio slabs, or drive-ways: Excavate and level the area to the required depth, ensuring the subgrade is free of debris. Spread Sable Marco® Screening evenly to create a smooth, level bedding layer. Lightly compact or screed the screenings to provide a stable, uniform surface for placing pavers or slabs.

Joint filling between paving units: After positioning interlocking pavers, patio slabs, or similar units, use Sable Marco® Screening to fill the joints evenly. Sweep into gaps, then lightly compact or vibrate to ensure the screenings settle.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sable Marco Inc
26 Chemin de la Pêche
Pont-Rouge
QC G3H 1C3