

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

SECTION 1. IDENTIFICATION

Product name : Sikadur F 2000 Part B Formerly MBrace F 2000 PTB
Product code : 000000000051683680

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Corrosive to Metals : Category 1
Skin corrosion/irritation : Category 1A
Serious eye damage/eye irritation : Category 1
Skin sensitization : Category 1A
Reproductive toxicity : Category 1B
Short-term (acute) aquatic hazard : Category 3
Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : Three GHS hazard pictograms are shown in red diamond shapes. From left to right: 1. Corrosive to Metals (C1), showing a hand being corroded by a liquid. 2. Health Hazard (H317), showing a person with a starburst on their chest. 3. Skin Sensitization (H335), showing a person with a starburst on their chest.

Signal Word : Danger
Hazard Statements : H317 May cause an allergic skin reaction.

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

H360D May damage the unborn child.
H314 Causes severe skin burns and eye damage.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P260 Do not breathe dust or mist.
P273 Avoid release to the environment.
P202 Do not handle until all safety precautions have been read and understood.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/ doctor/
P303 + P361 + P352 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 15 - < 20
Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number	25068-38-6	>= 10 - < 15

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

average molecular weight <= 700)		
Trimethylhexane-1,6-diamine	25620-58-0	>= 10 - < 15
Benzyl alcohol	100-51-6	>= 7 - < 10
imidazole	288-32-4	>= 1 - < 3
4-nonylphenol, branched	84852-15-3	>= 0 - < 0.1

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
Immediately remove contaminated clothing.
Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Keep patient calm, remove to fresh air, seek medical attention.
Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do NOT induce vomiting.
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0	Revision Date: 09/30/2020	SDS Number: 000000244190	Date of last issue: - Date of first issue: 09/30/2020
----------------	------------------------------	-----------------------------	--

Clean mouth with water and drink afterwards plenty of water.
Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye damage.
May damage the unborn child.
Causes severe burns.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
Store protected against freezing.
- Materials to avoid : Observe VCI storage rules.
- Recommended storage temperature : 32 °F / 0 °C
- Further information on storage stability : Minimum storage temperature:

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Kaolin	1332-58-7	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		REL value (Respirable)	5 mg/m3	NIOSH

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
 Date of first issue: 09/30/2020

		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) respirator as necessary.

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures

: Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: pasty

Color

: gray

Odor

: product specific

Odor Threshold

: No data available

pH

: neutral to slightly alkaline

Melting point

: No applicable information available.

Boiling point

: 401 °F / 205 °C

Flash point

: negligible

Evaporation rate

: not determined

Flammability (solid, gas)

: not highly flammable

Upper explosion limit / Upper flammability limit

: No applicable information available.

Lower explosion limit / Lower

: No applicable information available.

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0	Revision Date: 09/30/2020	SDS Number: 000000244190	Date of last issue: - Date of first issue: 09/30/2020
----------------	------------------------------	-----------------------------	--

flammability limit

Vapor pressure : No data available

Relative vapor density : not determined

Relative density : No applicable information available.

Density : approx. 1.14 g/cm³ (68 °F / 20 °C)

Solubility(ies)

 Water solubility : emulsifiable (68 °F / 20 °C)

 Solubility in other solvents : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

 Viscosity, dynamic : not determined

 Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive
Not explosive

Oxidizing properties : not fire-propagating

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Oxidizing agents
strong alkalis
Acids

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0	Revision Date: 09/30/2020	SDS Number: 000000244190	Date of last issue: - Date of first issue: 09/30/2020
----------------	------------------------------	-----------------------------	--

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Can sensitize the skin and/or respiratory tract of allergic persons.

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

Aspiration toxicity

Not classified based on available information.

Further information

Product:

- Remarks : According to our knowledge the product can cause damage to health, corrosive burns and sensitization. On the basis of results of animal tests, a risk of foetal damage must be considered probable. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.
- Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.
- Remarks : No data available
-

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

4-nonylphenol, branched:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available.

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Partition coefficient: n-octanol/water : log Pow: 0.99 (73 °F / 23 °C)
pH: 6.3
Method: Partition coefficient
GLP: no

Trimethylhexane-1,6-diamine:

Partition coefficient: n-octanol/water : log Pow: 1.60 (77 °F / 25 °C)
Method: other (calculated)

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

Remarks: The data refers to the undissociated form of the substance.

imidazole:

Partition coefficient: n-octanol/water : log Pow: -0.02 (77 °F / 25 °C)
Method: Partition coefficient (n-octanol/water), Shake-flask method
GLP: no

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(ALIPHATIC AMINE)
Class : 8
Packing group : III
Labels : 8

IATA-DGR

UN/ID No. : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(ALIPHATIC AMINE)
Class : 8

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

Packing group : III
Labels : Corrosive
Packing instruction (cargo aircraft) : 856
Packing instruction (passenger aircraft) : 852

IMDG-Code

UN number : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(ALIPHATIC AMINE)
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(ALIPHATIC AMINE)
Class : 8
Packing group : III
Labels : CORROSIVE
ERG Code : 154
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

Benzyl alcohol	100-51-6
carbon black	1333-86-4
talc	14807-96-6
listed	

New Jersey Right To Know

carbon black	1333-86-4
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2
talc	14807-96-6
Trimethylhexane-1,6-diamine	25620-58-0
listedSpecial Hazard.	

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version 1.0 Revision Date: 09/30/2020 SDS Number: 000000244190 Date of last issue: -
Date of first issue: 09/30/2020

California Prop. 65

WARNING: This product can expose you to chemicals including carbon black, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIH TLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/30/2020	000000244190	Date of first issue: 09/30/2020

29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/30/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensur-

SAFETY DATA SHEET

Sikadur F 2000 Part B Formerly MBrace F 2000 PTB



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/30/2020	000000244190	Date of first issue: 09/30/2020

ing the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN