

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0 Revision Date: 08/28/2021 SDS Number: 000000939939 Date of last issue: -
Date of first issue: 08/28/2021

SECTION 1. IDENTIFICATION

Product name : Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey
Product code : 00000000050107341
Other means of identification : Ucrete TCCS Part A light grey

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use


Recommended use : Floor coating
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2
Skin sensitization : Category 1
Hazardous to the aquatic environment - acute hazard : Category 3
Hazardous to the aquatic environment - chronic hazard : Category 3

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H402 Harmful to aquatic life.

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0 Revision Date: 08/28/2021 SDS Number: 000000939939 Date of last issue: -
Date of first issue: 08/28/2021

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

- P280 Wear protective gloves.
- P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
- P273 Avoid release to the environment.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

- P302 + P352 IF ON SKIN: Wash with plenty of water.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
- P332 + P313 If skin irritation occurs: Get medical advice/ attention.
- P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

- P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Blend based on:
methacrylates
acrylates

Components

Chemical name	CAS-No.	Concentration (% w/w)
Silicon dioxide	7631-86-9	>= 20 - < 30
Kaolin	1332-58-7	>= 5 - < 10
(5-ethyl-1,3-dioxan-5-yl)methyl acrylate	66492-51-1	>= 5 - < 10
aliphatic urethane acrylate	82339-26-2	>= 5 - < 10
Titanium dioxide	13463-67-7	>= 5 - < 10
Trimethylolpropane trimethacrylate	3290-92-4	>= 1 - < 5
Mica group minerals	12001-26-2	>= 1 - < 5
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 1 - < 5
Paraffin waxes and Hydrocarbon waxes	8002-74-2	>= 1 - < 5
Ethoxylated 4-methylaniline	103671-44-9	>= 0.1 - < 1
Trimethylolpropane triacrylate	15625-89-5	>= 0.1 - < 1

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0	Revision Date: 08/28/2021	SDS Number: 000000939939	Date of last issue: - Date of first issue: 08/28/2021
----------------	------------------------------	-----------------------------	--

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation. May cause an allergic skin reaction.
- Notes to physician : Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
- Further information : The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0 Revision Date: 08/28/2021 SDS Number: 000000939939 Date of last issue: -
Date of first issue: 08/28/2021

Special protective equipment : Wear a self-contained breathing apparatus.
for fire-fighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wear eye/face protection.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Pick up with suitable appliance and dispose of.
Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : The product is neither self-ignitable, nor an explosion hazard, nor does it promote fires.

Advice on safe handling : Avoid inhalation of dusts/mists/vapours.
Avoid skin contact.
Ensure adequate ventilation.
No special measures necessary provided product is used correctly.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Silicon dioxide	7631-86-9	REL value	6 mg/m ³	NIOSH
		TWA value	6 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA value	0.8 mg/m ³	29 CFR 1910.1000 (Table Z-3)
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version
1.0

Revision Date:
08/28/2021

SDS Number:
000000939939

Date of last issue: -
Date of first issue: 08/28/2021

			(Silica)	
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA	6 mg/m3 (Silica)	NIOSH REL
Kaolin	1332-58-7	TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Trimethylolpropane trimethacrylate	3290-92-4	TWA	1 mg/m3	US WEEL
Mica group minerals	12001-26-2	TWA value (Respirable fraction)	3 mg/m3	ACGIHTLV
		REL value (Respirable)	3 mg/m3	NIOSH
		TWA value (Respirable dust)	3 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Respirable particulate matter)	0.1 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m3	NIOSH REL
		TWA (respir-	3 mg/m3	OSHA P0

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0 Revision Date: 08/28/2021 SDS Number: 000000939939 Date of last issue: -
Date of first issue: 08/28/2021

		able dust fraction)		
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Paraffin waxes and Hydrocarbon waxes	8002-74-2	TWA value (fumes/smoke)	2 mg/m ³	ACGIHTLV
		REL value (fumes/smoke)	2 mg/m ³	NIOSH
		TWA value (fumes/smoke)	2 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Fumes)	2 mg/m ³	ACGIH
		TWA (Fumes)	2 mg/m ³	NIOSH REL
		TWA (Fumes)	2 mg/m ³	OSHA P0
Trimethylolpropane triacrylate	15625-89-5	TWA	1 mg/m ³	US WEEL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
Use NIOSH approved respiratory protection.

Hand protection

Remarks : Chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0	Revision Date: 08/28/2021	SDS Number: 000000939939	Date of last issue: - Date of first issue: 08/28/2021
----------------	------------------------------	-----------------------------	--

care agents applied.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: light gray
Odor	: acrylic-like
Odor Threshold	: not determined
pH	: ca. 6
Melting point	: not determined
Boiling point	: No data available.
Flash point	: 212 °F / 100 °C
Evaporation rate	: not determined
Flammability (liquids)	: The product is not flammable.
Self-ignition	: not self-igniting
Upper explosion limit / Upper flammability limit	: Not applicable
Lower explosion limit / Lower flammability limit	: Not applicable
Vapor pressure	: not determined
Relative vapor density	: not determined
Relative density	: No data available
Density	: 1.430 g/cm ³ (68 °F / 20 °C)
Solubility(ies)	
Water solubility	: not determined
Solubility in other solvents	: No data available
Partition coefficient: n-	: not applicable for mixtures

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0	Revision Date: 08/28/2021	SDS Number: 000000939939	Date of last issue: - Date of first issue: 08/28/2021
----------------	------------------------------	-----------------------------	--

octanol/water

Autoignition temperature : Not applicable

Decomposition temperature : Not applicable

Viscosity

Viscosity, dynamic : 5,600 mPa.s
Method: N-114; Brookfield Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : not fire-propagating

Sublimation point : No data available

Molecular weight : No data available

Metal corrosion rate : Corrosive effects to metal are not anticipated.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0 Revision Date: 08/28/2021 SDS Number: 000000939939 Date of last issue: -
Date of first issue: 08/28/2021

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans	
	Trimethylolpropane triacrylate	15625-89-5

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0 Revision Date: 08/28/2021 SDS Number: 000000939939 Date of last issue: -
Date of first issue: 08/28/2021

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Observe national and local legal requirements. Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal selected. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version 1.0 Revision Date: 08/28/2021 SDS Number: 000000939939 Date of last issue: -
Date of first issue: 08/28/2021

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

Silicon dioxide	7631-86-9
Kaolin	1332-58-7
Titanium dioxide	13463-67-7
Mica group minerals	12001-26-2
Distillates (petroleum), hydrotreated middle	64742-46-7
Paraffin waxes and Hydrocarbon waxes	8002-74-2
n-Butyl acetate	123-86-4
butan-2-ol	78-92-2
toluene	108-88-3
cyclohexane	110-82-7

New Jersey Right To Know

Kaolin	1332-58-7
Titanium dioxide	13463-67-7
Mica group minerals	12001-26-2
Paraffin waxes and Hydrocarbon waxes	8002-74-2

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains one or more components listed on the Canadian NDSL. All other components are on the Canadian DSL.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey




Version
1.0

Revision Date:
08/28/2021


SDS Number:
000000939939

Date of last issue: -
Date of first issue: 08/28/2021

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-3) / TWA value : Time Weighted Average (TWA):
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average
- US WEEL / TWA : 8-hr TWA

SAFETY DATA SHEET

Sika Ucrete TCCS PTA light grey Formerly Ucrete TCCS PTA light grey



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/28/2021	00000939939	Date of first issue: 08/28/2021

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/28/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN