

## PRODUCT DATA SHEET

# Testproduct Arvato Construction

2-part primer based on reactive acrylic resin

### DESCRIPTION

Testproduct Arvato Construction is a two part, low-viscosity, fast curing primer based on reactive acrylic resins for the Sikafloor® Pronto Modular System.

### USES

The Product is used as a:

- Adherent primer on concrete and cement substrates

Please note:

- The Product may only be used by experienced professionals.

### FEATURES

- Practical and safe
- Good penetrating properties as a standard primer
- Very fast curing even at low temperatures
- Solvent free

### CERTIFICATES AND TEST REPORTS

- CE Marking and Declaration of Performance to EN 13813:2002 — Screed material and floor screeds — Synthetic resin screed material
- Migration Behaviour EN 1186, EN 13130, CEN/TS 14234, Sikafloor® Pronto, ISEGA, Certificate No. 51188 U 20

### PRODUCT INFORMATION

<b>Packaging</b>	Refer to the individual Product Data Sheets
<b>Shelf life</b>	Refer to the individual Product Data Sheets
<b>Storage conditions</b>	Refer to the individual Product Data Sheets

### TECHNICAL INFORMATION

### SYSTEM INFORMATION

# **BASIS OF PRODUCT DATA APPLICATION INFORMATION**

---

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

## **LOCAL RESTRICTIONS**

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## **ECOLOGY, HEALTH AND SAFETY**

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## **LEGAL NOTES**

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: [www.sika.ca](http://www.sika.ca)