



PRODUCT DATA SHEET

SikaInject® AC-20 DE

Accelerator for polyurethane resins (formerly TPH.® PUR-O-STOP FS-C)

PRODUCT DESCRIPTION

SikaInject® AC-20 DE is an accelerator for various Sika® polyurethane-based injection resins, such as:

- SikaInject®-201 DE
- SikaInject®-210 DE
- SikaInject®-216 DE

Contact Sika Canada for compatibility with other injection resins.

WHERE TO USE

SikaInject® AC-20 DE may only be used by experienced professionals.

Accelerates the base resin where a short potlife is needed, such as:

- In flowing water applications
- In cold season
- In cold water applications

PRODUCT INFORMATION

Packaging	4.5 kg
Appearance / Colour	Liquid / Colourless
Shelf Life	12 months from date of production
Storage Conditions	Store in original, unopened and undamaged sealed packaging, in dry conditions, at temperatures between 15 °C and 25 °C.
Density	~1.03 kg/L (DIN EN ISO 2811-1)
Viscosity	~120 cps (DIN EN ISO 2555)

CHARACTERISTICS / ADVANTAGES

- Versatile accelerator, suitable for various SikaInject® PU resins
- Shortens potlife
- Increase of efficiency
- Reduction of product loss (for ex. in flowing water applications)

APPROVALS / CERTIFICATES

- German General Building Inspectorate Approval for curtain grouting, AbZ, DIBT Berlin

APPLICATION INFORMATION

Mixing Ratio

Measure and add small quantities of Sikalject® AC-20 DE into part A of the respective Sikalject®-PU Injection Resin and mix homogeneously (no streaks). The exact quantity (pot life table) can be found in the technical data sheet for the corresponding injection resin.

BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

ENVIRONMENT, HEALTH & SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca

Sika Canada Inc.

Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9
1-800-933-SIKA
www.sika.ca

Other locations

Boisbriand (Quebec)
Brantford; Cambridge;
Sudbury; Toronto (Ontario)
Edmonton (Alberta)
Surrey (British Columbia)

Product Data Sheet

Sikalject® AC-20 DE
February 2026, Version 01.01
020707010020000057

SikaljectAC-20DE-en-CA-(02-2026)-1-1.pdf

