



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sika® Teak Oil**REVISION DATE: January 15th, 2015

USAGE: OIL BLEND FOR TEAK

MANUFACTURER/SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666**

TDG CLASSIFICATION: Not regulated

WHMIS Classification: B3, D2B

UN NUMBER: Not established

Class: Not applicable

Packaging Group:

Not applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
Light petroleum distillate	60-100	200 mg/m ³ ACGIH	64742-47-8	Not Available	Not Available
Hydrogenated middle distillate (petroleum)	15-40	Not Available	64742-46-7	Not Available	Not Available

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid
 Appearance and Odor: Light brown with characteristic odor
 Odor Threshold: Not Available
 Evaporation Rate: Not Available
 Vapor Density: Not Available
 Vapor Pressure: Not Available

Boiling Point: Not Available
 Freezing Point: Not Available
 Density: 0.8 g/ml @ 20°C
 Water Solubility: Insoluble
 pH: Not Established
 % volatility: < 80
 Water/Oil Distribution: Not Established



PRODUCT: Sika® Teak Oil

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability:	Yes	TDG inflammability Class:	No
If Yes, under what conditions:	fire, spark	Flammable upper limits (% vol.):	Not Available
Extinguishing methods:	Foam, dry chemical products, CO ₂ , water hose.	Flammable lower limits (% vol.):	Not Available
Special Methods:	Firefighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.	Flash Point (method used):	65°C
		Auto-ignition temperature:	> 294°C
		Dangerous Combustion Products:	Carbon oxides.
		Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY

Chemical stability:	Yes.	Dangerous decomposition products:	Carbon oxides.
If not, under what conditions:			
Incompatibility with other material:	Yes	Polymerization Risks:	Will not occur
If Yes, which ones:	Strong oxidizer.		



PRODUCT: Sika® Teak Oil

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eyes irritations.

Skin: May be irritating to the skin, may cause sensitization. May cause skin's fat and drying of the skin. May cause dermatitis and allergic reactions.

Inhalation: May irritate the lungs, may cause an allergic reaction. May cause headaches, dizziness, and nausea. May cause central nervous system depression.

Ingestion: May cause irritation to the gastric-intestinal system. May cause vomiting, dizziness, diarrhea.

Carcinogenicity: Not Established

Toxic effects on reproduction: Not Established

Teratogenicity: Not Established

Mutagenicity: Not Established

Product with synergistic effects: Not Established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. Excessive inhalation of vapor may cause death.



PRODUCT: Sika® Teak Oil

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: NIOSH approved mask with organic vapor cartridge if the vapors are exceeding the TLV.

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sika® Teak Oil

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of soap and water.
Throw away shoes that were soiled on the inside.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water for several minutes to ensure a proper wash.
Consult a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.