

# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

### **SECTION 1. IDENTIFICATION**

Product name : SikaThorocoat-200 pastel tint base Formerly MProtect HB 200

pastel

Product code : 00000000051713996

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

## **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Carcinogenicity (Inhalation) : 1A

- repeated exposure

2 (Kidney)

Short-term (acute) aquatic

Specific target organ toxicity

hazard

: 3

**GHS** label elements

Hazard pictograms

Signal Word : Danger

Hazard Statements : H350 May cause cancer.

H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure. H402 Harmful to aquatic life.

Precautionary Statements : Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust or mist. P273 Avoid release to the environment.

Response:

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

P314 Get medical advice/ attention if you feel unwell.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 10 - < 50
Titanium dioxide	13463-67-7	>= 10 - < 25
ethyleneglycol	107-21-1	>= 1 - < 3
Isobutyric acid, monoester with 2,2,4-	25265-77-4	>= 0 - < 3
trimethylpentane-1,3-diol		
Mica-group minerals	12001-26-2	>= 1 - < 3
Quartz (SiO2)	14808-60-7	>= 0.1 - < 1
Poly(oxy-1,2-ethanediyl), .alpha	9036-19-5	>= 0.1 - < 0.2
[(1,1,3,3-tetramethylbutyl)phenyl]-		
.omegahydroxy-		
diuron	330-54-1	>= 0 - < 0.2
carbendazim	10605-21-7	>= 0 - <= 0.1
3-iodo-2-propynyl butylcarbamate; 3-	55406-53-6	>= 0 - < 0.1
iodoprop-2-yn-1-yl butylcarbamate		

### **SECTION 4. FIRST AID MEASURES**

General advice : Remove contaminated clothing.

Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash thoroughly with soap and water

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open.

Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May cause cancer.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.



# SikaThorocoat-200 pastel tint base Formerly **MProtect HB 200 pastel**

Version SDS Number: Date of last issue: -Revision Date:

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Prevent product from entering drains. **Environmental precautions** 

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Keep container tightly closed in a dry and well-ventilated Conditions for safe storage

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid No applicable information available.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components CA	AS-No.	Value type (Form of	Control parameters / Permissible	Basis
---------------	--------	------------------------	----------------------------------	-------



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

		exposure)	concentration	
ethyleneglycol	107-21-1	TWA value (Vapor frac-	25 ppm	ACGIHTLV
		tion)		
		STÉL value	50 ppm	ACGIHTLV
		(Vapor frac-	''	
		tion)		
		STEL value	10 mg/m3	ACGIHTLV
		(Aerosol,		7.00
		inhalable.)		
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Va-	50 ppm	ACGIH
		por)	оо ррш	Addin
		STEL (Inhal-	10 mg/m3	ACGIH
		able fraction,	10 mg/ms	ACGIH
		Aerosol only)	50 nn	OCHA DO
			50 ppm	OSHA P0
-liver -	200 54 4	TMA	125 mg/m3	ACCULITIA/
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR
				1910.1000
				(Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
Limestone	1317-65-3	REL value	5 mg/m3	NIOSH
		(Respirable)		
		REL value	10 mg/m3	NIOSH
		(Total)		
		PEL (Respir-	5 mg/m3	29 CFR
		able fraction)		1910.1000
				(Table Z-1)
		PEL (Total	15 mg/m3	29 CFR
		dust)		1910.1000
		,		(Table Z-1)
		TWA value	5 mg/m3	29 CFR
		(Respirable		1910.1000
		fraction)		(Table Z-1-A)
		TWA value	15 mg/m3	29 CFR
		(Total dust)		1910.1000
				(Table Z-1-A)
		TWA (total	15 mg/m3	OSHA Z-1
		dust)	3,	
		TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction)	5g,	00
		TWA (Total	15 mg/m3	OSHA P0
		dust)		
		TWA (respir-	5 mg/m3	OSHA P0
		able dust		
		fraction)		
		TWA (Res-	5 mg/m3	NIOSH REL



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

		pirable)	(Calcium car- bonate)	
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Mica-group minerals	12001-26-2	TWA value (Respirable fraction)	3 mg/m3	ACGIHTLV
		REL value (Respirable)	3 mg/m3	NIOSH
		TWA value (Respirable dust)	3 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
		TWA (Dust)	20 Million parti- cles per cubic foot	OSHA Z-3
		TWA (Res- pirable)	3 mg/m3	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m3	OSHA P0
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: 1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
PEL (respir- able)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

**Engineering measures** : No applicable information available.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) respirator as neces-

sary.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

Color : pigmented

pH : neutral to slightly alkaline (as an emulsion)

Boiling point : 379 - 401 °F / 193 - 205 °C

Flash point : 200.1 °F / 93.4 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not highly flammable

Method: derived from flash point

Upper explosion limit / Upper

flammability limit

15.3 %(V)

Lower explosion limit / Lower

flammability limit

3.2 %(V)

Vapor pressure : No applicable information available.

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 1.600 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : partly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

not applicable

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

Sublimation point : No applicable information available.

Molecular weight : No data available.

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

carbon oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

Not classified based on available information.

#### **Product:**

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

# Germ cell mutagenicity

Not classified based on available information.



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

## Carcinogenicity

May cause cancer.

#### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

# **Product:**

Remarks : The product has not been tested. The statements on toxicolo-

gy have been derived from the properties of the individual

components.

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

#### **Product:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

# Persistence and degradability

#### **Components:**

# Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:

Biodegradability : aerobic

Inoculum: activated sludge, domestic, non-adapted

Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

Method: Modified OECD-Screening-Test.

## **Bioaccumulative potential**

# **Components:**

#### Titanium dioxide:

Partition coefficient: n-

octanol/water

: Remarks: not applicable

# ethyleneglycol:



# SikaThorocoat-200 pastel tint base Formerly **MProtect HB 200 pastel**

Version SDS Number: Date of last issue: -Revision Date:

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

Partition coefficient: n-

log Pow: approx. -1.36 (73 °F / 23 °C) Method: Calculation Hansch/Leo octanol/water

GLP: no data

Remarks: Information taken from reference works and the

literature.

Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol:

Partition coefficient: nlog Pow: 3.2 (77 °F / 25 °C)

octanol/water pH: 7

Method: Partition coefficient (n-octanol/water), HPLC method.

GLP: no

Quartz (SiO2):

Partition coefficient: n-

octanol/water

Remarks: not applicable

Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:

Bioaccumulation Remarks: Accumulation in organisms is not to be expected.

carbendazim:

Partition coefficient: n-

octanol/water

Pow: approx. 36 (72 °F / 22 °C) log Pow: approx. 1.6 (72 °F / 22 °C)

pH: 5

Pow: approx. 59 (72 °F / 22 °C) log Pow: approx. 1.77 (72 °F / 22 °C)

pH: 7

Pow: approx. 81 (72 °F / 22 °C) log Pow: approx. 1.9 (72 °F / 22 °C)

pH: 9

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate:

log Pow: 2.81 (77 °F / 25 °C) Partition coefficient: n-

octanol/water Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: yes

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

#### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

**UNRTDG** 

Not regulated as a dangerous good

**IATA-DGR** 

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**Domestic regulation** 

**49 CFR** 

Not regulated as a dangerous good

## **SECTION 15. REGULATORY INFORMATION**

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

ethyleneglycol 107-21-1

# **US State Regulations**

# Pennsylvania Right To Know

 ethyleneglycol
 107-21-1

 Limestone
 1317-65-3

 Mica-group minerals
 12001-26-2

 Titanium dioxide
 13463-67-7

 ethylene oxide
 75-21-8

 propylene oxide
 75-56-9

 1,4-dioxane
 123-91-1

### **New Jersey Right To Know**



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version 1.0	Revision Date: 07/21/2020	SDS Number: 000000260721	Date of last issue: - Date of first issue: 0	7/21/2020
	Baseoil — unspecit bons obtained by the in the presence of a ing carbon number through C50 and presence of the country of the	Is  Im), hydrotreated heaver fied; [A complex combined in a petroleum frague a catalyst. It consists of a predominantly in the roduces a finished oil of 40 oC). It contains related to the second in	nation of hydrocar- ction with hydrogen f hydrocarbons hav- range of C20 of at least 100 SUS	107-21-1 1317-65-3 12001-26-2 13463-67-7 14808-60-7 14808-60-7 64742-52-5

### California Prop. 65

WARNING: This product can expose you to chemicals including ethylene oxide, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## The ingredients of this product are reported in the following inventories:


**TSCA** 

All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

### **SECTION 16. OTHER INFORMATION**


## **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations



# SikaThorocoat-200 pastel tint base Formerly **MProtect HB 200 pastel**

Version SDS Number: Date of last issue: -Revision Date:

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1000 (Table Z-OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

29 CFR 1910.1001-1050 OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

**ACGIHTLV** American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH USA. NIOSH Recommended Exposure Limits **NIOSH REL** 

OSHA Specifically Regulated Chemicals/Carcinogens OSHA CARC USA. OSHA - TABLE Z-1 Limits for Air Contaminants -OSHA P0

1910.1000

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- :

1-A) / TWA value

Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z- :

Permissible exposure limit 1) / PEL

29 CFR 1910.1000 (Table Z- : 3) / TWA value

Time Weighted Average (TWA):

29 CFR 1910.1001-1050 /

**OSHA Action level:** 

OSHA Action level

29 CFR 1910.1001-1050 / Time Weighted Average (TWA):

TWA value

8-hour, time-weighted average ACGIH / TWA Short-term exposure limit ACGIH / STEL

Short Term Exposure Limit (STEL): ACGIHTLV / STEL value ACGIHTLV / TWA value Time Weighted Average (TWA): NIOSH / REL value Recommended exposure limit (REL):

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL Permissible exposure limit (PEL) 8-hour time weighted average OSHA P0 / TWA

OSHA P0 / C Ceiling limit

OSHA Z-1 / TWA 8-hour time weighted average OSHA Z-3 / TWA 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dan-



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

gerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 07/21/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.



# SikaThorocoat-200 pastel tint base Formerly MProtect HB 200 pastel

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/21/2020 000000260721 Date of first issue: 07/21/2020

US / EN