

**SECTION 1. IDENTIFICATION**

Product name	:	Sikagard®-150 N Duroplast® Part B
Other means of identification	:	No data available
Company name	:	www.sika.ca Canada Pointe-Claire, QC H9R 4A9 601, avenue Delmar Sika Canada Inc.
Telephone	:	(514) 697-2610 / 1 (800) 933-7452
Telefax	:	(514) 694-2792
E-mail address	:	ehs@ca.sika.com
Emergency telephone	:	CANUTEC (collect) (613) 996-6666 (24 hours)
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Skin irritation	:	Category 2
Serious eye damage	:	Category 1
Skin sensitization	:	Sub-category 1A

**GHS label elements**

Hazard pictograms	:	
-------------------	---	--

Signal Word	:	Danger
Hazard Statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

Precautionary Statements	:	<b>Prevention:</b> P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of
--------------------------	---	---



the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Aminopolymer	180583-06-6	Skin Sens. 1; H317	$\geq 5 - < 10$
2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine	90530-15-7	Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	$\geq 1 - < 5$
Isophoronediamine	2855-13-2	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	$\geq 1 - < 5$
m-phenylenebis(methylamine)	1477-55-0	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317	$\geq 1 - < 5$
3,6,9-triazaundecamethylenediamine	112-57-2	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	$\geq 0.1 - < 1$

Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**



General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	:	irritant effects sensitizing effects Allergic reactions Excessive lachrymation Erythema Dermatitis Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.
Notes to physician	:	Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**



- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with local regulations.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
m-phenylenebis(methylamine)	1477-55-0	(c)	0.1 mg/m <sup>3</sup>	CA AB OEL
		C	0.1 mg/m <sup>3</sup>	CA BC OEL
		C	0.1 mg/m <sup>3</sup>	CA QC OEL
		C	0.018 ppm	ACGIH

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-



ed or statutory limits.

**Personal protective equipment**

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
  
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Color : various
- Odor : ammoniacal
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available



Flash point	:	> 100 °C (> 212 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	23 hpa
Relative vapor density	:	No data available
Density	:	ca. 1.25 g/cm <sup>3</sup> (23.7 °C (74.7 °F))
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	24 g/l A+B Combined

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.



Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Components:****Isophoronediamine:**

Acute oral toxicity	:	LD50 Oral (Rat): 1,030 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 10 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 - 5,000 mg/kg

**m-phenylenebis(methylamine):**

Acute oral toxicity	:	LD50 Oral (Rat): 930 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 1.34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	:	LD50 Dermal (Rat): > 3,100 mg/kg

**3,6,9-triazaundecamethylenediamine:**

Acute oral toxicity	:	LD50 Oral (Rat): 1,716.2 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rat): 1,260 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Method	:	In Vitro Membrane Barrier Test Method for Skin Corrosion - CORROSITEX
Result	:	Skin irritation

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans	
	Carbon black, amorphous	1333-86-4

**OSHA** Not applicable

**NTP** Not applicable

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity****Components:****Isophoronediamine:**

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

**m-phenylenebis(methylamine):**

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h



**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 May be harmful to the environment if released in large quantities.  
 Water polluting material.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 3082  
 Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
 (aliphatic polyamine, Aminopolymer)  
 Class : 9  
 Packing group : III  
 Labels : Miscellaneous  
 Packing instruction (cargo aircraft) : 964  
 Packing instruction (passenger aircraft) : 964

**IMDG-Code**

UN number : UN 3082  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,



		N.O.S. (aliphatic polyamine, Aminopolymer)
Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation**

DOT: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant.

**TDG**

Not regulated as a dangerous good

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****Canadian lists**

No substances are subject to a Significant New Activity Notification.

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / C	:	Ceiling limit
CA AB OEL / (c)	:	ceiling occupational exposure limit
CA BC OEL / C	:	ceiling limit
CA QC OEL / C	:	Ceiling
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System



IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

Revision Date	:	01/25/2022
Date format	:	mm/dd/yyyy
Prepared by	:	R & D of Sika Canada Inc.
Material number	:	626,143

CA / Z8