

Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

SECTION 1. IDENTIFICATION

Product name : Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155

dark gray

Product code : 00000000050184370

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

No need for classification according to GHS criteria for this product.

GHS label elements

The product does not require a hazard warning label in accordance with GHS criteria.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
dichromium trioxide	1308-38-9	>= 5 - < 15
Iron oxide	1309-37-1	>= 25 - < 50
Limestone	1317-65-3	>= 10 - < 50
Titanium dioxide	13463-67-7	>= 25 - < 50

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Remove contaminated clothing. Do not leave the victim unattended.



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

If inhaled : After inhalation of dust.

Keep patient calm, remove to fresh air.

If difficulties occur: Seek medical attention.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off thoroughly with ample water.

If irritation develops, seek medical attention.

In case of eye contact : Flush with copious amounts of water for at least 15 minutes.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

None known.

Notes to physician

Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

Special protective equipment :

for fire-fighters

Wear a self-contained breathing apparatus.

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emergency procedures

Avoid dust formation.

Avoid contact with skin and eyes. Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice. Avoid dust formation.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up

Avoid raising dust.

Pick up and arrange disposal without creating dust.

Sweep up and shovel.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Keep away from sources of ignition - No smoking.

Dust can form an explosive mixture with air.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid dust formation.

Avoid inhalation of dusts.

Avoid skin contact.

Pour downwind and allow as little free fall as possible while

emptying bags into equipment.

Breathing must be protected when large quantities are de-

canted without local exhaust ventilation.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Conditions for safe storage : Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor- : Keep only in the original container in a cool, dry, well-



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

age conditions ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : No applicable information available.

No materials to be especially mentioned.

Further information on stor-

age stability

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dichromium trioxide	1308-38-9	PEL	0.5 mg/m3 (Chromium (Cr))	29 CFR 1910.1000 (Table Z-1)
		TWA value	1 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Inhalable fraction)	0.003 mg/m3 (chromium(III))	ACGIHTLV
		REL value	0.5 mg/m3 (chromium(III))	NIOSH
		TWA	0.5 mg/m3 (chromium)	OSHA Z-1
		TWA	0.5 mg/m3 (chromium)	NIOSH REL
Iron oxide	1309-37-1	TWA value (Respirable fraction)	5 mg/m3	ACGIHTLV
		REL value (Dust and fume)	5 mg/m3 (iron (Fe))	NIOSH
		PEL (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable particulate matter)	5 mg/m3	ACGIH
		TWA (dust and fume)	5 mg/m3 (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m3	OSHA Z-1



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Fumes)	10 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWÁ	10 mg/m3 (Titanium dioxide)	ACGIH

Engineering measures : No applicable information available.



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Hand protection

Remarks : Chemical resistant protective gloves Manufacturer's direc-

tions for use should be observed because of great diversity of

types.

Eye protection : Tightly fitting safety goggles (chemical goggles).

Safety glasses

Skin and body protection : Body protection must be chosen based on level of activity

and exposure. Protective suit

Protective measures : Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts.

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks). General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : fine powder

Color : gray

Odor : odorless

Odor Threshold : No data available

pH : 5-8

not applicable

Melting point : No applicable information available.

Boiling point : No applicable information available.

Flash point : No applicable information available.



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Self-ignition : not self-igniting

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : not applicable

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : 4 - 5 g/cm3

Bulk density : 3.5 - 5 g/m3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

not applicable

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Self-heating substances : No data available

Sublimation temperature : No applicable information available.

Molecular weight : No data available



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Stable under recommended storage conditions.

No hazards to be specially mentioned.

Conditions to avoid : See SDS section 7 - Handling and storage.

See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from products of a similar structure and

composition.

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

dichromium trioxide:

Partition coefficient: n-

octanol/water

Remarks: The value has not been determined because the

substance is inorganic.

Iron oxide:

Partition coefficient: n-

octanol/water

Remarks: Study scientifically not justified.

Titanium dioxide:

Partition coefficient: n-

octanol/water

: Remarks: not applicable

Mobility in soil

No data available



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

Other adverse effects

Product:

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Observe national and local legal requirements.

Residues should be disposed of in the same manner as the

substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not permitted for transport

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

dichromium triox- 1308-38-9

ide

US State Regulations

New Jersey Right To Know



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version SDS Number: Date of last issue: -Revision Date:

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

> Limestone 1317-65-3 Titanium dioxide 13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:

Flammability Health Instability 0 0

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000 1)

ACGIH USA. ACGIH Threshold Limit Values (TLV)

American Conference of Governmental Industrial Hygienists -**ACGIHTLV**

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH USA. NIOSH Recommended Exposure Limits **NIOSH REL**

USA. OSHA - TABLE Z-1 Limits for Air Contaminants -OSHA P0

1910.1000

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-OSHA Z-1

its for Air Contaminants



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 09/23/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in



Sikafloor PGM 155 Pronto dark gray Formerly MTop PGM 155 dark gray

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/23/2020 000000480002 Date of first issue: 09/23/2020

a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE, FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN