according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

#### **SECTION 1. IDENTIFICATION**

Product name : HP-S6

Other means of identification : HP-S6 SCC

Company name www.sika.ca

Canada

Pointe-Claire, QC H9R 4A9

601, avenue Delmar Sika Canada Inc.

Telephone (514) 697-2610 / 1 (800) 933-7452

Telefax (514) 694-2792

E-mail address ehs@ca.sika.com

Emergency telephone CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the

chemical and restrictions on

use

For further information, refer to product data sheet.

## **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

Skin corrosion Category 1

Serious eye damage Category 1

Skin sensitization Category 1

Carcinogenicity (Inhalation) Category 1A

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity :

- repeated exposure

Category 1 (Lungs)

**GHS** label elements

Hazard pictograms







according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure.

Precautionary Statements : Pres

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection/ hearing protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce verniting

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON

CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025

Print Date 09/22/2025

## **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

## Components

| Chemical name                  | CAS-No.    | Classification   | Concentration (% w/w) |
|--------------------------------|------------|--|-----------------------|
| Quartz (SiO2)                  | 14808-60-7 | Carc. 1A; H350<br>STOT RE 1; H372<br>STOT SE 3; H335                             | >= 60 - < 80          |
| dicalcium silicate             | 10034-77-2 | Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>STOT SE 3; H335                    | >= 5 - < 10           |
| Portland Cement                | 65997-15-1 | Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>STOT SE 3; H335 | >= 5 - < 10           |
| Aluminum calcium oxide sulfate | 12004-14-7 | Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>STOT SE 3; H335                       | >= 5 - < 10           |
| Cristobalite                   | 14464-46-1 | Carc. 1A; H350   | >= 1 - < 5            |

Actual concentration or concentration range is withheld as a trade secret

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure.

Causes severe burns.

Health injuries may be delayed.

corrosive effects sensitizing effects Allergic reactions

**Dermatitis** 

Notes to physician Treat symptomatically.

# **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

cannot be contained.

Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : Explosives

Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids

Spontaneously Combustible Substances

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Ingredients with workplace control parameters

| Components    | CAS-No.    | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|---------------|------------|-------------------------------------|--|-----------|
| Quartz (SiO2) | 14808-60-7 | TWA (Res-                           | 0.025 mg/m3                                    | CA AB OEL |

# Safety Data Sheet according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

| 1               | Ī          | pirable par-  |                                       |           |
|-----------------|------------|---------------|---------------------------------------|-----------|
|                 |            | ticulates)    |                                       |           |
|                 |            | TWA (Res-     | 0.1 mg/m3                             | CA ON OEL |
|                 |            | pirable frac- | o. i mg/mo                            | 07.01.022 |
|                 |            | tion)         |                                       |           |
|                 |            | TWA (Res-     | 0.025 mg/m3                           | CA BC OEL |
|                 |            | pirable)      | (Silica)                              | OA BO OLL |
|                 |            | TWAEV         | 0.05 mg/m3                            | CA QC OEL |
|                 |            | (respirable   | 0.05 mg/m5                            | OA QU OLL |
|                 |            | aerosol frac- |                                       |           |
|                 |            |               |                                       |           |
|                 |            | tion)         | 0.005/0                               | OA BO OEL |
|                 |            | TWA (Res-     | 0.025 mg/m3                           | CA BC OEL |
|                 |            | pirable)      |                                       |           |
|                 |            | TWA (Res-     | 0.025 mg/m3                           | CA BC OEL |
|                 |            | pirable)      | (Silica)                              |           |
|                 |            | TWA (Res-     | 0.025 mg/m3                           | ACGIH     |
|                 |            | pirable par-  |                                       |           |
|                 |            | ticulate mat- |                                       |           |
|                 |            | ter)          |                                       |           |
|                 |            | TWA (Res-     | 0.025 mg/m3                           | ACGIH     |
|                 |            | pirable par-  | (Silica)                              |           |
|                 |            | ticulate mat- | , ,                                   |           |
|                 |            | ter)          |                                       |           |
|                 |            | TWA (Res-     | 0.025 mg/m3                           | ACGIH     |
|                 |            | pirable par-  | i i i i i i i i i i i i i i i i i i i |           |
|                 |            | ticulate mat- |                                       |           |
|                 |            | ter)          |                                       |           |
|                 |            | TWA (Res-     | 0.025 mg/m3                           | ACGIH     |
|                 |            | pirable par-  | (Silica)                              | 7.00111   |
|                 |            | ticulate mat- | (Gillou)                              |           |
|                 |            | ter)          |                                       |           |
| Portland Cement | 65997-15-1 | TWA           | 10 mg/m3                              | CA AB OEL |
| Portiand Cement | 03997-13-1 | TWA (Res-     |                                       | CA BC OEL |
|                 |            | ,             | 1 mg/m3                               | CA BC OEL |
|                 |            | pirable)      | F/ 0                                  | 04.00.051 |
|                 |            | TWAEV         | 5 mg/m3                               | CA QC OEL |
|                 |            | (respirable   |                                       |           |
|                 |            | dust)         | 10 / 5                                | 04.00.00  |
|                 |            | TWAEV (to-    | 10 mg/m3                              | CA QC OEL |
|                 |            | tal dust)     |                                       |           |
|                 |            | TWAEV         | 1 mg/m3                               | CA QC OEL |
|                 |            | (respirable   |                                       |           |
|                 |            | aerosol frac- |                                       |           |
|                 |            | tion)         |                                       |           |
|                 |            | TWA (Res-     | 1 mg/m3                               | ACGIH     |
|                 |            | pirable par-  | _                                     |           |
|                 |            | ticulate mat- |                                       |           |
|                 |            | ter)          |                                       |           |
| Cristobalite    | 14464-46-1 | TWA (Res-     | 0.025 mg/m3                           | CA AB OEL |
|                 |            | pirable par-  | 2.020                                 | 0         |
|                 |            | ticulates)    |                                       |           |
|                 |            | liculates     |                                       |           |

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

|                          |           | TWA (Respirable fraction)                          | 0.05 mg/m3              | CA ON OEL |
|--------------------------|-----------|--|-------------------------|-----------|
|                          |           | TWA (Res-<br>pirable)                              | 0.025 mg/m3<br>(Silica) | CA BC OEL |
|                          |           | TWAEV<br>(respirable<br>aerosol frac-<br>tion)     | 0.05 mg/m3              | CA QC OEL |
|                          |           | TWA (Res-<br>pirable par-<br>ticulate mat-<br>ter) | 0.025 mg/m3<br>(Silica) | ACGIH     |
| calcium sulfate, natural | 7778-18-9 | TWA  | 10 mg/m3<br>(Calcium)   | CA AB OEL |
|                          |           | TWAEV (in-<br>halable dust)                        | 10 mg/m3                | CA QC OEL |
|                          |           | TWA (Inhal-<br>able particu-<br>late matter)       | 10 mg/m3<br>(Calcium)   | ACGIH     |

**Engineering measures** 

Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

# Personal protective equipment

Respiratory protection

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

Avoid breathing dust.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : powder

Color : various

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/ range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : ca. 2.5 g/l (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

Not applicable

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No hazardous decomposition products are known.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Acute toxicity**

Not classified due to lack of data.

#### Skin corrosion/irritation

Causes severe burns.

# Serious eye damage/eye irritation

Causes serious eye damage.

## Respiratory or skin sensitization

# Skin sensitization

May cause an allergic skin reaction.

# Respiratory sensitization

Not classified due to lack of data.

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025

Print Date 09/22/2025

# Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 1: Carcinogenic to humans

Cristobalite 14464-46-1

(Silica dust, crystalline)

**OSHA** OSHA specifically regulated carcinogen

Quartz (SiO2) 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

Known to be human carcinogen

Cristobalite 14464-46-1

(Silica, Crystalline (Respirable Size))

## Reproductive toxicity

Not classified due to lack of data.

# STOT-single exposure

May cause respiratory irritation.

## STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged exposure can cause silicosis.

# **Aspiration toxicity**

Not classified due to lack of data.

## **Further information**

## **Product:**

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025

Print Date 09/22/2025

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

# **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

## **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

#### **IATA-DGR**

Not regulated as a dangerous good

## **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **Domestic regulation**

#### **TDG**

Not regulated as a dangerous good

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

## Special precautions for user

Not applicable

#### **SECTION 15. REGULATORY INFORMATION**

## **Canadian lists**

No substances are subject to a Significant New Activity Notification.

No substances are subject to CEPA Section 84 Ministerial Conditions.

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

Ontario Table of Occupational Exposure Limits made under CA ON OEL

the Occupational Health and Safety Act.

CA QC OEL Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA 8-hour, time-weighted average CA AB OEL / TWA 8-hour Occupational exposure limit 8-hour time weighted average CA BC OEL / TWA CA ON OEL / TWA Time-Weighted Average Limit (TWA) CA QC OEL / TWAEV Time-weighted average exposure value

**ADR** Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS Chemical Abstracts Service **DNEL** Derived no-effect level

EC50 Half maximal effective concentration

**GHS** Globally Harmonized System International Air Transport Association IATA

**IMDG** International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

**MARPOL** International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

according to the Hazardous Products Regulations



# HP-S6

Revision Date 09/22/2025 Print Date 09/22/2025

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

## Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 09/22/2025 Date format : mm/dd/yyyy

Person who prepared the

SDS

: R & D of Sika Canada Inc.

Material number : 645,592

CA / Z8