



## PRODUCT DATA SHEET

# Sika® Stabilizer-2222 TBM

TBM tail seal sealant (formerly Sika® Stabilizer TBM TS-2 TK)

### PRODUCT DESCRIPTION

Sika® Stabilizer-2222 TBM is a tail seal sealant used during excavation with TBMs. It has been developed for tunnel boring machines (TBM) using backfilling grout for filling the gap between the machine and the precast segment lining.

### WHERE TO USE

- Provides a seal between the inside of the shield and the surrounding ground conditions
- Sealing of the tail seal brushes preventing grout, water, foam, soil ingress and washout effects
- Designed for use in urban areas where soil and ground water could come in contact with the TBM excavation

### CHARACTERISTICS / ADVANTAGES

- Good adhesion to concrete and steel in wet and dry conditions
- Ensures a seal between the inside of the shield and the outside environment preventing ingress of water, soil and grout
- Good anti-washout properties and watertightness
- Extends the life-time of the wire brushes in the tail seals
- Does not react with the segmental seals
- Withstands high water pressure
- Good pumpability
- Lower consumption compared to other types of tail seal greases
- Easy to handle

### PRODUCT INFORMATION

Composition / Manufacturing	Organic compound
Packaging	25, 70 and 250 kg drums Refer to current price list for packaging variations
Shelf Life	12 months from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +40 °C. Always refer to packaging.
Appearance / Colour	Homogenous paste, grey
Density	1,460 kg/l ± 0,070
Solubility	Not soluble
Consistency	240 ± 10 (+20 °C) (ASTM D217)

### SYSTEMS

---

**Compatibility**

Compatible with Sika® admixtures and other Sika® products.  
Contact Sika Technical Services for additional information.

---

**APPLICATION INFORMATION**

---

**Recommended Dosage**

Standard consumption is 0,5–1,5 kg/m<sup>2</sup> of the external surfaces of the concrete precast rings and segments.  
Consumption can change depending on the conditions on site and due to the precast segments surface roughness, brush condition, segments alignment, etc.  
Contact Sika Technical Services for additional information.

---

**BASIS OF PRODUCT DATA**

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

**ENVIRONMENT, HEALTH & SAFETY**

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

**APPLICATION INSTRUCTIONS****DISPENSING**

Sika® Stabilizer-2222 TBM is pumped through the grease lines between the rows of brushes in the gap between the tail skin and the lining segments using the equipment already installed in the machine.

**LOCAL RESTRICTIONS**

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

**LEGAL NOTES**

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: [www.sika.ca](http://www.sika.ca)

**Sika Canada Inc.**

Head Office  
601, avenue Delmar  
Pointe-Claire, Quebec  
H9R 4A9  
1-800-933-SIKA  
[www.sika.ca](http://www.sika.ca)

**Other locations**

Boisbriand (Quebec)  
Brantford; Cambridge;  
Sudbury; Toronto (Ontario)  
Edmonton (Alberta)  
Surrey (British Columbia)

**Product Data Sheet**

Sika® Stabilizer-2222 TBM  
January 2023, Version 01.01  
02140407100000059

SikaStabilizer-2222TBM-en-CA-(01-2023)-1-1.pdf

