

Revision Date 09/22/2022

SECTION 1. IDENTIFICATION

Product name : Sika® Icosit® KC 340/7 CA Part B

Other means of identification : No data available

Company name : www.sika.ca

Canada

Pointe-Claire, QC H9R 4A9

601, avenue Delmar Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

# **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity:

- repeated exposure

Category 2

**GHS** label elements



Revision Date 09/22/2022 Print Date 10/12/2024

Hazard pictograms





Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or re-

peated exposure.

# **Precautionary Statements**

# Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P284 In case of inadequate ventilation wear respiratory protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container



Revision Date 09/22/2022

Print Date 10/12/2024

tightly closed. P405 Store locked up.

# Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

# **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

# Components

| Chemical name   | CAS-No.     | Classification   | Concentra-<br>tion (% w/w) |
|---|-------------|--|----------------------------|
| 4,4'-methylenediphenyl diisocyanate   | 101-68-8    | Acute Tox. 4; H332<br>Skin Irrit. 2; H315<br>Eye Irrit. 2B; H320<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>STOT SE 3; H335<br>STOT RE 2; H373                  | >= 30 - < 60               |
| Diphenylmethanediisocyanate, isomeres and homologues  | 9016-87-9   | Acute Tox. 4; H332<br>Skin Irrit. 2; H315<br>Eye Irrit. 2B; H320<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>STOT SE 3; H335<br>STOT RE 2; H373                  | >= 10 - < 30               |
| 1,3-Butanediol, polymer with 1,1'-methylenebis[isocyanatobenzene], 2,2'-oxybis[ethanol] and 1,2-propanediol | 155662-82-1 | Acute Tox. 4; H332<br>Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>Carc. 2; H351<br>STOT SE 3; H335<br>STOT RE 2; H373 | >= 10 - < 30               |
| o-(p-isocyanatobenzyl)phenyl isocy-<br>anate  | 5873-54-1   | Acute Tox. 4; H332<br>Skin Irrit. 2; H315<br>Eye Irrit. 2B; H320<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>STOT SE 3; H335<br>STOT RE 2; H373                  | >= 10 - < 30               |

Actual concentration or concentration range is withheld as a trade secret

# **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.



Revision Date 09/22/2022 Print Date 10/12/2024

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects

sensitizing effects
Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Headache Dermatitis

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must



Revision Date 09/22/2022 Print Date 10/12/2024

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment. Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products.

Store in original container. Conditions for safe storage

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Ingredients with workplace control parameters



Revision Date 09/22/2022 Print Date 10/12/2024

| Components  | CAS-No.     | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|---|-------------|-------------------------------------|--|-----------|
| 4,4'-methylenediphenyl diiso-<br>cyanate  | 101-68-8    | TWA                                 | 0.005 ppm                                      | CA BC OEL |
|   |             | С                                   | 0.01 ppm                                       | CA BC OEL |
|   |             | TWA                                 | 0.005 ppm                                      | CA ON OEL |
|   |             | С                                   | 0.02 ppm                                       | CA ON OEL |
|   |             | TWAEV                               | 0.005 ppm<br>0.051 mg/m3                       | CA QC OEL |
|   |             | TWA                                 | 0.005 ppm                                      | ACGIH     |
| Diphenylmethanediisocyanate, isomeres and homologues  | 9016-87-9   | TWA                                 | 0.005 ppm<br>0.07 mg/m3                        | CA AB OEL |
| _   |             | TWA                                 | 0.005 ppm                                      | CA BC OEL |
|   |             | С                                   | 0.01 ppm                                       | CA BC OEL |
|   |             | TWAEV                               | 0.005 ppm<br>0.051 mg/m3                       | CA QC OEL |
| 1,3-Butanediol, polymer with 1,1'- meth- ylenebis[isocyanatobenzene], 2,2'-oxybis[ethanol] and 1,2- propanediol | 155662-82-1 | TWA                                 | 0.005 ppm                                      | CA BC OEL |
|   |             | С                                   | 0.01 ppm                                       | CA BC OEL |

#### **Engineering measures**

Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

# Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-



Revision Date 09/22/2022

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : brown

Odor : musty

Odor Threshold : No data available

pH : No data available

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : > 205 °C (401 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : 0.01 hpa

Relative vapor density : No data available

Density : ca. 1.23 g/ml (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available



Revision Date 09/22/2022

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

No data available Viscosity, kinematic

Explosive properties No data available

Oxidizing properties No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid No data available

Incompatible materials No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

# **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Harmful if inhaled.

#### **Components:**

# 4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

# Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity LD50 Oral (Rat): > 10,000 mg/kg



Revision Date 09/22/2022

Print Date 10/12/2024

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

# Serious eye damage/eye irritation

Causes serious eye irritation.

# Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

# Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# Germ cell mutagenicity

Not classified based on available information.

# Carcinogenicity

Suspected of causing cancer.

IARC Not applicable

**OSHA** Not applicable

NTP Not applicable

#### Reproductive toxicity

Not classified based on available information.

# STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### **Aspiration toxicity**

Not classified based on available information.



Revision Date 09/22/2022

Print Date 10/12/2024

# **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Components:**

# Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1,640

mg/l

# Persistence and degradability

No data available

# **Bioaccumulative potential**

No data available

#### Mobility in soil

No data available

#### Other adverse effects

#### Product:

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

# **SECTION 13. DISPOSAL CONSIDERATIONS**

#### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

# **IMDG-Code**

Not regulated as a dangerous good



Revision Date 09/22/2022 Print Date 10/12/2024

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

**TDG** 

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average

CA BC OEL / C : ceiling limit
CA ON OEL / C : Ceiling Limit (C)

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit



Revision Date 09/22/2022 Print Date 10/12/2024

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

# Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 09/22/2022 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 738,823

CA / Z8