



RhinoBond® ROOF SYSTEM

Quick and Easy to Install

No Membrane Fastener Penetrations

Increased Productivity

Even Wind Load Distribution

Enhanced Wind Uplift Resistance

Reduced Membrane 'Flutter'

Elimination of Half Sheets

Covered by System Warranty

FM Approval Up to 210 PSF

CSA A123.21-14 Approval tested to 210 PSF

The RhinoBond® Roof System is used with Sarnafil® and Sikaplan® PVC membranes to increase contractor productivity and enhance roof wind uplift resistance.

This innovative attachment system relies on electromagnetic induction welding to eliminate fastener penetrations. Specially-coated membrane plates are fastened to the roof assembly and later heat-welded to the underside of membrane using the RhinoBond® tool.

The RhinoBond® Roof System uses a patented 'stand-up' tool – a single worker places the unit above a plate and activates the electromagnetic pulse, which is completely safe. The pulse causes the securement plate to heat up and fuse to the membrane directly above it. Typical weld time is five seconds per plate. A weighted RhinoBond® 'cooling clamp magnet' is then temporarily placed on top of the plate to assure a strong bond.

RhinoBond® is ideal for projects that require enhanced wind protection. The system achieves an FM I-90 rating in the field while requiring 30 percent fewer fasteners per square.

The system is also perfect for metal retrofit applications. Contractors can improve productivity by avoiding the need to drill and fasten into steel roof purlins, as long as the steel deck is strong enough. Another time-saving benefit of RhinoBond is the option to use wider roof membrane sheets, resulting in fewer seams to weld.

RhinoBond® is simple to use and has proven to be a real time saver for contractors.



**BUILDING TRUST
CONSTRUIRE LA CONFIANCE**



**A TOOL THAT IS EASY TO HANDLE ...
EASY TO USE ON ROOFS**

The RhinoBond® tool is lightweight, portable and has an adjustable handle. An LED display provides detailed information for start-up, ready, energy level, number of plates welded / remaining, and cycles to date. Error messages notify the operator of high or low voltage conditions, and also if no plate is found.

Stable power (110 - 125 volts, 60 Hz) is required to operate the tool. Operators should use a 5,000 watt generator (minimum) with one 20A GFCI-protected circuit per tool. A maximum of two (2) RhinoBond® tools per 5,000 watt generator is recommended. The power cord should be 12 gauge at a minimum, with a maximum length of 30 m (100 ft).

Six (6) cooling clamp magnets come with the tool. A convenient carry case protects the unit during transit and storage.

To obtain pricing and ordering information for the RhinoBond Roof Fastening Tool or to purchase a unit, contact your regional Sika Canada representative.



A PVC membrane undergoing wind resistance tests. The membrane is seen secured on the left portion of the test bed with the RhinoBond® tool, and at right using conventional in-seam attachment.

RhinoBond® Roof Fastening Tool

Ordering Information

Part Number	Description	Packaging	Weight
1352653	RhinoBond® Tool and 6 Cooling Clamp Magnets	Molded Cases	26 kg (58 lb)
1352654	6 Cooling Clamp Magnets	Molded Case	9.5 kg (21 lb)
1352641	PVC Plates	500 / Bucket	15.9 kg (35 lb)

Physical Data

RhinoBond® Tool	Cooling Clamp Magnets
Height: 72.39 cm (28.5 in), Handle Extends to 86.34 cm (34 in)	Quantity: 6 / Case
Width: 31.75 cm (12.5 in)	Base Diameter: 8.9 cm (3.25 in)
Weight: 10.4 kg (23 lb)	Weight: 1.1 kg (2.5 lb). Each
Case Weight (Empty): 12.7 kg (14 lb)	Case Weight (Empty): 2.4 kg (6 lb)
Total Weight (Tool w/Case): 16.8 kg (37 lb)	Total Weight (Clamps w/Case): 9.5 kg (21 lb)



RhinoBond® features an adjustable handle and easy-to-read LED display.



Vinyl-coated plates are fastened to the roof substrate and heat-welded to the underside of PVC membranes.



RhinoBond® is a registered trademark of OMG, Inc. Our most current General Sales Conditions shall apply. Please consult the Product Data Sheet prior to any use and processing.

SIKA CANADA INC.
Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9

Autres sites
Toronto
Edmonton
Vancouver

1-800-933-SIKA
www.sika.ca

Certified ISO 9001 (CERT-0102780)
Certified ISO 14001 (CERT-0102791)

**BUILDING TRUST
CONSTRUIRE LA CONFiance**

