



SikaLevel®-250

SUPERIOR FLOW, CEMENTITIOUS, SELF-LEVELLING UNDERLAYMENT



SikaLevel®-250 is a one-component, polymer-modified, self-levelling cementitious underlayment applicable at thicknesses ranging from 3 mm to 31 mm (1/8 in to 1 1/4 in). SikaLevel®-250 is compatible with a wide variety of existing substrates, producing a flat and cost-effective substrate prior to application of a final floor finish.

ADVANTAGES

- Can be mixed by hand using a drill or by using a mixing and pumping equipment
- High-flow and superior workability for easy installation/levelling
- Can be walked on after 3 hours at 23 °C (73 °F)
- Ceramic tiles and non-moisture sensitive natural stone and agglomerated stones can be installed after only 3 hours
- Other floor coverings: 16-hour waiting time (minimum)

WHERE TO USE

- Concrete
- Approved plywood underlayments
- Unconventional substrates with SikaLevel®-02 EZ Primer CA (see product data sheet for more information)



TO LEARN MORE

Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

Sika Canada Inc.
Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9

Other locations
Boisbriand (QC)
Brantford; Cambridge;
Sudbury; Toronto (ON)
Edmonton (AB) Surrey (BC)

1-800-933-SIKA
www.sika.ca

© Sika Canada Inc. / 06.2025

BUILDING TRUST
CONSTRUIRE LA CONFIANCE

