

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128

Product code : 000000000057627100

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

No need for classification according to GHS criteria for this product.

GHS label elements

The product does not require a hazard warning label in accordance with GHS criteria.

Other hazards

No applicable information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	>= 20 - < 25
Iron oxide	1309-37-1	>= 10 - < 15
carbon black	1333-86-4	>= 1 - < 3
aluminium hydroxide	21645-51-2	>= 1 - < 3

SECTION 4. FIRST AID MEASURES

General advice : Remove contaminated clothing.

Do not leave the victim unattended.

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0	Revision Date: 07/28/2020	SDS Number: 000000260945	Date of last issue: - Date of first issue: 07/28/2020
----------------	------------------------------	-----------------------------	--

- If inhaled : Keep patient calm, remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash thoroughly with soap and water
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO2)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment : Wear self-contained breathing apparatus for firefighting if nec-
-

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

for fire-fighters essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Materials to avoid : No applicable information available.
No materials to be especially mentioned.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Iron oxide	1309-37-1	TWA value (Respirable fraction)	5 mg/m3	ACGIHTLV

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version
1.0

Revision Date:
07/28/2020

SDS Number:
000000260945

Date of last issue: -
Date of first issue: 07/28/2020

		REL value (Dust and fume)	5 mg/m3 (iron (Fe))	NIOSH
		PEL (fumes/smoke)	10 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smoke)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable particulate matter)	5 mg/m3	ACGIH
		TWA (dust and fume)	5 mg/m3 (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m3	OSHA Z-1
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Fumes)	10 mg/m3	OSHA P0
carbon black	1333-86-4	TWA value (Inhalable fraction)	3 mg/m3	ACGIHTLV
		PEL	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	0.1 mg/m3 (Polycyclic aromatic hydrocarbons (PAH))	NIOSH
		TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total	15 mg/m3	OSHA Z-1

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

		dust)		
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
aluminium hydroxide	21645-51-2	TWA value (Respirable fraction)	1 mg/m3	ACGIHTLV
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Hand protection

Remarks : impermeable gloves rubber Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : red-brown

pH : neutral to slightly alkaline

Flash point : 376 °F / 191 °C

Method: Flash-Point by Pensky-Martens Closed Cup Tester.,
closed cup
375.80 °F / 191.00 °C

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

Method: Flash-Point by Pensky-Martens Closed Cup Tester., closed cup

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Self-ignition : not self-igniting

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 1.59 g/cm³ (68 °F / 20 °C)
approx. 13.23 lb/USg (68.00 °F / 20.00 °C)

Solubility(ies)
Water solubility : partly soluble

Solubility in other solvents : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-
scribed/indicated.

Viscosity
Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive
Not explosive

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac- : Stable under recommended storage conditions.
tions No hazards to be specially mentioned.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0	Revision Date: 07/28/2020	SDS Number: 000000260945	Date of last issue: - Date of first issue: 07/28/2020
----------------	------------------------------	-----------------------------	--

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0	Revision Date: 07/28/2020	SDS Number: 000000260945	Date of last issue: - Date of first issue: 07/28/2020
----------------	------------------------------	-----------------------------	--

Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Titanium dioxide:

Partition coefficient: n-octanol/water : Remarks: not applicable

Iron oxide:

Partition coefficient: n-octanol/water : Remarks: Study scientifically not justified.

carbon black:

Partition coefficient: n-octanol/water : Remarks: not applicable

aluminium hydroxide:

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0	Revision Date: 07/28/2020	SDS Number: 000000260945	Date of last issue: - Date of first issue: 07/28/2020
----------------	------------------------------	-----------------------------	--

tions.
Residues should be disposed of in the same manner as the substance/product.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Clean Air Act

:

CA TAC

:

HON HAP (US)

:

:

Threshold for emissions from stacks less than 25 ft::

Ambient air standard::

Threshold for emissions from stacks less than 25 ft::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

Ambient air standard::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

HON SOC (US) : Group I

:

Maximum allowable concentration::

VOC AE (US) Reactivity factor::

VOC (US) :

VOC EQ (US) :

CA MIR Maximum Incremental Reactivity (MIR) value::

CAA (US) :

:

:

CA TAC :

HON HAP (US) :

:

Threshold for emissions from stacks less than 25 ft::

Ambient air standard::

Threshold for emissions from stacks less than 25 ft::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

Ambient air standard::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

Threshold for emissions from stacks greater than or equal to 75 ft.:

HON SOC (US) : Group I

:

Maximum allowable concentration::

VOC AE (US) Reactivity factor::

VOC (US) :

VOC EQ (US) :

CA MIR Maximum Incremental Reactivity (MIR) value::

CAA (US) :

:

:

CA TAC :

HON HAP (US) :

:

Threshold for emissions from stacks less than 25 ft.:

Ambient air standard::

Threshold for emissions from stacks less than 25 ft.:

Threshold for emissions from stacks 40 to less than 75 ft.:

Threshold for emissions from stacks 25 to less than 40 ft.:

Threshold for emissions from stacks greater than or equal to 75 ft.:

Ambient air standard::

Threshold for emissions from stacks 40 to less than 75 ft.:

Threshold for emissions from stacks 25 to less than 40 ft.:

Threshold for emissions from stacks greater than or equal to 75 ft.:

HON SOC (US) : Group I

:

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

VOC EQ (US) :

CA MIR Maximum Incremental Reactivity (MIR) value::

CAA (US) :

:

:

CA TAC :

HON HAP (US) :

:

Threshold for emissions from stacks less than 25 ft::

Ambient air standard::

Threshold for emissions from stacks less than 25 ft::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

Ambient air standard::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

HON SOC (US) : Group I

:

Maximum allowable concentration::

VOC AE (US) Reactivity factor::

VOC (US) :

VOC EQ (US) :

CA MIR Maximum Incremental Reactivity (MIR) value::

CAA (US) :

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

:

US State Regulations

Pennsylvania Right To Know

Iron oxide	1309-37-1
carbon black	1333-86-4
Titanium dioxide	13463-67-7

New Jersey Right To Know

carbon black	1333-86-4
Titanium dioxide	13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including carbon black, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information


SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128




Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000260945 Date of last issue: -
Date of first issue: 07/28/2020

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration asso-

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/28/2020	000000260945	Date of first issue: 07/28/2020

ciated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/28/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE

SAFETY DATA SHEET

Sikaflex-900 redwood tan 128 Formerly MSeal 900 Rdw Tan 128



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/28/2020	000000260945	Date of first issue: 07/28/2020

ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN