



SECTION I: PRODUCT INFORMATION

PRODUCT: **SikaPower®-497**

REVISION DATE: November 4, 2014

USAGE:

SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666****FOR ROAD:**TDG CLASSIFICATION: Not Regulated
UN NUMBER: Not Established
Packaging Group: Not ApplicableWHMIS Classification: D2B, E
Class: Not Applicable**FOR IATA / IMDG:**

Proper Shipping Name: Environmentally hazardous substance, Solid, NOS (Epoxy Resin & P-TERT-BUTYLPHENYL GLYCIDYL ETHER)

TDG Class : 9 UN NUMBER: 3077
Packaging Group: III

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (Species, route)	LC ₅₀ (Species, route)
EPOXY RESIN	30-60	Not Available	25068-38-6	> 5000 (oral, rat)	Not Available
CALCIUM OXIDE	5-10	ACGIH 2 mg/m ³ TWA	1305-78-8	Not Available	Not Available

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Paste
Appearance and Odor: Green paste, odorless
Odor Threshold: Not Established
Evaporation Rate: Not Applicable
Vapor Density: Not Established
Vapor Pressure: Not EstablishedBoiling Point: Not Established
Freezing Point: Not Established
Density: ~1.25 g/m³ @ 20°C
Water Solubility: Not Established
pH: Not Established
% volatility: Not Applicable
Water/Oil Distribution: Not Established



PRODUCT: SikaPower®-497

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions:	No	TDG Flammability Class:	Not Regulated
Extinguishing methods:	Foam, dry chemical products, CO ₂ , water hose.	Flammable upper limits (% vol.):	Not Applicable
Special Methods:	Fire fighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.	Flammable lower limits (% vol.):	Not Applicable
		Flash Point (method used):	> 150°C
		Auto-ignition temperature:	Not Established
		Dangerous Combustion Products:	Carbon oxides, nitrogen oxides.
		Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY

Chemical stability: If not, under what conditions:	Yes But excessive heat will degrade the resin.	Dangerous decomposition products:	Carbon oxides, nitrogen oxides.
Incompatibility with other material: If Yes, which ones:	Yes Strong acid, base, and oxidizer.	Polymerization Risks:	No.



PRODUCT: **SikaPower®-497**

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations. May cause serious eye damage.

Skin: May be irritating to the skin, may cause sensitization by skin contact and allergic skin reaction

Inhalation: Exposure to the decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Ingestion: Harmful if swallowed.

Carcinogenicity: Not Established

Toxic effects on reproduction: Not Established

Teratogenicity: Not Established

Mutagenicity: Not Established

Product with synergistic effects: Not Established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: SikaPower®-497

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: NIOSH approved mask with organic vapor cartridge if the ventilation is deficient.

Eyes: Safety glasses

Shoes: Ordinary

Clothing: Rubber Apron

Other: No

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand or other absorbent material. Residue may be removed with steam or hot water and soap. All precautions should be taken when cleaning the spill with solvent.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: SikaPower®-497

SECTION VIII: FIRST AID

Skin: Remove and clean all contaminated clothing.
Wash immediately with plenty of soap and water.
Consult a physician if required.

Eyes: Rinse with water for at least 15 minutes.
Consult a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.