

## Sarnatred - V

<b>Description</b>	Sarnatred - V is a rolled-out, heat welded walkway that has an improved “chevron” design. Sarnatred-V is used to protect the Sika® Sarnafil® membrane from foot traffic.
<b>Composition</b>	■ Sarnatred -V is a 2.4 mm (96 mil) thick, polyester reinforced, membrane made from the same proven formulation as our Sarnafil® membrane.
<b>Features</b>	■ Sarnatred -V is dimensionally stable and durable. ■ Sarnatred -V is light gray and has a textured surface similar to a chevron pattern.
<b>Packaging/Storage</b>	■ Sarnatred - V is provided in rolls on wood pallets. ■ Dimensions are approximately 1 m (39 in) wide by 15 m (50 ft) long.
<b>Installation</b>	<p>Roofing membrane to receive Sarnatred - V shall be clean and dry. Chalk lines on deck sheet to indicate location of walkway. Apply a continuous coat of Sarnacol 2170 adhesive to the deck sheet and the back of Sarnatred - V in accordance with Sika Canada’s installation requirements for this adhesive. Make sure to leave the area on the deck sheet and on the back of the Sarnatred - V that will be hot-air welded free of adhesive. The entire perimeter of Sarnatred - V will be welded.</p> <p>Roll Sarnatred - V into Sarnacol 2170 adhesive then press into place with a minimum (45 kg) 100 lb linoleum roller. Clean the deck membrane and the back of Sarnatred - V in areas to be welded if need be. Hot-air weld the entire perimeter of Sarnatred - V to the Sika® Sarnafil® deck sheet. Check all welds with a rounded screwdriver. Reweld any inconsistencies.</p> <p>For complete instructions on how to install Sika® Sarnafil® walkways, refer to Sika Canada’s Applicator Handbook.</p> <p><b>Important: Check all existing deck membrane seams that are to be covered by Sarnatred - V with rounded screwdriver and reweld any inconsistencies before walkway installation. Do not use solvent-based adhesive when polystyrene is used as an insulation board in the roof assembly or in geographic areas where voc compliance is not met.</b></p>
<b>Availability</b>	Sarnatred - V is available directly from Sika Canada Authorized Applicators when used within a Sarnafil® Roofing or Waterproofing System. Contact Sika Canada or visit <a href="http://www.sika.ca">www.sika.ca</a> for further information.
<b>Warranty</b>	As a Sika Canada-supplied accessory, Sarnatred - V is included in Sika Canada’s Standard or System Warranty.
<b>Maintenance</b>	<p>Sarnatred - V may require periodic cleaning or removal of leaves and similar debris.</p> <p>Periodic maintenance of a Sarnafil® system ensures extended performance and reduces life cycle costs. Consistent with industry practices, Sika Canada recommends inspecting the roof system for damage, plugged drains, weathered sealants, etc. at least twice a year and after each storm.</p>



# Construction

**Technical Support** Sika Canada provides technical support. Technical staff is available to advise applicators as to the proper installation method.

## Technical Data

*(as manufactured):*

### Parameters

#### Reinforcing Material

**Overall Thickness D751**, nominal

**Tensile Strength D751**, min.

**Elongation at Break D751**, min.

**Tearing Resistance D751**, min

**Low Temperature Bend D2136**, -40°C- (30°F)

**Fire Resistance E108**

**UV Resistance D2565**

**Puncture Resistance (Federal Test) 2065**

**Recycled Content**

**UL 410 "Slip Resistance of Floor Surface Material"**

### Typical Physical Properties

Polyester

2.4 mm (0.096 in)

275 psi

15%

50 lbf

Pass

25 ft

5000 hrs

24.5 kg (54 lb)

1% Post Consumer / 9% Pre Consumer

Pass

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions, within their shelf life. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request or can be accessed in the Internet under [www.sika.ca](http://www.sika.ca).



### Sika Canada Inc.

#### Head Office

601 Delmar Avenue  
Pointe-Claire, Quebec  
H9R 4A9

#### Other locations

Toronto  
Edmonton  
Vancouver

**1-800-933-SIKA**  
**[www.sika.ca](http://www.sika.ca)**

An ISO 9001 certified company  
Pointe-Claire: ISO 14001 certified EMS