



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

### SECTION 1. IDENTIFICATION

Product name : Sikalastic® Primer

Other means of identification : No data available

Company name : www.sika.ca  
Canada  
Pointe-Claire, QC H9R 4A9  
601, avenue Delmar  
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

#### GHS label elements



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
P284 In case of inadequate ventilation wear respiratory protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
modified MDI	53862-89-8	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335	$\geq 30 - < 60$
4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	98-56-6	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1B; H317 STOT SE 3; H335	$\geq 10 - < 30$
Isophorondiisocyanate homopolymer	53880-05-0	Skin Sens. 1B; H317 STOT SE 3; H335	$\geq 10 - < 30$
4,4'-methylenediphenyl diisocyanate	101-68-8	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	$\geq 5 - < 10$



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 5 - < 10
methylenediphenyl diisocyanate	26447-40-5	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 1 - < 5
solvent naphtha (petroleum), light arom.	64742-95-6	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Asp. Tox. 1; H304	>= 1 - < 5
1,2,4-trimethylbenzene	95-63-6	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335	>= 1 - < 5

Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitizing effects  
Asthmatic appearance  
Cough  
Respiratory disorder  
Allergic reactions  
Excessive lachrymation  
Erythema  
Headache  
Dermatitis  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapors accumulating to form explosive concentra-



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

- tions. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.
- Materials to avoid : Explosives  
Oxidizing agents



**Sikalastic® Primer**

Revision Date 01/31/2025

Print Date 02/03/2025

Poisonous gases  
Poisonous liquids

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
modified MDI	53862-89-8	TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWA	0.005 ppm 0.05 mg/m3	CA AB OEL
		TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.07 mg/m3	CA AB OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
		TWA	0.005 ppm	ACGIH
methylenediphenyl diisocyanate	26447-40-5	TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm	ACGIH
solvent naphtha (petroleum), light arom.	64742-95-6	TWAEV	200 mg/m3	CA QC OEL
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 123 mg/m3	CA AB OEL
		TWAEV	25 ppm	CA QC OEL
		TWA	25 ppm	CA BC OEL
		TWA	10 ppm	ACGIH

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

### Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : light yellow
- Odor : mild





## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/ range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	38.89 °C (102.00 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	0.8 %(V)
Vapor pressure	:	7.066066 hpa
Relative vapor density	:	No data available
Density	:	1.16 g/cm <sup>3</sup> (23 °C (73 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s
Explosive properties	:	No data available
Oxidizing properties	:	No data available



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

Volatile organic compounds : 96 g/l  
(VOC) content

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.  
Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

Hazardous decomposition products : No decomposition if stored and applied as directed.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Harmful if inhaled.

#### Components:

##### **4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene:**

Acute oral toxicity : LD50 Oral (Rat): > 13,000 mg/kg

##### **4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgment

##### **Diphenylmethanediisocyanate, isomeres and homologues:**

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgment  
Assessment: The component/mixture is moderately toxic after short term inhalation.



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

### **solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

#### **Carcinogenicity**

Not classified due to lack of data.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	98-56-6
-------------	---	---------

**OSHA** Not applicable

**NTP** Not applicable

#### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT-single exposure**

May cause respiratory irritation.

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### **Aspiration toxicity**

Not classified due to lack of data.



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene:**

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 3 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2 mg/l  
aquatic invertebrates Exposure time: 48 h
- Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.41  
plants mg/l  
Exposure time: 72 h

##### **Diphenylmethanediisocyanate, isomeres and homologues:**

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l  
Exposure time: 96 h
- Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): > 1,640  
plants mg/l

##### **solvent naphtha (petroleum), light arom.:**

- Toxicity to algae/aquatic : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9  
plants mg/l

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

No data available

#### **Mobility in soil**

No data available

#### **Other adverse effects**

##### Product:

- Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
May be harmful to the environment if released in large quantities.  
Water polluting material.



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 1263  
Proper shipping name : Paint  
(4-chloro-alpha,alpha,alpha-trifluorotoluene)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355  
Environmentally hazardous : yes

##### IMDG-Code

- UN number : UN 1263  
Proper shipping name : PAINT  
(4-chloro-alpha,alpha,alpha-trifluorotoluene)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

DOT: As per 49CFR 173.150 (f) Combustible Liquid Exception, Material is Not Regulated.  
DOT: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant.  
IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

### TDG

UN number : UN 1263  
Proper shipping name : PAINT

Class : 3  
Packing group : III  
Labels : 3  
ERG Code : 128  
Marine pollutant : yes

### Special precautions for user

Remarks : DOT: As per 49CFR 173.150 (f) Combustible Liquid Exception, Material is Not Regulated., DOT: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant., IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### Canadian lists

No substances are subject to a Significant New Activity Notification.

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA BC OEL / C : ceiling limit  
CA ON OEL / C : Ceiling Limit (C)  
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

CA QC OEL / TWA EV	:	Time-weighted average exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.



## Sikalastic® Primer

Revision Date 01/31/2025

Print Date 02/03/2025

---

Revision Date : 01/31/2025  
Date format : mm/dd/yyyy  
Prepared by : R & D of Sika Canada Inc.  
Material number : 532,711

CA / Z8