

FLOW CONTROL®

Additive to Increase Strength and Fluidity



PRODUCT DATASHEET

DESCRIPTION: Rapid Set® FLOW CONTROL® is a flow enhancing additive that allows higher fluidity or lower water requirement. Reducing water content by adding FLOW CONTROL will increase the final strength and durability.

USES: Use FLOW CONTROL with Rapid Set cement products. Add 1 to 4 packets of FLOW CONTROL to increase fluidity, and/or increase strength to satisfy jobsite requirements. A trial batch is recommended to fine-tune the dosage. FLOW CONTROL may be used in combination with all other products of the Rapid Set® Concrete Pharmacy®.

DIRECTIONS: Place desired amount of potable water into mixing container. Add half cement product into mixing container and mix with mechanical drill/mixer. Continue mixing while adding FLOW CONTROL 2.1-oz (60-grams) powder to mixing container. Add remaining cement product into mixing container. Follow product mixing instructions and maximum water requirements described on the package of the cement product. Mix to a workable, lump-free consistency. Do NOT exceed 4 packets per 50-lb to 70-lb bag of Rapid Set branded cement product. Too much water in the mixture may cause aggregate segregation, which can reduce strengths.

SHELF LIFE: FLOW CONTROL has a shelf life of 12 months when stored properly in a dry location, protected from moisture, out of direct sunlight, and in an undamaged package.

USER RESPONSIBILITY: Before using Rapid Set products, read current technical data sheet, bulletins, product label and safety data sheet at www.CTScement.com. It is the user's responsibility to review instructions and warnings for any Rapid Set product in current technical data sheet, bulletins, product label and safety data sheet prior to use.

WARNING: CAUSES MILD SKIN IRRITATION. MAY BE HARMFUL IN CONTACT WITH SKIN. CAUSES SERIOUS EYE IRRITATION. Protect eyes with goggles or safety glasses with side shields. Cover skin with protective clothing. Use chemical resistant gloves and waterproof boots. In case of skin contact, immediately wash with soap and water. In case of eye contact, flush immediately and repeatedly with clean water, and consult a physician. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Please refer to the SDS and www.CTScement.com for additional safety information regarding this material.

LIMITED WARRANTY: CTS CEMENT MANUFACTURING CORP. (CTS) warrants its materials to be of good quality and, at its option, will replace or refund the purchase price of any material proven to be defective within one (1) year from date of purchase. The above remedies shall be the limit of CTS's responsibility. Except for the foregoing, all warranties expressed or implied, including merchantability and fitness for a particular purpose, are excluded. CTS shall not be liable for any consequential, incidental, or special damages arising directly or indirectly from the use of the materials.

⚠ WARNING

CANCER and REPRODUCTIVE HARM - www.P65Warnings.ca.gov

OVERVIEW

Highlights:

For use with Rapid Set® cement products

Water reducing additive

Increases fluidity

Increases compressive strength

Manufacturer:

CTS Cement Manufacturing Corp.
12442 Knott St.
Garden Grove, CA 92841
Tel: 800-929-3030 | Fax: 714-379-8270
Web: www.CTScement.com
E-mail: info@CTScement.com





AVAILABLE PACKETS:

SET CONTROL®

Set Retarding Admixture

A set retarding additive that extends the setting time, allowing more time for placing and finishing.

FLOW CONTROL®

Increase Strength & Fluidity

A plasticizing additive that allows higher fluidity or a lower water requirement. Reducing water content by adding Flow Control will increase the final strength and durability.

CORROSION INHIBITOR

Protection Against Corrosion

A high performance additive designed to extend the life of reinforced concrete structures.

BOND

Vinyl Polymer Additive

A polymer modifying additive that improves adhesion to the application surface.

DARK

Gray Pigment Admixture

A pigment additive that darkens the color. Use varying amounts to achieve a desired shade of gray.

FAST

Accelerating Additive

An accelerating additive that improves performance when experiencing delayed setting times in cold weather applications.

FIBER

Synthetic Fiber Reinforcement

A synthetic fiber additive that reduces potential cracking issues.

LIGHT

White Pigment Admixture

A pigment additive that lightens the color. Use varying amounts to achieve a desired tint.

EISENWALL® SET CONTROL

Set Retarding Admixture

A set retarding additive for Eisenwall Cement that extends the setting time, allowing more time for placing and finishing.

MORE INFORMATION

Concrete Pharmacy® Specialty Additives

Customize your cement mixtures for packaged cement, mortar, concrete, plaster and grout

Easy To Use: Just add to the mixing water

Available in Convenient Packets: Easy control of dosages

Visit CTScement.com

Discover additional products and services



USGBC and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.