

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

---

### SECTION 1. IDENTIFICATION

Product name : Sikadur-914 Formerly MSeal 914 Accel

Product code : 000000000050340396

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE  
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 2

Reproductive toxicity : Category 1B

Specific target organ toxicity : Category 1  
- single exposure

Specific target organ toxicity : Category 3 (Respiratory system)  
- single exposure

Specific target organ toxicity : Category 2  
- repeated exposure

Short-term (acute) aquatic hazard : Category 2

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

Long-term (chronic) aquatic hazard : Category 3

### GHS label elements

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H341 Suspected of causing genetic defects.  
H351 Suspected of causing cancer.  
H360FD May damage fertility. May damage the unborn child.  
H370 Causes damage to organs.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H401 Toxic to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

---

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P307 + P311 IF exposed: Call a POISON CENTER or doctor/physician.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

### Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	$\geq 10 - < 20$
ethylbenzene	100-41-4	$\geq 1 - < 5$
dibutyltin dilaurate	77-58-7	$\geq 1 - < 5$
cumene	98-82-8	$\geq 0.1 - < 1$

Actual concentration is withheld as a trade secret

---

## SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.
- If inhaled : Keep patient calm, remove to fresh air, seek medical attention.
- In case of skin contact : Immediately wash thoroughly with soap and water, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

---

- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
Suspected of causing genetic defects.  
Suspected of causing cancer.  
May damage fertility. May damage the unborn child.  
Causes damage to organs.  
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray
- Hazardous combustion products : fumes/smoke  
harmful vapours  
Carbon oxides  
nitrogen oxides  
carbon black
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water.  
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
Wear eye/face protection.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Pick up with suitable appliance and dispose of.  
Dispose of absorbed material in accordance with regulations.
-

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Product is not explosive.
- Advice on safe handling : Avoid inhalation of dusts/mists/vapours.  
Avoid skin contact.  
Ensure adequate ventilation.  
No special measures necessary provided product is used correctly.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.
- Materials to avoid : Observe TRGS 509/510 storage rules.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA P0
ethylbenzene	100-41-4	TWA	100 ppm 435 mg/m3	OSHA P0
		TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
cumene	98-82-8	STEL	125 ppm 545 mg/m3	OSHA P0
		TWA	5 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
xylene	1330-20-7	Methylhip-puric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g cre-atinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-oxalic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

**Engineering measures** : No applicable information available.

### Personal protective equipment

Respiratory protection : No applicable information available.

Hand protection

Remarks : No applicable information available.

Eye protection : No applicable information available.

Skin and body protection : No applicable information available.

Protective measures : Do not inhale dust/fumes/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

---

Odor : aromatic, solvent

Boiling point : 277.00 - 500.00 °F / 136.11 - 260.00 °C

Flash point : 93.9 °F / 34.4 °C  
Method: Standard Method of Test for Flash Point by Setaflash Closed Tester, closed cup

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Highly flammable.  
Method: derived from flash point

Upper explosion limit / Upper flammability limit : 6.7 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Relative vapor density : Heavier than air.

Relative density : 1.0262

Density : 1.0262 g/cm<sup>3</sup> (68 °F / 20 °C)

Solubility(ies)  
Water solubility : slightly soluble  
Solubility in other solvents : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, kinematic : 56 mm<sup>2</sup>/s (104 °F / 40 °C)

Explosive properties : Not explosive  
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : Not applicable

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

---

### SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.
- Chemical stability : The product is stable if stored and handled as prescribed/indicated.
- Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.
- Conditions to avoid : See SDS section 7 - Handling and storage.
- Incompatible materials : Oxidizing agents
- Hazardous decomposition products : carbon oxides
- 

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Product:

- Acute oral toxicity : Remarks: No applicable information available.
- Acute inhalation toxicity : Remarks: No applicable information available.
- Acute dermal toxicity : Remarks: No applicable information available.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

##### Skin sensitization

May cause an allergic skin reaction.

##### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

Suspected of causing genetic defects.

#### Carcinogenicity

Suspected of causing cancer.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
	Group 2B: Possibly carcinogenic to humans cumene	98-82-8

**OSHA** No component of this product present at levels greater than or equal to 0.1% is



# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

---

on OSHA's list of regulated carcinogens.

**NTP**      Reasonably anticipated to be a human carcinogen  
cumene      98-82-8

### Reproductive toxicity

May damage fertility. May damage the unborn child.

### STOT-single exposure

May cause respiratory irritation.  
Causes damage to organs.

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

Not classified based on available information.

### Further information

#### Product:

Remarks      :    The product has not been tested. The statement has been derived from the properties of the individual components.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity      :    Toxic to aquatic life.

Chronic aquatic toxicity      :    Harmful to aquatic life with long lasting effects.

### Persistence and degradability

#### Product:

Biodegradability      :    Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

### Bioaccumulative potential

#### Product:

Bioaccumulation      :    Remarks: No data available.  
Discharge into the environment must be avoided.

### Mobility in soil

No data available

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

---

### Other adverse effects

#### Product:

Additional ecological information : No data available  
Do not discharge product into the environment without control.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### **UNRTDG**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(ETHYLBENZENE, XYLENE)  
Class : 3  
Packing group : III  
Labels : 3

#### **IATA-DGR**

UN/ID No. : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(ETHYLBENZENE, XYLENE)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

#### **IMDG-Code**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(ETHYLBENZENE, XYLENE)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1993  
Proper shipping name : Flammable liquids, n.o.s.  
(ETHYLBENZENE, XYLENE)  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylene	1330-20-7	100	503
ethylbenzene	100-41-4	1000	20140

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

xylene	1330-20-7
ethylbenzene	100-41-4
cumene	98-82-8

### US State Regulations

#### Pennsylvania Right To Know

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."-	25791-96-2
1,2,3- propanetriyltris[.omega.-hydroxy-	
xylene	1330-20-7
Butane-1,3-diol	107-88-0
ethylbenzene	100-41-4
cumene	98-82-8

#### New Jersey Right To Know

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha."- 25791-96-2  
1,2,3- propanetriyltris[.omega.-hydroxy- 1330-20-7  
xylene 107-88-0  
Butane-1,3-diol 100-41-4  
ethylbenzene 77-58-7  
dibutyltin dilaurate

### California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory  
DSL : All components of this product are on the Canadian DSL

### TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
NIOSH REL : USA. NIOSH Recommended Exposure Limits

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version 1.0      Revision Date: 01/06/2022      SDS Number: 000000261445      Date of last issue: -  
Date of first issue: 01/06/2022

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek  
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday  
OSHA P0 / TWA : 8-hour time weighted average  
OSHA P0 / STEL : Short-term exposure limit  
OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/06/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

# SAFETY DATA SHEET

## Sikadur-914 Formerly MSeal 914 Accel



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/06/2022	000000261445	Date of first issue: 01/06/2022

---

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN