

## SikaThorolastic-850 neutral factory the Formerly MProtect EL 850 col ser neu

Version Revision Date: SDS Number: Date of last issue: 09/08/2020 2.0 03/19/2021 000000261061 Date of first issue: 09/08/2020

#### **SECTION 1. IDENTIFICATION**

Product name : SikaThorolastic-850 neutral factory tbse Formerly MProtect EL

850 col ser neu

Product code : 00000000051703184

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

## **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Carcinogenicity (Inhalation) : Category 1A

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

**GHS** label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : H350i May cause cancer by inhalation.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P201 Obtain special instructions before use.



## SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

P202 Do not handle until all safety precautions have been read

and understood.

P273 Avoid release to the environment.

Response:

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 15 - < 50
Titanium dioxide	13463-67-7	>= 1 - < 3
Silicon dioxide	7631-86-9	>= 0.3 - < 3
zinc oxide	1314-13-2	>= 0.3 - < 1
Quartz (SiO2) particle size < 63 µm	14808-60-7	>= 0 - < 1
2-amino-2-methylpropanol	124-68-5	>= 0.1 - < 1
diuron	330-54-1	>= 0 - < 0.2
carbendazim	10605-21-7	>= 0 - < 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	>= 0 - < 0.1

## **SECTION 4. FIRST AID MEASURES**

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15

to 20 minutes. Remove contact lenses, if present, after first 5

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,



## SikaThorolastic-850 neutral factory the Formerly MProtect EL 850 col ser neu

Version Revision Date: SDS Number: Date of last issue: 09/08/2020 2.0 03/19/2021 000000261061 Date of first issue: 09/08/2020

seek medical attention. Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

May cause cancer by inhalation.

Notes to physician : Treat symptomatically.

## **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black carbon oxides

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.



## SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

Version Revision Date: SDS Number: Date of last issue: 09/08/2020 2.0 03/19/2021 000000261061 Date of first issue: 09/08/2020

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Recommended storage tem-

perature

> 41 °F / > 5 °C

Further information on stor-

age stability

PROTECT FROM FREEZING DURING THE COLD-SEASON

(BELOW 40°F / 5°C).

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
zinc oxide	1314-13-2	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		STEL value (Respirable fraction)	10 mg/m3	ACGIHTLV
		REL value (fumes/smok e)	5 mg/m3	NIOSH



# SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

REL value (dust)	5 mg/m3	NIOSH
STEL value (fumes/smok e)	10 mg/m3	NIOSH
Ceil_Time (dust)	15 mg/m3	NIOSH
PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
PEL (fumes/smok e)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
TWA value (fumes/smok e)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
STEL value (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
TWA (Respirable particulate matter)	2 mg/m3	ACGIH
STEL (Respirable particulate matter)	10 mg/m3	ACGIH
TWA (Dust)	5 mg/m3	NIOSH REL
TWA (Fumes)	5 mg/m3	NIOSH REL
ST (Fumes)	10 mg/m3	NIOSH REL
C (Dust)	15 mg/m3	NIOSH REL
TWA (Fumes)	5 mg/m3	OSHA Z-1
TWA (total dust)	15 mg/m3	OSHA Z-1
TWA (respirable fraction)	5 mg/m3	OSHA Z-1
TWA (Total dust)	10 mg/m3	OSHA P0
TWA (respirable dust fraction)	5 mg/m3	OSHA P0



# SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

	1	1	1	1
		TWA (Fumes)	5 mg/m3	OSHA P0
		STEL (Fumes)	10 mg/m3	OSHA P0
Quartz (SiO2) particle size < 63 µm	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respir- able)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respir- able)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respir- able)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m3	29 CFR



# SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

		(Respirable fraction)		1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Silicon dioxide	7631-86-9	REL value	6 mg/m3	NIOSH
		TWA value	6 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA value	0.8 mg/m3	29 CFR 1910.1000 (Table Z-3)
		TWA (Dust)	20 Million parti- cles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA (Res- pirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA	6 mg/m3 (Silica)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3	ACGIH



## SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

Version Revision Date: SDS Number: Date of last issue: 09/08/2020 2.0 03/19/2021 000000261061 Date of first issue: 09/08/2020

(Titanium dioxide)

**Engineering measures** : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : light protective clothing

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : pigmented

Odor : mild, like acrylic

Odor Threshold : not determined

pH : 8 - 9.5

Melting point : No data available



## SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

Boiling point : 212 °F / 100 °C

Flash point : A flash point determination is unnecessary due to the high

water content.

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : 1

Relative density : 1.27

Density : approx. 1.0 g/cm3 (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : partly soluble

Solubility in other solvents : partly soluble

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No data available

Molecular weight : No data available



## SikaThorolastic-850 neutral factory the Formerly MProtect EL 850 col ser neu

Version Revision Date: SDS Number: Date of last issue: 09/08/2020 2.0 03/19/2021 000000261061 Date of first issue: 09/08/2020

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong bases

Strong acids

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

## Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

## Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

May cause cancer by inhalation.

## Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.



## SikaThorolastic-850 neutral factory the Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

**Aspiration toxicity** 

Not classified based on available information.

**Further information** 

**Product:** 

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

**SECTION 12. ECOLOGICAL INFORMATION** 

**Ecotoxicity** 

**Product:** 

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**Components:** 

zinc oxide:

M-Factor (Acute aquatic tox-

city)

M-Factor (Chronic aquatic

toxicity)

: 1

diuron:

M-Factor (Acute aquatic tox- :

10

icity)

M-Factor (Chronic aquatic

toxicity)

10

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

Persistence and degradability

No data available

**Bioaccumulative potential** 

No data available



## SikaThorolastic-850 neutral factory the Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

## Mobility in soil

No data available

## Other adverse effects

#### **Product:**

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Residues should be disposed of in the same manner as the

substance/product.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

#### **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

## **UNRTDG**

Not regulated as a dangerous good

## IATA-DGR

Not regulated as a dangerous good

### **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **Domestic regulation**

## 49 CFR

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

## **US State Regulations**

## Pennsylvania Right To Know

propane-1,2-diol 57-55-6



## SikaThorolastic-850 neutral factory thse Formerly MProtect EL 850 col ser neu

Version 2.0	Revision Date: 03/19/2021	SDS Number: 000000261061	Date of last issue: 09/08/2020 Date of first issue: 09/08/2020
	zinc oxide Limestone Silicon dioxide Titanium dioxide		1314-13-2 1317-65-3 7631-86-9 13463-67-7
New	Jersey Right To Know		
	propane-1,2-diol zinc oxide Limestone Titanium dioxide Quartz (SiO2) parti Distillates (petroleu	cle size < 63 µm ım), hydrotreated heav	57-55-6 1314-13-2 1317-65-3 13463-67-7 14808-60-7 vy naphthenic 64742-52-5

## California Prop. 65

WARNING: This product can expose you to chemicals including ethylene oxide, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as


active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

#### **SECTION 16. OTHER INFORMATION**


### **Further information**

## NFPA 704:



Special hazard

## HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)



## SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

Version SDS Number: Date of last issue: 09/08/2020 Revision Date: 2.0 03/19/2021 000000261061 Date of first issue: 09/08/2020

1910.1000

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000 29 CFR 1910.1000 (Table Z-

OSHA - Specifically Regulated Substances (29 CFR 29 CFR 1910.1001-1050

1910.1001-1050)

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

**ACGIHTLV** American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH USA. NIOSH Recommended Exposure Limits NIOSH REL

OSHA Specifically Regulated Chemicals/Carcinogens **OSHA CARC** USA. OSHA - TABLE Z-1 Limits for Air Contaminants -OSHA P0

1910.1000

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-OSHA Z-1

its for Air Contaminants

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- :

1-A) / STEL value

Short Term Exposure Limit (STEL):

Time Weighted Average (TWA):

Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z- :

1-A) / TWA value 29 CFR 1910.1000 (Table Z- :

1) / PEL 29 CFR 1910.1000 (Table Z- :

Permissible exposure limit

3) / TWA value

29 CFR 1910.1001-1050 /

**OSHA Action level:** 

OSHA Action level

29 CFR 1910.1001-1050 / Time Weighted Average (TWA):

TWA value

ACGIH / TWA 8-hour, time-weighted average Short-term exposure limit ACGIH / STEL

Short Term Exposure Limit (STEL): ACGIHTLV / STEL value ACGIHTLV / TWA value Time Weighted Average (TWA):

NIOSH / Ceil Time Ceiling Limit Value and Time Period (if specified):

NIOSH / REL value Recommended exposure limit (REL): NIOSH / STEL value Short Term Exposure Limit (STEL):

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C Ceiling value not be exceeded at any time.

Permissible exposure limit (PEL) OSHA CARC / PEL 8-hour time weighted average OSHA P0 / TWA Short-term exposure limit OSHA P0 / STEL 8-hour time weighted average OSHA Z-1 / TWA OSHA Z-3 / TWA 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency



## SikaThorolastic-850 neutral factory the Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 03/19/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND



# SikaThorolastic-850 neutral factory tbse Formerly MProtect EL 850 col ser neu

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/08/2020

 2.0
 03/19/2021
 000000261061
 Date of first issue: 09/08/2020

INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN