

SAFETY DATA SHEET

Sikagard® Color A50 Lo-VOC



Version
1.1

Revision Date:
12/14/2016

SDS Number:
100000004271

SECTION 1. IDENTIFICATION

Product name : Sikagard® Color A50 Lo-VOC

Manufacturer or supplier's details

Company name : Sika Canada Inc.
601, avenue Delmar
Pointe-Claire, QC H9R 4A9
Canada
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's
e-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Sub-category 1B

Reproductive toxicity : Category 2

Specific target organ system-
ic toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ system-
ic toxicity - repeated expo-
sure (Inhalation) : Category 2

Aspiration hazard : Category 1

GHS label elements

Version
1.1Revision Date:
12/14/2016SDS Number:
100000004271

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements

: **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P331 Do NOT induce vomiting.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.

Version
1.1Revision Date:
12/14/2016SDS Number:
10000004271

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Warning : Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Other hazards

None known.

Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
4-chloro-a,a,a-trifluorotoluene	98-56-6	>= 55 - <= 65
Toluene	108-88-3	>= 10 - < 20
trimethoxy(2-methylpropyl)silane	18395-30-7	>= 2 - < 5
methanol	67-56-1	>= 0 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Version
1.1Revision Date:
12/14/2016SDS Number:
10000004271

	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Risk of serious damage to the lungs (by aspiration). irritant effects sensitizing effects Aspiration may cause pulmonary edema and pneumonitis. Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.
Notes to physician	: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: Water High volume water jet
Specific hazards during fire fighting	: Do not use a solid water stream as it may scatter and spread fire.
Further information	: Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.



Version
1.1

Revision Date:
12/14/2016

SDS Number:
10000004271

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

Version
1.1Revision Date:
12/14/2016SDS Number:
10000004271**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene	108-88-3	TWA	50 ppm 188 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m ³	CA QC OEL
methanol	67-56-1	TWA	20 ppm	ACGIH
		TWA	200 ppm 262 mg/m ³	CA AB OEL
		STEL	250 ppm 328 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		TWAEV	200 ppm 262 mg/m ³	CA QC OEL
		STEV	250 ppm 328 mg/m ³	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after	15 mg/l	ACGIH BEI

Version
1.1Revision Date:
12/14/2016SDS Number:
10000004271

				exposure ceases)		
--	--	--	--	---------------------	--	--

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Color : colored
Odor : irritating

SAFETY DATA SHEET

Sikagard® Color A50 Lo-VOC



Version
1.1

Revision Date:
12/14/2016

SDS Number:
100000004271

Odor Threshold	: No data available
pH	: not determined
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: 28 °C (82 °F) Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 1 %(V)
Vapor pressure	: 28.9975 hpa (21.750 mmHg)
Relative vapor density	: No data available
Density	: 1.020 g/ml (23 °C (73 °F) ())
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: not determined
Explosive properties	: No data available
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reac-	: Stable under recommended storage conditions.

Version
1.1Revision Date:
12/14/2016SDS Number:
100000004271

tions Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION
Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Ingredients:**4-chloro-a,a,a-trifluorotoluene:**

Acute oral toxicity : LD50 Oral (Rat): > 13,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 33 mg/l
Exposure time: 4 h
Test atmosphere: vapor

methanol:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg
Method: Converted acute toxicity point estimate

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg
Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Version
1.1Revision Date:
12/14/2016SDS Number:
100000004271

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

Group 2B: Possibly carcinogenic to humans

titanium dioxide

13463-67-7

NTP

Not applicable

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****4-chloro-a,a,a-trifluorotoluene:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 3 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2 mg/l
aquatic invertebrates : Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.41
mg/l
Exposure time: 72 h

M-Factor (Acute aquatic tox- : 1
icity)

M-Factor (Chronic aquatic : 1
toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Version
1.1Revision Date:
12/14/2016SDS Number:
10000004271**Mobility in soil**

No data available

Other adverse effects**Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
May be harmful to the environment if released in large quantities.
Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**Domestic regulation****TDG (road/train)**

UN number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3

International Regulations**IATA-DGR**

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

SAFETY DATA SHEET

Sikagard® Color A50 Lo-VOC



Version
1.1

Revision Date:
12/14/2016

SDS Number:
100000004271

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Revision Date : 12/14/2016
Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Full text of other abbreviations

ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association

SAFETY DATA SHEET

Sikagard® Color A50 Lo-VOC



Version
1.1

Revision Date:
12/14/2016

SDS Number:
100000004271

IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

CA / Z8