



## SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikafloor® Duochem 9017N PART A** REVISION DATE: November 6th, 2015

USAGE: Epoxy binder

MANUFACTURER/SUPPLIER: SIKA CANADA INC.  
601, avenue Delmar  
Pointe Claire, QC  
H9R 4A9

**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666**

TDG CLASSIFICATION:	Not regulated	WHMIS Classification:	D2B
UN NUMBER:	Not applicable	Class:	Not applicable
Packaging Group	Not applicable		

## SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD <sub>50</sub> (mg/kg) (route, species)	LC <sub>50</sub> (species, route)
EPOXY RESIN	40-70	Not available	25085-99-8	> 5000 (oral, rat)	Not available

## SECTION III: PHYSICAL CHARACTERISTICS

Physical State:	Liquid	Boiling Point:	> 200°C
Appearance and Odor:	Colored liquid, epoxide odor	Freezing Point:	Not established
Odor Threshold:	Not established	Density:	1.25 - 1.30 g/ml
Evaporation Rate:	< 1 (N-Butyl acetate=1)	Water Solubility:	No
Vapor Density:	> 1 (air=1)	pH:	Not established
Vapor Pressure:	Not applicable	% volatility:	Not applicable
		Water/Oil Distribution:	Not established



PRODUCT: **Sikafloor® Duochem 9017N PART A**

**SECTION IV: FIRE AND EXPLOSION HAZARDS**

Flammability:	No	TDG Flammability Class:	Not regulated
If Yes, under what conditions:		Flammable upper limits (% vol.):	Not established
Extinguishing methods:	Foam, dry chemical products, CO <sub>2</sub> , water hose.	Flammable lower limits (% vol.):	Not established
		Flash Point (method used):	> 93.3°C (tcc)
		Auto-ignition temperature:	Not established
		Dangerous Combustion Products:	COx, phenol.
Special Methods:	Firefighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.	Protect from mechanical impact:	No
		Protect from static discharge:	No

**SECTION V: REACTIVITY**

Chemical stability:	Yes	Dangerous decomposition products:	COx, phenol
If not, under what conditions	But avoid excessive heat.		
Incompatibility with other material:	Yes	Polymerization Risks:	No.
If Yes, which ones:	Oxidizer, strong bases and acids.		



PRODUCT: Sikafloor® Duochem 9017N PART A

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations.

Carcinogenicity: Not Established

Skin: May cause skin irritations, dermatitis, allergic reactions and sensitization.

Toxic effects on reproduction: Not Established

Inhalation: Vapor and mist may cause respiratory tract irritation.

Teratogenicity: Not Established

Ingestion: May cause gastro-intestinal irritation, nausea, vomiting and diarrhea.

Mutagenicity: Not Established

Product with synergistic effects: Not Established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: Sikafloor® Duochem 9017N PART A

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand or other absorbent material. Residue may be removed with steam or hot water and soap. All precautions should be taken when cleaning the spill with solvent.

Handling and Equipment methods: Avoid skin, eye and clothing contact.

Warehouse requirements: Keep all containers closed. Keep in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class.

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikafloor® Duochem 9017N PART A

## SECTION VIII: FIRST AID

**Skin:** Remove contaminated clothing and shoes.  
Wash immediately with plenty of soap and water.  
Wash clothing before re-wearing.  
Consult a physician if required.

**Eyes:** Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.  
Consult a physician if required.

**Inhalation:** In the case of overexposure, evacuate to fresh air.  
Consult a physician if required.

**Ingestion:** Drink plenty of water. Do not induce vomiting.  
Do not give anything by mouth to an unconscious person.  
See a physician immediately.

## SECTION IX: PREPARATION INFORMATION

Prepared By: Sika Canada R & D.  
Telephone #: (514) 697-2610  
Fax #: (514) 694-2792

**Notice To Reader**

*The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.*

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

*All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.*

AQ 191 A

Date: 2012/02/01

App: S.G.



## SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikafloor® Duochem 9017N PART B**REVISION DATE: March 4<sup>th</sup>, 2016

USAGE: Hardener

MANUFACTURER/SUPPLIER: SIKA CANADA INC.  
601, avenue Delmar  
Pointe Claire, QC  
H9R 4A9**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666**

TDG CLASSIFICATION: Polyamines, Liquid, corrosive, N.O.S. (TRIETHYLENE TETRAMINE &amp; ISOPHORONEDIAMINE)

WHMIS Classification: D2B, E  
Class: 8UN NUMBER: 2735  
Packaging Group: III

## SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD <sub>50</sub> (mg/kg) (route, species)	LC <sub>50</sub> (species, route)
POLYAMINE: TRIETHYLENE TETRAMINE ADDUCT	60-100	Not available	26950-63-0	Not available	Not available
BENZYL ALCOHOL	7-13	Not available	100-51-6	>1230 (oral, rat)	>4000mg/l (inhalation, rat)
ISOPHORONEDIAMINE	1-5	Not available	2855-13-2	Not available	Not available

## SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid  
Appearance and Odor: Amber clear with amine odor  
Odor Threshold: Not established  
Evaporation Rate: < 1 (N-Butyl acetate=1)  
Vapor Density: > 1 (air=1)  
Vapor Pressure: Not applicableBoiling Point: 205°C  
Freezing Point: Not established  
Density: 1.01 – 1.03 g/ml  
Water Solubility: Not established  
pH: Alkaline  
% volatility: Not established  
Water/Oil Distribution: Not established



PRODUCT: Sikafloor® Duochem 9017N

PART B

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions:	No	TDG Flammability Class:	None
Extinguishing methods:	Foam, dry chemical products, CO <sub>2</sub> , water hose.	Flammable upper limits (% vol.):	Not established
Special Methods:	Fire fighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.	Flammable lower limits (% vol.):	Not established
		Flash Point (method used):	~ 96°C
		Auto-ignition temperature:	Not established
		Dangerous Combustion Products:	Carbon oxides, nitrogen oxides and ammonia.
		Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY DATA

Chemical stability: If not, under what conditions	Yes	Dangerous decomposition products:	Carbon oxides, nitrogen oxides and ammonia.
Incompatibility with other material: If Yes, which ones	Yes Oxidizing agents, acids, bases and nitrites.	Polymerization Risks:	No



PRODUCT: Sikafloor® Duochem 9017N PART B

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations. May cause severe burns. May cause blindness.

Skin: May be irritating to the skin, may cause severe burns, can be absorbed by skin. Contact may cause necrosis, dermatitis, allergic reactions, and sensitization.

Inhalation: Vapors or mist of this product may cause irritation.

Ingestion: May cause severe burns to the mouth, throat and stomach. May cause nausea, vomiting, dizziness, diarrhea, damages to the lungs and death.

Carcinogenicity: Not Established

Toxic effects on reproduction: Not Established

Teratogenicity: Not Established

Mutagenicity: Not Established

Product with synergistic effects: Not Known

**An over-exposure** may cause breathing difficulty, headaches, nausea, damages to the lungs, vomiting, sensitization and dizziness. May cause problems to the skin, eyes, and lungs. May aggravate allergic and respiratory problems.

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.





PRODUCT: Sikafloor® Duochem 9017N PART B

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: Use a NIOSH /MSHA approved air purifying organic vapor mask if ventilation is inadequate.

Eyes Full face mask or safety glasses

Shoes: Leather

Clothing: Rubber apron

Other: Eye wash station, shower

OTHERS

Ventilation: Use adequate ventilation

Procedure in case of leaks: Remove all sources of ignition (flames, sparks, etc.). Provide adequate ventilation. Avoid prolonged breathing of vapors. Remove to a container or absorb with clay, diatomaceous earth or other suitable inert absorbent.

Handling and Equipment Methods: Avoid inhalation, skin and eye contact. Wash repeatedly with soap and water during the workday.

Warehouse Requirements: Keep all containers closed in a cool, dry and well-ventilated area.

Special Shipping Instructions: See TDG class.

Waste Disposal: Dispose of residues according to municipal, provincial or federal laws for disposal of chemicals. Do not incinerate closed containers.



PRODUCT: Sikafloor® Duochem 9017N PART B

SECTION VIII: FIRST AID

**Skin:** Remove contaminated clothing and shoes.  
Wash immediately with plenty of soap and water.  
Throw away shoes that were soiled on the inside.  
Wash clothing before re-wearing.  
Consult a physician if necessary.

**Eyes:** Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.  
The eye rinse within the first minute is essential to ensure maximum protection.  
Consult a physician immediately.

**Inhalation:** In the case of overexposure, evacuate to fresh air.  
Consult a physician if required.

**Ingestion:** Drink plenty of water. Do not induce vomiting.  
Do not give anything by mouth to an unconscious person.  
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: Sika Canada R & D.  
Telephone #: (514) 697-2610  
Fax #: (514) 694-2792

**Notice To Reader**

*The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.*

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

*All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.*