MaxFlash Flashing Membrane



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/01/2023

 3.0
 06/09/2023
 000000699016
 Date of first issue: 05/27/2020

SECTION 1. IDENTIFICATION

Product name : MaxFlash Flashing Membrane

Product code : 00000000050440171

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Sika MBCC Canada, Inc.

Address : 601 DELMAR AVE

Pointe-Claire QC H9R 4A9

Emergency telephone : ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use : Waterproof coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Reproductive toxicity : Category 1B

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer by inhalation.

H360 May damage fertility or the unborn child.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

MaxFlash Flashing Membrane



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/01/2023

 3.0
 06/09/2023
 000000699016
 Date of first issue: 05/27/2020

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture based on:

polymers

Components

| Chemical name | Common Name/Synonym | CAS-No. | Concentration (% w/w) |
|--|----------------------------------|------------|-----------------------|
| calcium carbonate | Carbonic acid calcium salt (1:1) | 471-34-1 | >= 30 - < 50 |
| Limestone | Calcium car- bonate | 1317-65-3 | >= 10 - < 20 |
| Titanium dioxide | C.I. Pigment White 6 | 13463-67-7 | >= 1 - < 5 |
| Triethoxyoctylsilane | Silane, triethox- yoctyl- | 2943-75-1 | >= 1 - < 5 |
| Calcium distearate | Octadecanoic acid, calcium salt | 1592-23-0 | >= 1 - < 5 |
| Carbon black | Lampblack | 1333-86-4 | >= 0.1 - < 1 |
| Aminoethyl aminopropyl trimethoxy silane | 1,2- Ethanediamine, | 1760-24-3 | >= 0.1 - < 1 |

MaxFlash Flashing Membrane



Version Revision Date: SDS Number: Date of last issue: 02/01/2023 3.0 06/09/2023 000000699016 Date of first issue: 05/27/2020

| | N-[3- (trimethoxysi- lyl)propyl]- | | |
|--|--|---------------|--------------|
| Proprietary amide wax** | Proprietary am- ide wax | Proprietary** | >= 0.1 - < 1 |
| bis(2,2,6,6-tetramethyl- 4-piperidyl)sebacate | Decanedioic acid, bis(2,2,6,6- tetramethyl-4- piperidinyl) ester | 52829-07-9 | >= 0.1 - < 1 |
| Dibutyltin diacetyldi- acetonate | Tin, dibu- tylbis(2,4- pentanedionato- O,O')-, (OC-6- 11)- | 22673-19-4 | >= 0.1 - < 1 |
| | Crystalline silica | | >= 0.1 - < 1 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Remove contaminated clothing.

If inhaled : If generated vapours are inhaled, move to fresh air.

Seek medical attention.

In case of skin contact : Wash thoroughly with soap and water

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open, consult an eye specialist. Remove contact lenses, if present, after first 5 minutes, then

continue rinsing for an additional 15 minutes.

If swallowed : Rinse mouth and then drink 200-300 ml of water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause cancer by inhalation.

May damage fertility or the unborn child.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

^{**} See Section 15 for HMIRA information.

^{**}The masked component(s) has only environmental hazards; HMIRA claims are not required for masked components with only environmental hazards.

MaxFlash Flashing Membrane



Version 3.0

Revision Date: 06/09/2023

SDS Number: 000000699016 Date of last issue: 02/01/2023 Date of first issue: 05/27/2020

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black

Further information The degree of risk is governed by the burning substance and

the fire conditions.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Sweep/shovel up.

Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid contact with the skin, eyes and clothing.

Conditions for safe storage Keep only in the original container in a cool, well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Protect from direct sunlight. Store protected against freezing.

Recommended storage tem-

perature

> 4 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type | Control parame- | Basis |
|------------|---------|------------|--------------------|-------|
| | | (Form of | ters / Permissible | |

MaxFlash Flashing Membrane



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/01/2023

 3.0
 06/09/2023
 000000699016
 Date of first issue: 05/27/2020

| | | exposure) | concentration | |
|--------------------------------|------------|--|--|-----------|
| calcium carbonate | 471-34-1 | TWAEV (to- | 10 mg/m3 | CA QC OEL |
| Calcium Carbonate | 471-34-1 | tal dust) | , and the second | CA QC OEL |
| | | TWA | 10 mg/m3 (Calcium car- bonate) | CA AB OEL |
| | | TWA (Total dust) | 10 mg/m3 | CA BC OEL |
| | | TWA (respirable dust fraction) | 3 mg/m3 | CA BC OEL |
| | | STEL | 20 mg/m3 | CA BC OEL |
| Limestone | 1317-65-3 | TWA | 10 mg/m3 | CA AB OEL |
| | | TWAEV (to- tal dust) | 10 mg/m3 | CA QC OEL |
| | | TWA (Total dust) | 10 mg/m3 | CA BC OEL |
| | | TWA (respirable dust fraction) | 3 mg/m3 | CA BC OEL |
| | | STEL | 20 mg/m3 | CA BC OEL |
| Titanium dioxide | 13463-67-7 | TWA | 10 mg/m3 | CA AB OEL |
| | | TWA (Total dust) | 10 mg/m3 | CA BC OEL |
| | | TWA (respirable dust fraction) | 3 mg/m3 | CA BC OEL |
| | | TWAEV (to- tal dust) | 10 mg/m3 | CA QC OEL |
| | | TWA (Respirable particulate matter) | 0.2 mg/m3 (Titanium dioxide) | ACGIH |
| | | TWA (Respirable particulate matter) | 2.5 mg/m3 (Titanium dioxide) | ACGIH |
| Calcium distearate | 1592-23-0 | TWA | 10 mg/m3 | CA AB OEL |
| | | TWA (Inhal- able) | 10 mg/m3 | CA BC OEL |
| | | TWA (Respirable) | 3 mg/m3 | CA BC OEL |
| | | TWA (Inhal- able particu- late matter) | 10 mg/m3 | ACGIH |
| | | TWA (Respirable particulate matter) | 3 mg/m3 | ACGIH |
| Dibutyltin diacetyldiacetonate | 22673-19-4 | TWA value | 0.1 mg/m3 (tin (Sn)) | ACGIHTLV |
| | | STEL value | 0.2 mg/m3 (tin (Sn)) | ACGIHTLV |





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/01/2023

 3.0
 06/09/2023
 000000699016
 Date of first issue: 05/27/2020

| | | REL value | 0.1 mg/m3 (tin (Sn)) | NIOSH |
|---------------|------------|-------------------------------------|-------------------------|--------------------------------------|
| | | PEL | 0.1 mg/m3 (tin (Sn)) | 29 CFR 1910.1000 (Table Z-1) |
| | | TWA value | 0.1 mg/m3 (tin (Sn)) | 29 CFR 1910.1000 (Table Z-1-A) |
| | | TWA | 0.1 mg/m3 (Tin) | CA AB OEL |
| | | STEL | 0.2 mg/m3 (Tin) | CA AB OEL |
| | | TWAEV | 0.1 mg/m3 (Tin) | CA QC OEL |
| | | STEV | 0.2 mg/m3 (Tin) | CA QC OEL |
| | | TWA | 0.1 mg/m3 (Tin) | CA BC OEL |
| | | STEL | 0.2 mg/m3 (Tin) | CA BC OEL |
| | | TWA | 0.1 mg/m3 (Tin) | CA ON OEL |
| | | TWA | 0.1 mg/m3 (Tin) | ACGIH |
| | | STEL | 0.2 mg/m3 (Tin) | ACGIH |
| Quartz (SiO2) | 14808-60-7 | TWA (Respirable particulates) | 0.025 mg/m3 | CA AB OEL |
| | | TWA (Respirable fraction) | 0.1 mg/m3 | CA ON OEL |
| | | TWAEV (respirable dust) | 0.1 mg/m3 | CA QC OEL |
| | | TWÁ (Respirable) | 0.025 mg/m3 (Silica) | CA BC OEL |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

MaxFlash Flashing Membrane



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/01/2023

 3.0
 06/09/2023
 000000699016
 Date of first issue: 05/27/2020

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Avoid contact with the skin, eyes and clothing.

No special measures necessary if stored and handled cor-

rectly.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : gray

Odor : faint odour

Odor Threshold : No data available

pH : insoluble

Melting point : No data available

Freezing point No data available

Boiling point : No data available

Flash point : 93.34 °C

Method: Standard Method of Test for Flash Point by Setaflash

Closed Tester

Evaporation rate : No data available

Flammability (solid, gas) : not flammable

Method: derived from flash point

Upper explosion limit / Upper : No data available

MaxFlash Flashing Membrane



Version Revision Date: SDS Number: Date of last issue: 02/01/2023 3.0 06/09/2023 000000699016 Date of first issue: 05/27/2020

flammability limit

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : approx. 12.65 lb/USg (23 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

not applicable for mixtures

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : approx. 7,000 mPa.s (23 °C)

Method: Adhesives - Determination of viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

MaxFlash Flashing Membrane



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/01/2023

 3.0
 06/09/2023
 000000699016
 Date of first issue: 05/27/2020

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

Group 2B: Possibly carcinogenic to humans

Carbon black 1333-86-4

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

MaxFlash Flashing Membrane



Version Revision Date: SDS Number: Date of last issue: 02/01/2023 3.0 06/09/2023 000000699016 Date of first issue: 05/27/2020

Remarks : The product has not been tested. The statements on toxicolo-

gy have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Calcium distearate:

Partition coefficient: n- : log Pow: 0.8

octanol/water Method: OECD Test Guideline 107

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

MaxFlash Flashing Membrane



Version **Revision Date:** SDS Number: Date of last issue: 02/01/2023 000000699016 Date of first issue: 05/27/2020 3.0 06/09/2023

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory

DSL All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000 1)

ACGIH USA. ACGIH Threshold Limit Values (TLV)

American Conference of Governmental Industrial Hygienists -**ACGIHTLV**

threshold limit values (US)

CA AB OEL Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

Canada. British Columbia OEL CA BC OEL

Ontario Table of Occupational Exposure Limits made under CA ON OEL

the Occupational Health and Safety Act.

CA QC OEL Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

NIOSH NIOSH Pocket Guide to Chemical Hazards (US)

29 CFR 1910.1000 (Table Z- :

Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA 8-hour, time-weighted average ACGIH / STEL Short-term exposure limit

MaxFlash Flashing Membrane



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/01/2023

 3.0
 06/09/2023
 000000699016
 Date of first issue: 05/27/2020

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

NIOSH / REL value : Recommended exposure limit (REL):

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 06/09/2023 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MaxFlash Flashing Membrane



Version 3.0

Revision Date: 06/09/2023

SDS Number: 000000699016

Date of last issue: 02/01/2023 Date of first issue: 05/27/2020

CA / EN