



## SECTION I: PRODUCT INFORMATION

PRODUCT: **SikaLastomer®-64**REVISION DATE: January 15<sup>th</sup>, 2015

USAGE: ONE COMPONENT SEALANT

MANUFACTURER/SUPPLIER: SIKA CANADA INC.  
601, avenue Delmar  
Pointe Claire, QC  
H9R 4A9EMERGENCY TELEPHONE NUMBER: **CANUTEC (collect) (613) 996-6666**TDG CLASSIFICATION: Non Regulated  
UN NUMBER: Not Established  
Packaging Group: Not ApplicableWHMIS Classification: D2B  
Class: Not Applicable

## SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD <sub>50</sub> (species, route)	LC <sub>50</sub> (species, route)
Amorphous Silica	5-10	Not Established	7631-86-9	Not Established	Not Established

## SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Paste(Solid as per ASTM)  
Appearance and Odor: Colored paste, no odorOdor Threshold: Not Established  
Evaporation Rate: Not Established  
Vapor Density: Not Established  
Vapor Tension: Not EstablishedBoiling Point: Not Established  
Freezing Point: Not Established  
Density: 1.1 g/ml  
Water Solubility: Not Established  
pH: Not Established  
% volatile: < 5  
Water/Oil Distribution: Not Established



PRODUCT: SikaLastomer® -64

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: No

If Yes, under what conditions:

Extinguishing methods: Foam, dry chemical products, CO<sub>2</sub>, water for large flames.

Special Methods: Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin.

TDG flammability Class: Not Regulated

Flammable upper limits (% vol.): Not Established

Flammable lower limits (% vol.): Not Established

Flash Point (method used): Not established

Auto-ignition temperature: Not Established

Dangerous Combustion Products: Carbon oxides.

Protect from mechanical impact: No

Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes

If not, under what conditions

Incompatibility with other material: Yes

If Yes, which ones: Acid, strong oxidizer,

Dangerous decomposition products: Carbon oxides.

Polymerization Risks: No



PRODUCT: **SikaLastomer<sup>®</sup>-64**

**SECTION VI: TOXIC PROPERTIES**

ROUTE OF ENTRY / CONTACT

Eyes: Irritating

Skin: Irritating. Contact may result in dermatitis.

Inhalation: May cause irritation.

Ingestion: May cause nausea, vomiting, diarrhea, constipation.

Carcinogenicity: Not established

Toxic effects on reproduction: Not established

Teratogenicity: Not established

Mutagenicity: Not established

Product with synergistic effects: Not established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: SikaLastomer®-64

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Use chemical resistant gloves.

Respiratory equipment: Not required

Eyes: Face mask or safety glasses

Shoes:

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.

PRODUCT: SikaLastomer<sup>®</sup>-64

## SECTION VIII: FIRST AID

- Skin : Remove contaminated clothing and shoes.  
Wash immediately with plenty of water.  
Wash clothing before re-wearing.  
Consult a physician if required.
- Eyes : Rinse eyes immediately with plenty of water for several minutes, while holding eyelids open, to ensure a proper wash.  
Consult a physician if required.
- Inhalation : In the case of overexposure, evacuate to fresh air.  
Consult a physician if required.
- Ingestion : Drink plenty of water or milk. Do not induce vomiting.  
Do not give anything by mouth to an unconscious person.  
See a physician immediately.

## SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.  
Telephone #: (514) 697-2610  
Fax #: (514) 694-2792

**Notice To Reader**

*The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.*

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

*All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.*