



PREMIUM MULTIPURPOSE EPOXY GROUT

Sikadur[®]-53^{CA}



A premium solution combining advanced formulation and versatility for 3-in-1 use: **Injection - anchoring - seating**, all with an extended application thickness range (0.5 - 30 mm) and fast return to service. Thanks to Sikadur[®]-53^{CA}, it is no longer necessary to use a specific product per type of application, but only one!

- Cures even in wet or submerged conditions
- Applicable for gravity feeding or pressure injection of cracks widths ranging from 0.5 to 30 mm
- Can be applied at a maximum thickness of 30 mm (per layer) for base plate/seating applications
- Application temperature between 5 and 30 °C
- Application capacity 5x greater than traditional epoxy (6 mm)

THE SIKA ADVANTAGE

At Sika, we offer more than just grouts ...

Ask Sika's experts how they can provide a full scope of protection and repair solutions.

For more information, contact your Technical Sales Representative or visit www.sika.ca

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.

Sika Canada Inc.
Head Office
601 Delmar Avenue
Pointe-Claire, Quebec
H9R 4A9

Other locations
Boisbriand (QC)
Brantford; Cambridge;
Sudbury; Toronto (ON)
Edmonton (AB) Surrey (BC)

1-800-933-SIKA
www.sika.ca

Scan or click below



© Sika Canada Inc. / 05.2021

**BUILDING TRUST
CONSTRUIRE LA CONFIANCE**

