PIGMENT EXTERIOR YELLOW 8882551AXX



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/07/2020

 2.0
 01/25/2023
 000000269224
 Date of first issue: 08/07/2020

SECTION 1. IDENTIFICATION

Product name : PIGMENT EXTERIOR YELLOW 8882551AXX

Product code : 00000000050702116

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Sika MBCC Canada, Inc.

Address : 601 DELMAR AVE

Pointe-Claire QC H9R 4A9

Emergency telephone : ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use : Coloring agent

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Carcinogenicity : Category 1A

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system)

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H350 May cause cancer.

H335 May cause respiratory irritation.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P261 Avoid breathing dust, fume, gas, mist, vapors or spray. P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P271 Use only outdoors or in a well-ventilated area.

PIGMENT EXTERIOR YELLOW 8882551AXX



Version Revision Date: SDS Number: Date of last issue: 08/07/2020 2.0 01/25/2023 000000269224 Date of first issue: 08/07/2020

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Ethyleneglycol	1,2-Ethanediol	107-21-1	>= 15 - < 40
talc	hydrated mag- nesium silicate	14807-96-6	>= 15 - < 40
Diethylene glycol	2,2'- Oxydiethanol	111-46-6	>= 3 - < 10
tributyl phosphate	Phosphoric acid tributyl ester	126-73-8	>= 0.1 - < 5
Polyoxyethylene nonylphenol branched ether phosphate sodi- um salt	Poly(oxy-1,2- ethanediyl), α- (nonylphenyl)- ω-hydroxy-, branched, phosphates, sodium salts	68954-84-7	>= 0.1 - < 5
Quartz (SiO2)	crystalline silica	14808-60-7	>= 0.1 - < 1
Titanium dioxide	C.I. Pigment White 6	13463-67-7	>= 0 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

PIGMENT EXTERIOR YELLOW 8882551AXX



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/07/2020

 2.0
 01/25/2023
 000000269224
 Date of first issue: 08/07/2020

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Remove contact lenses, if present.

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

May cause respiratory irritation.

May cause cancer.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod: :

ucts

harmful vapours nitrogen oxides fumes/smoke

tumes/smoke carbon black carbon oxides

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus and chemical-

protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

PIGMENT EXTERIOR YELLOW 8882551AXX



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/07/2020

 2.0
 01/25/2023
 000000269224
 Date of first issue: 08/07/2020

gency procedures If exposed to high vapour concentration, leave area immedi-

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Pick up with suitable appliance and dispose of.

Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact.

Avoid contact with eyes.

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking.

Protect from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethyleneglycol	107-21-1	(c)	100 mg/m3	CA AB OEL
		C (Vapor)	50 ppm	CA BC OEL
		C (Vapour and mist)	50 ppm 127 mg/m3	CA QC OEL
		TWA (Total, aerosol only)	10 mg/m3	CA BC OEL
		STEL (Total, aerosol only)	20 mg/m3	CA BC OEL
		C (Total, aerosol only)	100 mg/m3	CA BC OEL
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
talc	14807-96-6	TWAEV (fi- bers)	1 fibres per cubic centimeter	CA QC OEL





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/07/2020

 2.0
 01/25/2023
 000000269224
 Date of first issue: 08/07/2020

		TWAEV (respirable dust)	2 mg/m3	CA QC OEL
		TWA	0.1 fibres per cubic centimeter	CA BC OEL
		TWA (Respirable particulates)	2 mg/m3	CA AB OEL
		TWA (Respirable)	2 mg/m3	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Respirable fraction)	2 mg/m3	CA ON OEL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
tributyl phosphate	126-73-8	TWA	0.2 ppm 2.2 mg/m3	CA AB OEL
		TWA	0.2 ppm	CA BC OEL
		TWAEV (in- halable frac- tion and va- pour)	5 mg/m3	CA QC OEL
		TWA (Inhalable fraction and vapor)	5 mg/m3	ACGIH
Quartz (SiO2)	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Res- pirable frac- tion)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

PIGMENT EXTERIOR YELLOW 8882551AXX



Version Revision Date: SDS Number: Date of last issue: 08/07/2020 2.0 01/25/2023 000000269224 Date of first issue: 08/07/2020

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : yellow

Odor : slight

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

> 100 °C

Flash point : 119 °C

Method: estimate

Evaporation rate : No data available

PIGMENT EXTERIOR YELLOW 8882551AXX



Version Revision Date: SDS Number: Date of last issue: 08/07/2020 2.0 01/25/2023 000000269224 Date of first issue: 08/07/2020

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.4

Solubility(ies)

Water solubility : dispersible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

not applicable for mixtures

Autoignition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Self-heating substances : No data available

Sublimation point : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong oxidizing agents

PIGMENT EXTERIOR YELLOW 8882551AXX



Version Revision Date: SDS Number: Date of last issue: 08/07/2020 2.0 01/25/2023 000000269224 Date of first issue: 08/07/2020

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

PIGMENT EXTERIOR YELLOW 8882551AXX



Version 2.0

Revision Date: 01/25/2023

SDS Number: 000000269224

Date of last issue: 08/07/2020 Date of first issue: 08/07/2020

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

PIGMENT EXTERIOR YELLOW 8882551AXX



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/07/2020

 2.0
 01/25/2023
 000000269224
 Date of first issue: 08/07/2020

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA, ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / (c) : ceiling occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit

CA BC OEL / C : ceiling limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / C : Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Con-

PIGMENT EXTERIOR YELLOW 8882551AXX



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/07/2020

 2.0
 01/25/2023
 000000269224
 Date of first issue: 08/07/2020

centration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 01/25/2023 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN