

Sarnavap Self-Adhered Primer WB (water base)

Description	Sarnavap Self-Adhered Primer WB is a polymer emulsion-based primer designed to improve the adhesion of the Sarnavap Self-Adhered membrane on most substrates. Particularly recommended when the use of solvent-based primer is not advised and/or not permitted.
Composition	<ul style="list-style-type: none">■ See Material Safety Data Sheet for composition information.■ VOC Content: 3 g/L
Features	<ul style="list-style-type: none">■ Enhanced adhesion strength between primed substrates and Sarnavap Self-Adhered membrane.
Packaging/Storage	19 L (5 US gal.) pails. <ul style="list-style-type: none">■ Shelf Life: 12 months in the original sealed container when kept from freezing temperatures.
Installation	<p>Sarnavap Self-Adhered Primer WB must be shaken well before use. Apply to clean and dry surfaces. Minimum application temperature: 5°C (41°F). Application rate will vary depending on substrate with an average coverage for porous surfaces of 0.3 to 0.5 L/m² (0.74 to 1.22 US gal./sq.) and 0.1 to 0.25 L/m² (0.25 to 0.61 US gal./sq.) for non porous surfaces. Apply the primer with a brush, roller or spray and allow primer to dry completely. Sarnavap Self-Adhered membranes must be installed on the same day as the application of Sarnavap Self-Adhered Primer WB.</p> <p>Spraying equipment recommendations:</p> <ol style="list-style-type: none">1. Spray tip size: between 20 and 25 mils2. Pressure: 1300 psi continuous
Availability	Sarnavap Self-Adhered Primer WB is available directly from Sika Canada Authorized Applicators when used within a Sarnafil® Roofing or Waterproofing System. Contact Sika Canada or visit www.sika.ca for further information.
Warranty	As a Sika Canada-supplied accessory, Sarnavap Self-Adhered Primer WB is included in Sika Canada's Standard or System Warranty.
Maintenance	<p>Sarnavap Self-Adhered Primer WB requires no maintenance.</p> <p>Periodic maintenance of a Sarnafil® system ensures extended performance and reduces life cycle costs. Consistent with industry practices, Sika Canada recommends inspecting the roof system for damage, plugged drains, weathered sealants, etc. at least twice a year and after each storm.</p>



Construction

Technical Support Sika Canada provides technical support. Technical staff is available to advise applicators as to the proper installation method.

Technical Data

(as manufactured):

Property	Typical Physical Properties
Colour	Blue
Specific gravity at 20°C (68°F)	1.00 kg/L
Solids Content	55%
Brookfield Viscosity at 25°C (77°F)	500 cP
Drying Time	30 minutes to 3 hours

All values are nominal.

Health and Safety Information

For information and advice on the safe handling, storage and disposal of chemical products, users should refer to the **most recent Material Safety Data Sheet** containing physical, ecological, toxicological and other safety-related data.

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions, within their shelf life. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request or can be accessed in the Internet under www.sika.ca.



Sika Canada Inc.
Head Office
601 Delmar Avenue
Pointe-Claire, Quebec
H9R 4A9

Other locations
Toronto
Edmonton
Vancouver

1-800-933-SIKA
www.sika.ca

An ISO 9001 certified company
Pointe-Claire: ISO 14001 certified EMS