

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version 3.0 Revision Date: 03/23/2024 SDS Number: 000000260459 Date of last issue: 10/07/2021
Date of first issue: 08/18/2020

SECTION 1. IDENTIFICATION

Product name : Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN
Product code : 000000000056585597

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use



Recommended use : Floor coating
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2
Skin irritation : Category 2
Skin sensitization : Category 1B
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
Short-term (acute) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version 3.0 Revision Date: 03/23/2024 SDS Number: 000000260459 Date of last issue: 10/07/2021
Date of first issue: 08/18/2020

H402 Harmful to aquatic life.

Precautionary Statements :

Prevention:

- P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing mist or vapors.
- P264 Wash skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ eye protection/ face protection.

Response:

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

Disposal:

- P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : methacrylates

Components

Chemical name	CAS-No.	Concentration (% w/w)
methyl methacrylate	80-62-6	>= 90 - <= 100

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version	Revision Date:	SDS Number:	Date of last issue: 10/07/2021
3.0	03/23/2024	000000260459	Date of first issue: 08/18/2020

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : Wash thoroughly with soap and water
If symptoms persist, seek medical advice.
- In case of eye contact : Flush with copious amounts of water for at least 15 minutes.
If irritation develops, seek medical attention.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Hazardous combustion products : harmful vapours
fumes/smoke
carbon oxides
- Further information : Keep containers cool by spraying with water if exposed to fire. Containers may rocket or explode in heat of fire. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version	Revision Date:	SDS Number:	Date of last issue: 10/07/2021
3.0	03/23/2024	000000260459	Date of first issue: 08/18/2020

-
- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Avoid contact with the skin, eyes and clothing.
Remove all sources of ignition.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil barriers).
Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Use only explosion-proof equipment.
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.
- Advice on safe handling : Wear suitable personal protective clothing and equipment.
Do not breathe vapors or spray mist.
Take precautionary measures against static discharges.
Keep away from sources of ignition - No smoking.
Provide good room ventilation even at ground level (vapours are heavier than air).
- Conditions for safe storage : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Further information on storage conditions : Vapours may travel along floor and ignite at a location distant from the handling point.
Take precautionary measures against static discharges.
Electrical equipment must be explosion-proof to the appropriate standards. Keep containers tightly closed. No smoking.
Prevent unauthorized access. Containers which are opened must be carefully resealed.
- Materials to avoid : Segregate from incompatible substances.
See SDS section 10 - Stability and reactivity.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version 3.0 Revision Date: 03/23/2024 SDS Number: 000000260459 Date of last issue: 10/07/2021
Date of first issue: 08/18/2020

Recommended storage temperature : < 86 °F / < 30 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm 410 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	100 ppm 410 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation, especially in confined areas. Exhaust fans should be explosion proof.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection

: Wear safety glasses with side shields or goggles. Wear face shield if splashing hazard exists.

Skin and body protection

: Body protection must be chosen based on level of activity and exposure. Antistatic apron

Protective measures

: Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended.

Hygiene measures

: Food, beverages, and tobacco products shall not be carried,

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version	Revision Date:	SDS Number:	Date of last issue: 10/07/2021
3.0	03/23/2024	000000260459	Date of first issue: 08/18/2020

stored, or consumed where this material is in use.
Hands and/or face should be washed before breaks and at the end of the shift.
Handle in accordance with good industrial hygiene and safety practice.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	colourless, clear
Odor	:	sweet, ester-like
Odor Threshold	:	0.5 - 1.0 ppm
pH	:	Not applicable
Melting point/freezing point	:	-54 °F / -48 °C
Boiling point/boiling range	:	212.9 °F / 100.5 °C
Flash point	:	50 °F / 10 °C Method: closed cup
Evaporation rate	:	3.1 (Butyl Acetate=1.0)
Flammability (liquids)	:	Highly flammable liquid and vapor.
Upper explosion limit / Upper flammability limit	:	12.5 %(V)
Lower explosion limit / Lower flammability limit	:	2.1 %(V)
Vapor pressure	:	27 mmHg (68 °F / 20 °C)
Relative vapor density	:	3.5 (Air = 1.0)
Relative density	:	0.96

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version	Revision Date:	SDS Number:	Date of last issue: 10/07/2021
3.0	03/23/2024	000000260459	Date of first issue: 08/18/2020

Density : 0.949 g/ml (68 °F / 20 °C)
7.92 lb/USg (68 °F / 20 °C)

Solubility(ies)
Water solubility : slightly soluble (68 °F / 20 °C)
Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 1.38

Autoignition temperature : 790 °F / 421 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Temperature of polymerization (SAPT) : > 131 °F / > 55 °C

Viscosity
Viscosity, dynamic : 0.53 mPa.s (68 °F / 20 °C)
Method: Brookfield
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Refractive index : 1.412

Sublimation point : No data available

Molecular weight : 100.12 g/mol

Minimum ignition energy : 0.89 - 0.97 mJ (73 °F / 23 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.
Follow precautionary advice and avoid incompatible materials and conditions

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version	Revision Date:	SDS Number:	Date of last issue: 10/07/2021
3.0	03/23/2024	000000260459	Date of first issue: 08/18/2020

Possibility of hazardous reactions	:	Vapors may form explosive mixture with air. Risk of hazardous polymerization under certain conditions (e.g. elevated temperatures, low inhibitor and oxygen concentration).
Conditions to avoid	:	Heat. Exposure to sunlight.
Incompatible materials	:	Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization. azo compounds polymerization catalysts Strong oxidizing agents Strong acids transition metal salts Metal oxides nitro-compounds Amines Ketones
Hazardous decomposition products	:	carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version	Revision Date:	SDS Number:	Date of last issue: 10/07/2021
3.0	03/23/2024	000000260459	Date of first issue: 08/18/2020

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version	Revision Date:	SDS Number:	Date of last issue: 10/07/2021
3.0	03/23/2024	000000260459	Date of first issue: 08/18/2020

Contaminated packaging : Uncleaned empty vessels may contain product gases which can form explosive mixtures with air. Avoid all sources of ignition.
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1247
Proper shipping name : METHYL METHACRYLATE MONOMER, STABILIZED
Class : 3
Packing group : II
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1247
Proper shipping name : Methyl methacrylate monomer, stabilized
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1247
Proper shipping name : METHYL METHACRYLATE MONOMER, STABILIZED
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1247
Proper shipping name : Methyl methacrylate monomer, stabilized

Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version 3.0 Revision Date: 03/23/2024 SDS Number: 000000260459 Date of last issue: 10/07/2021
Date of first issue: 08/18/2020

ERG Code : 129P
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methyl methacrylate	80-62-6	1000	1000

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

methyl methacrylate 80-62-6 >= 90 - <= 100 %
late

US State Regulations

Pennsylvania Right To Know

methyl methacrylate 80-62-6

New Jersey Right To Know

methyl methacrylate 80-62-6

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN


Version
3.0

Revision Date:
03/23/2024

SDS Number:
000000260459

Date of last issue: 10/07/2021
Date of first issue: 08/18/2020

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Admin-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-100 CLN Pronto Formerly MTop SRS 100CLN

Version	Revision Date:	SDS Number:	Date of last issue: 10/07/2021
3.0	03/23/2024	000000260459	Date of first issue: 08/18/2020

istration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/23/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN