SECTION I: PRODUCT INFORMATION

PRODUCT: **SikaTitan P2G+** REVISION DATE: January 15th, 2015

USE: ONE COMPONENT POLYURETHANE

MANUFACTURER/SUPPLIER: SIKA CANADA INC.

601, avenue Delmar Pointe Claire, QC

H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not Regulated WHMIS Classification: B3, D2A UN NUMBER: Not Established Class: Not Applicable

Packaging Group: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS					
Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (route, species)	LC ₅₀ (species, route)
POLYISOCYANATE PREPOLYMER	30-60	Not established	Mixture	Not established	Not established
CARBON BLACK	10-30	3.5 mg/m ³ (TWA)	1333-86-4	15 400 (oral, rat)	Not established
METHYLENE BIS PHENYL ISOCYANATE	0.1-1.0	ACGIH 0,005 ppm	101-68-8	31 600 (oral, rat)	369mg/m ³ /4H
PETROLEUM DISTILLATE	1-5	ACGIH 100 ppm (TWA)	8052-41-3	> 5 000 (oral, rat)	> 5,5 mg/L/4H (rat)

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Paste

Appearance and Odor: Hydrocarbon odor black paste

Odor Threshold: Not Established Evaporation Rate: Not Established Vapor Density: Not Established Vapor Pressure: Not Established

Boiling Point: Not Established Freezing Point: Not Established Density: 113 g/ml

Density: 1,13 g/ml Water Solubility: Not Estab

Water Solubility: Not Established Not Established Not Established Water/Oil Distribution: Not Established Not Established



PRODUCT:	SikaTitan P2G+
FIXUUUUI.	SIRATILATIFZGT

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: Combustible

If Yes, under what conditions: Flame, spark

Extinguishing methods: Foam, dry chemical

products, CO₂, water for

large flames.

Special Methods: Firefighters must wear

complete protective clothing with respiratory equipment and they must protect any exposed skin. Heated isocyanates react

strongly with water.

TDG inflammability Class:

Flammable upper limits (% vol.):

Not Regulated

Not Established

Not Established

Flash Point (method used): > 80°C

Auto-ignition temperature: Not Established Dangerous Combustion Products: Carbon oxides,

Nitrogen oxide, halogenated compounds.

Protect from mechanical impact: No

Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes

If not, under what conditions:

Dangerous decomposition products:

Should not be produced under

normal conditions of storage and use.

Incompatibility with other material: Yes

If Yes, which ones: Acid, strong

oxidizer, amine

Polymerization Risks:

No



PRODUCT: SikaTitan P2G+

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes Irritating.

Skin: Irritating. Contact may result in allergic

reactions and sensitization.

Inhalation: Vapor or mist from this product may

cause irritation.

Ingestion: Harmful if swallowed.

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting. May aggravate respiratory, skin, eye, lung problems and allergies.

If the product is applied according to the manufacturer, none of these symptoms should be encountered.

A person who is sensitized to isocyanate may have a reaction with a level of isocyanate well below the T.L.V.

Carcinogenicity: Carbon black is possibly

carcinogen according to the IARC (2B group).

Toxic effects

on reproduction: Not Established

Teratogenicity: Not Established

Mutagenicity: Not Established

Product with synergistic

effects: Not Known

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. An over exposure may cause death.



PRODUCT: SikaTitan P2G+

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Use chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case

of leaks: Absorb with sand or other

absorbent material.

Handling and Equipment

methods: Avoid skin, eye and clothing

contact

Warehouse

Requirements: Keep all containers closed in a

cool, dry and well ventilated area. Keep away from heat and open

flame.

Special Shipping

Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water

according to municipal, provincial or federal laws for disposal of

chemicals.



PRODUCT: SikaTitan P2G+

SECTION VIII: FIRST AID

Skin : Remove contaminated clothing and shoes.

Wash immediately with plenty of water.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes : Rinse eyes immediately with plenty of water for several minutes, while holding

eyelids wide open, to ensure a proper wash.

See a physician immediately.

In the case of overexposure, evacuate to fresh air.

Consult a physician if required.

Ingestion : Drink plenty of water. Do not induce vomiting.

Do not give anything by mouth to an unconscious person.

See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.

Telephone #: (514) 697-2610 Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

AQ 191 A Date: 2012/02/01 App: S.G.