



PRODUCT DATA SHEET

Sika® Stabilizer-2132 TBM T

First-fill, tail sealant grease for shielded TBMs

PRODUCT DESCRIPTION

Sika® Stabilizer-2132 TBM T is a first-fill, tail sealant grease for shielded TBM equipped with a metal brush system. It is formulated to resist high water and ground pressures, has very good pumping properties, and adheres very well to all types of surfaces.

WHERE TO USE

Sika® Stabilizer-2132 TBM T is used for:

- Sealing and protecting the metal brushes located in the tail shield before TBM start-up.

CHARACTERISTICS / ADVANTAGES

- Sealing properties designed for any current metal brush system
- Very good adhesion to metal and concrete surfaces
- Easy to pump with flexible pipe
- Improved consistency
- Resistant to washout
- Non-miscible with annulus grout

PRODUCT INFORMATION

Packaging	Drum	70 kg and 250 kg for press plate pumps
Refer to the current price list for available packaging variations.		
Appearance / Colour	Homogeneous paste, light grey	
Shelf Life	12 months from date of production	
Storage Conditions	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +35 °C. Always refer to the packaging. Refer to the current Safety Data Sheet for information on safe handling and storage.	
Density	(1.79 ± 0.05) kg/L	(EN ISO 2811-1)
Consistency	Tested at +20 °C	200 ± 10 (ASTM D217)

TECHNICAL INFORMATION

Specific Advice	Matsumura sealing test	34 bar (passed)
	Load hysteresis value (at 10mm)	6.0 N
	Sliding on metal surface (dropping time)	> 45 min
	Water spray-off test	< 5% (ASTM D4049)

APPLICATION INFORMATION

Consumption	Average consumption to fill a three-row brush system is 50 kg/m of shield circumference. Consumption depends on site conditions before the TBM excavation, and the condition of the metal brushes. Contact Sika Technical Services for additional information.
-------------	--

SYSTEMS

Compatibility	Compatible with Sika® admixtures and other Sika® products. Contact Sika Technical Services for additional information.
---------------	---

BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

ENVIRONMENT, HEALTH & SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

- IMPORTANT** Avoid discharge of the Product into the environment. Before starting up the TBM, apply the Product onto the metal brushes with a grease pump. Make sure the grease pump is as close as possible to the TBM.
Note: Keep the grease temperature above +15 °C during application.
- Perform the initial filling with a separate flexible pumping hose (minimum diameter 2"). Make sure that there is no obstruction or bottleneck after the pump.

Note: Fit a flat tube to the end of the hose in order to ease the filling operation and ensure not to damage the brushes.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be

Sika Canada Inc.

Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9
1-800-933-SIKA
www.sika.ca

Other locations

Boisbriand (Quebec)
Brantford; Cambridge;
Sudbury; Toronto (Ontario)
Edmonton (Alberta)
Surrey (British Columbia)

Product Data Sheet

Sika® Stabilizer-2132 TBM T
November 2024, Version 03.01
021404071000000130

