

Revision	Date	12/10/2024
1101011	Duio	

Print Date 12/10/2024

### **SECTION 1. IDENTIFICATION**

Product name	:	Sikagard <sup>®</sup> P 770 Part A
Other means of identification	:	No data available
Company name	:	www.sika.ca Canada Pointe-Claire, QC H9R 4A9 601, avenue Delmar Sika Canada Inc.
Telephone	:	(514) 697-2610 / 1 (800) 933-7452
Telefax	:	(514) 694-2792
E-mail address	:	ehs@ca.sika.com
Emergency telephone	:	CANUTEC (collect) (613) 996-6666 (24 hours)
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accore Skin irritation	dan :	ce with the Hazardous Products Regulations Category 2
Serious eye damage	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)
GHS label elements Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation.
Precautionary Statements	:	Prevention:



Revision Date 12/10/2024 Print Date 12/10/2024 P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. **Response:** P302 + P352 IF ON SKIN: Wash with plenty of water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

#### Disposal:

Mixture

P501 Dispose of contents/ container to an approved waste disposal plant.

#### **Additional Labeling**

Substance / Mixture

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.


#### Other hazards

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components			
Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
Calcium dihydroxide	1305-62-0	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 10 - < 30
Poly(oxy-1,2-ethanediyl), .alpha tridecylomegahydroxy-, branched	69011-36-5	Eye Irrit. 2A; H319	>= 1 - < 5
naphtha (petroleum), heavy alkylate	64741-65-7	Flam. Liq. 3; H226 Eye Irrit. 2B; H320 Asp. Tox. 1; H304	>= 1 - < 5
C12-18 (even numbered) Alkylami- dopropylbetaines	Not Assigned	Eye Dam. 1; H318	>= 1 - < 4

Revision Date 12/10/2024



#### **SECTION 5. FIRE-FIGHTING MEASURES**

		0.144
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.



Print Date 12/10/2024



Revision Date 12/10/2024	Print Date 12/10/2024
	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment : for fire-fighters	In the event of fire, wear self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions :	Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for : containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Follow standard hygiene measures when handling chemical products.</li> </ul>
Conditions for safe storage	:	Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
--------------------	------------------------	---------------------------------------	-------



<b>Revision Dat</b>	te 12/10/2024

### Print Date 12/10/2024

Calcium dihydroxide1305-62-0TWA5 mg/m3CA AB CCalcium dihydroxide1305-62-0TWA5 mg/m3CA AB CTWA5 mg/m3CA QC CTWA5 mg/m3CA QC CTWA5 mg/m3CA QC CTWA5 mg/m3CA AB Cglycerol56-81-5TWA (Mist)10 mg/m3CA AB CTWA5 mg/m3CA BC CTWA (Mist)10 mg/m3CA BC CTWA5 mg/m3CA BC CTWA (Res- pirable mist)3 mg/m3CA BC CTWATWAEV10 mg/m3CA QC CCharlesUse of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend ed or statutory limits.Personal protective equipment Respiratory protectionUse a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.The filter class for the respirator must be suitable for the max imum expected contaminant to nocentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.	DEL
Image: Second	DEL
Image: system of the system	
Image: space spac	DEL
glycerol       56-81-5       TWA (Mist)       10 mg/m3       CA AB C         TWA (Mist)       10 mg/m3       CA BC C         TWA (Res- pirable mist)       3 mg/m3       CA BC C         TWA (Res- pirable mist)       3 mg/m3       CA BC C         TWA (Res- pirable mist)       3 mg/m3       CA QC C         Engineering measures       :       Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend ed or statutory limits.         Personal protective equipment       :       Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.         The filter class for the respirator must be suitable for the max imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.	
TWA (Mist)         10 mg/m3         CA BC C           TWA (Res- pirable mist)         3 mg/m3         CA BC C           TWA (Res- pirable mist)         3 mg/m3         CA QC C           TWAEV (Mist)         10 mg/m3         CA QC C           Engineering measures         :         Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend ed or statutory limits.           Personal protective equipment         :         Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.           The filter class for the respirator must be suitable for the max imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.	
TWA (Res- pirable mist)         3 mg/m3         CA BC ( CA BC ( pirable mist)           Engineering measures         :         Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend ed or statutory limits.           Personal protective equipment         Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.           The filter class for the respirator must be suitable for the max imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.	
pirable mist)         rwaEv (Mist)         10 mg/m3         CA QC of CA QC of Mist)           Engineering measures         :         Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend ed or statutory limits.           Personal protective equipment         Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.           The filter class for the respirator must be suitable for the max imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.	
Engineering measures       :       Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend ed or statutory limits.         Personal protective equipment         Respiratory protection       :       Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.         The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.	)EL
Engineering measures       :       Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend ed or statutory limits.         Personal protective equipment       Image: Statute of the statute of	
worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend ed or statutory limits.Personal protective equipmentUse a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.The filter class for the respirator must be suitable for the max imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.	)EL
Respiratory protection       : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.         The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.	
respirator complying with an approved standard if a risk as- sessment indicates this is necessary. The filter class for the respirator must be suitable for the max imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.	
imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.	
	-
Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.	J
Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.	
Skin and body protection : Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe cific work-place.	

Hygiene measures	:	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES



Revision Date 12/10/2024		Print Date 12/10/2024
Appearance	:	liquid
Color	:	various
Odor	:	aliphatic
Odor Threshold	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/ range / Freez-	:	No data available
ing point Boiling point/boiling range	:	No data available
Flash point	:	> 101 °C (214 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	23 hpa
Relative vapor density	:	No data available
Density	:	ca. 1.25 g/cm3 (20 °C (68 °F))
Solubility(ies) Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	ca. 2,000 mPa.s (20 °C (68 °F))
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
		6/11



Revision Date 12/10/2024		Print Date 12/10/2024	
Oxidizing properties	:	No data available	
SECTION 10. STABILITY AND REACTIVITY			
Reactivity	:	No dangerous reaction known under conditions of normal use.	
Chemical stability	:	The product is chemically stable.	
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.	
Conditions to avoid	:	No data available	
Incompatible materials	:	No data available	
Hazardous decomposition products	:	No decomposition if stored and applied as directed.	
SECTION 11. TOXICOLOGICAL INFORMATION			
Acute toxicity			
Not classified due to lack of data.			
<u>Components:</u>			
C12-18 (even numbered) Alk	yla	midopropylbetaines:	
Acute oral toxicity	:	LD50 Oral (Rat): 2,235 mg/kg	

#### Skin corrosion/irritation

Causes skin irritation.

#### Components:

#### naphtha (petroleum), heavy alkylate:

Assessment:Repeated exposure may cause skin dryness or cracking.Result:Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

#### Skin sensitization

Not classified due to lack of data.

#### **Respiratory sensitization**

Not classified due to lack of data.



ision Date 12	2/10/2024		Print Date 12/10/
Germ cell	mutagenicity		
Not classifi	ed due to lack of data	а.	
Carcinoge	nicity		
Not classifi IARC	ed due to lack of data Not applicable	а.	
OSHA	OSHA specifica Talc (crystalline silica	lly regulated carcinogen	14807-96-6
NTP	Not applicable		
Reproduct	ive toxicity		
Not classifi	ed due to lack of data	а.	
STOT-sing	le exposure		
May cause	respiratory irritation.		
STOT-repe	ated exposure		
Not classifi	ed due to lack of data	а.	
Aspiration	toxicity		
Not classifi	ed due to lack of data	а.	
<b>Ecotoxicit</b> No data av	ailable e and degradability		
	ulative potential		
No data av	-		
Mobility in	soil		
No data av			
Other adve	erse effects		
Product:			
Additional e	ecological infor-	Do not empty into drains; dis	pose of this material and its con-

Additional ecological information

Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Revision Date 12/10/2024	Print Date 12/10/2024
SECTION 13. DISPOSAL CONSIDERATIONS	

#### **Disposal methods**

Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

TDG

Not regulated as a dangerous good

#### SECTION 15. REGULATORY INFORMATION

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safe- ty, Schedule 1, Part 1: Permissible exposure values for air- borne contaminants
ACGIH / TWA CA AB OEL / TWA		8-hour, time-weighted average 8-hour Occupational exposure limit



Revision Date 12/10/2024		Print Date 12/10/2024
CA BC OEL / TWA CA QC OEL / TWAEV	:	8-hour time weighted average Time-weighted average exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

#### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.



#### Revision Date 12/10/2024

Print Date 12/10/2024

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date Date format	: 12/10/2024 : mm/dd/yyyy
Prepared by	: R & D of Sika Canada Inc.
Material number	: 781,323

CA / Z8