according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

SECTION 1. IDENTIFICATION

Product name : Sikalastic TC 297 FS Formerly MSeal TC 297FS

Product code : 00000000050002015

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Sika MBCC Canada, Inc.

Address : 601 DELMAR AVE

Pointe-Claire QC H9R 4A9

Emergency telephone : ChemTel: +1-813-248-0585;

National Emergency Tele-

phone Number

: Canada: 1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Floor coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2

Skin irritation : Category 2

Skin sensitization : Category 1B

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapors.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 05/17/2024 000000260445 Date of first issue: 10/29/2020 2.0

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature methacrylates

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
methyl methacrylate	2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	>= 30 - < 60
2-ethylhexyl acrylate	2-Propenoic acid, 2- ethylhexyl ester	103-11-7	>= 30 - < 60
2,2'- Ethylenedioxydiethyl dimethacrylate	Triethylene gly- col dimethacry- late	109-16-0	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice First aid personnel should pay attention to their own safety.

Remove contaminated clothing.

If inhaled Remove the affected individual into fresh air and keep the

person calm.

If breathing difficulties develop, aid in breathing and seek im-

mediate medical attention.

In case of skin contact Wash thoroughly with soap and water

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact Contact lenses should be removed. Hold eyelids open and

flush with copious amounts of clean, fresh water or a special

eyewash solution and seek medical advice.

If swallowed Rinse mouth and then drink 200-300 ml of water.

Do not induce vomiting due to aspiration hazard.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Most important symptoms

and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction. May cause respiratory irritation.

Notes to physician Treat symptomatically.

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry powder

Foam

Carbon dioxide (CO2)

Water spray

Alcohol-resistant foam

Unsuitable extinguishing

media

water jet

Hazardous combustion prod- :

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black

Further information : Containers may rocket or explode in heat of fire.

carbon oxides

Keep containers cool by spraying with water if exposed to fire. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of igni-

tion.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Run-off water from fire may cause pollution.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment:

for fire-fighters

Firefighters should be equipped with self-contained breathing

apparatus and turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Can release flammable vapours. Wind direction should be noted.

Avoid all sources of ignition: heat, sparks, open flame.

Use antistatic tools.

Breathing protection required. Use personal protective clothing.

Avoid contact with the skin, eyes and clothing.

Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil

barriers).

Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Keep away from open flames, hot surfaces and sources of

ignition.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Use only explosion-proof equipment.

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of igni-

tion.

Advice on safe handling : Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges. Provide good room ventilation even at ground level (vapours

are heavier than air).
Avoid formation of aerosol.
Do not breathe mist or vapors.
Avoid contact with skin and eyes.

Conditions for safe storage : Keep containers tightly closed in a cool, well-ventilated place.

Keep away from heat.

Keep away from sources of ignition - No smoking.

Materials to avoid : Segregate from foods and animal feeds.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	STEL	100 ppm 410 mg/m3	CA AB OEL
		TWA	50 ppm 205 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH

Engineering measures : Provide local exhaust ventilation to maintain recommended

P.E.L.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid prolonged and/or repeated contact with the skin. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : Food, beverages, and tobacco products shall not be carried,

stored, or consumed where this material is in use.

Hands and/or face should be washed before breaks and at

the end of the shift.

Handle in accordance with good industrial hygiene and safety

practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : amber, cloudy

Odor : sweet, ester-like

Odor Threshold : not determined

pH : No data available

Melting point/freezing point : -48 °C

Boiling point/boiling range : 100 °C

Flash point : 9 °C

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

Evaporation rate : > 1

(Butyl Acetate=1.0)

Flammability (liquids) : Highly flammable liquid and vapor.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : 27.8 mmHg (20 °C)

Relative vapor density : 3.1

(Air = 1.0)

Relative density : 0.97

Density : 0.97 g/ml (25 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

not applicable for mixtures

Autoignition temperature : 430 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 200 cps (25 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

No hazardous reactions if stored and handled as pre-

scribed/indicated.

Conditions to avoid : Avoid all sources of ignition: heat, sparks, open flame.

Avoid electro-static discharge.

Avoid heat.

Incompatible materials : Strong bases

Acids

Oxidizing agents

Hazardous decomposition

products

carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Group 2B: Possibly carcinogenic to humans

2-ethylhexyl acrylate 103-11-7

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicolo-

gy have been derived from the properties of the individual

components.

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

Do not discharge into drains/surface waters/groundwater. Residues should be disposed of in the same manner as the

substance/product.

Contaminated packaging : Uncleaned empty vessels may contain product gases which

can form explosive mixtures with air. Avoid all sources of igni-

tion.

Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo : 364

aircraft)

Packing instruction (passen- :

ger aircraft)

353

IMDG-Code

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/12/2022

 2.0
 05/17/2024
 000000260445
 Date of first issue: 10/29/2020

Class : 3
Packing group : II
Labels : 3
ERG Code : 127
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumu-

according to the Hazardous Products Regulations



Sikalastic TC 297 FS Formerly MSeal TC 297FS

Version Revision Date: SDS Number: Date of last issue: 01/12/2022 2.0 05/17/2024 000000260445 Date of first issue: 10/29/2020

lative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 05/17/2024 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN