

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 000000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

SECTION 1. IDENTIFICATION

Product name : SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M

Product code : 000000000051718448

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Waterproof coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)


Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity : Category 2 (Kidney)
- repeated exposure

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 00000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapors.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards
None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Acrylic polymer
inorganic compounds

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 30 - < 50
Titanium dioxide	13463-67-7	>= 5 - < 10
Perlite, expanded	93763-70-3	>= 5 - < 10
ethylene glycol	107-21-1	>= 1 - < 5
zinc oxide	1314-13-2	>= 0.1 - < 1
Quartz (SiO ₂)	14808-60-7	>= 0.1 - < 1
diuron	330-54-1	< 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	< 0.1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.
Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,
remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water
and soap.

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version	Revision Date:	SDS Number:	Date of last issue: 10/15/2020
2.0	07/26/2021	00000261433	Date of first issue: 10/15/2020

- Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,
seek medical attention.
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : May cause cancer by inhalation.
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protection : Do not breathe vapour/aerosol/spray mists.
-

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 000000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

- tive equipment and emergency procedures : Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Recommended storage temperature : > 39 °F / > 4 °C
- Further information on storage stability : PROTECT FROM FREEZING DURING THE COLD-SEASON (BELOW 40°F / 5°C).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of)	Control parameters / Permissible	Basis
------------	---------	----------------------	----------------------------------	-------

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 000000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

		exposure)	concentration	
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Perlite, expanded	93763-70-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (Total)	15 mg/m3	OSHA P0

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 00000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

		dust)		
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
zinc oxide	1314-13-2	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		STEL value (Respirable fraction)	10 mg/m3	ACGIHTLV
		REL value (fumes/smoke)	5 mg/m3	NIOSH
		REL value (dust)	5 mg/m3	NIOSH
		STEL value (fumes/smoke)	10 mg/m3	NIOSH
		Ceil_Time (dust)	15 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (fumes/smoke)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smoke)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value (fumes/smoke)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable particulate mat-	2 mg/m3	ACGIH

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 000000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

		ter)		
		STEL (Respirable particulate matter)	10 mg/m3	ACGIH
		TWA (Dust)	5 mg/m3	NIOSH REL
		TWA (Fumes)	5 mg/m3	NIOSH REL
		ST (Fumes)	10 mg/m3	NIOSH REL
		C (Dust)	15 mg/m3	NIOSH REL
		TWA (Fumes)	5 mg/m3	OSHA Z-1
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Fumes)	5 mg/m3	OSHA P0
		STEL (Fumes)	10 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0

Engineering measures : Wear appropriate respiratory protection.

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 000000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : pigmented

Odor : sweetish, slight odour

Odor Threshold : not determined

pH : 9.2 - 10.0

Melting point : No data available

Boiling point : 379 - 401 °F / 193 - 205 °C

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 000000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

Flash point : > 200.1 °F / > 93.4 °C

Evaporation rate : No data available

Flammability (liquids) : not highly flammable
Method: derived from flash point

Upper explosion limit / Upper flammability limit : 15.3 %(V)

Lower explosion limit / Lower flammability limit : 3.2 %(V)

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : 1.2 - 1.4

Density : 1.2 - 1.4 g/cm³ (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)
Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 000000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.
- Chemical stability : The product is stable if stored and handled as prescribed/indicated.
- Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.
- Conditions to avoid : See SDS section 7 - Handling and storage.
- Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents
- Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.
-

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
	Group 2A: Probably carcinogenic to humans Perlite, expanded (glass)	93763-70-3
	Group 2B: Possibly carcinogenic to humans Titanium dioxide	13463-67-7

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 000000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

OSHA	OSHA specifically regulated carcinogen Quartz (SiO ₂) (crystalline silica)	14808-60-7
NTP	Known to be human carcinogen Quartz (SiO ₂) (Silica, Crystalline (Respirable Size))	14808-60-7

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

diuron:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic toxicity) : 10

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0	Revision Date: 07/26/2021	SDS Number: 000000261433	Date of last issue: 10/15/2020 Date of first issue: 10/15/2020
----------------	------------------------------	-----------------------------	---

icity)

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version 2.0 Revision Date: 07/26/2021 SDS Number: 00000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
carbendazim	10605-21-7	10	27700

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethylene glycol 107-21-1 >= 1 - < 5 %

US State Regulations

Pennsylvania Right To Know

Limestone	1317-65-3
Titanium dioxide	13463-67-7
Perlite, expanded	93763-70-3
ethylene glycol	107-21-1
zinc oxide	1314-13-2
diuron	330-54-1
ammonia	7664-41-7
ammonia, aqueous solution	1336-21-6

New Jersey Right To Know

Limestone	1317-65-3
Titanium dioxide	13463-67-7
Perlite, expanded	93763-70-3
ethylene glycol	107-21-1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Quartz (SiO ₂)	14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

DSL : This product contains one or more components not listed on the Canadian DSL or NDSL. All other components are on the Canadian DSL.

Canadian lists

The following substance(s) is/are subject to a Significant New Activity Notification:
carbendazim 10605-21-7

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M




Version 2.0 Revision Date: 07/26/2021 SDS Number: 00000261433 Date of last issue: 10/15/2020
Date of first issue: 10/15/2020


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- 29 CFR 1910.1000 (Table Z-1-A) / STEL value : Short Term Exposure Limit (STEL):
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version	Revision Date:	SDS Number:	Date of last issue: 10/15/2020
2.0	07/26/2021	00000261433	Date of first issue: 10/15/2020

ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / Ceil_Time : Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value : Recommended exposure limit (REL):
NIOSH / STEL value : Short Term Exposure Limit (STEL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded
at any time during a workday
NIOSH REL / C : Ceiling value not be exceeded at any time.
OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA P0 / C : Ceiling limit
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/26/2021

SAFETY DATA SHEET

SikaThorolastic-750 coarse medium series Formerly MProtect EL 750 CS Ser M



Version	Revision Date:	SDS Number:	Date of last issue: 10/15/2020
2.0	07/26/2021	00000261433	Date of first issue: 10/15/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN