

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 03/29/2021
3.0	03/25/2024	000000260446	Date of first issue: 08/04/2020

SECTION 1. IDENTIFICATION

Product name : Sikafloor-41 P Pronto Formerly MTop SRS 41P

Product code : 000000000056433858

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Floor coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure

Specific target organ toxicity : Category 2
- repeated exposure

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version 3.0 Revision Date: 03/25/2024 SDS Number: 000000260446 Date of last issue: 03/29/2021
Date of first issue: 08/04/2020

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ atten-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version 3.0 Revision Date: 03/25/2024 SDS Number: 000000260446 Date of last issue: 03/29/2021
Date of first issue: 08/04/2020

tion.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : methacrylic ester

Components

Chemical name	CAS-No.	Concentration (% w/w)
methyl methacrylate	80-62-6	$\geq 60 - < 90$
N,N-dimethyl-p-toluidine	99-97-8	$\geq 1 - < 5$
2,2'-Ethylenedioxydiethyl dimethacrylate	109-16-0	$\geq 1 - < 5$
2,6-di-tert-butyl-p-cresol	128-37-0	$\geq 0 - < 1$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled : Remove the affected individual into fresh air and keep the person calm. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

In case of skin contact : Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

In case of eye contact : Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.

If swallowed : Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting due to aspiration hazard. Do not induce vomiting unless told to by a poison control center or doctor.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 03/29/2021
3.0	03/25/2024	000000260446	Date of first issue: 08/04/2020

Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry powder
Alcohol-resistant foam
Water spray
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides

Further information : The degree of risk is governed by the burning substance and the fire conditions.
Containers may rocket or explode in heat of fire.
Keep containers cool by spraying with water if exposed to fire.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Avoid contact with the skin, eyes and clothing.
Remove all sources of ignition.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil barriers).
Contain contaminated water/firefighting water.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version 3.0 Revision Date: 03/25/2024 SDS Number: 000000260446 Date of last issue: 03/29/2021
Date of first issue: 08/04/2020

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Sources of ignition should be kept well clear.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.
Substance/product can form explosive mixture with air.
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Advice on safe handling : Wear suitable personal protective clothing and equipment.
Take precautionary measures against static discharges.
Keep away from sources of ignition - No smoking.
Provide good room ventilation even at ground level (vapours are heavier than air).

Conditions for safe storage : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Vapours may travel along floor and ignite at a location distant from the handling point.
Take precautionary measures against static discharges.
Electrical equipment must be explosion-proof to the appropriate standards. Keep containers tightly closed. No smoking.
Prevent unauthorized access. Containers which are opened must be carefully resealed.

Materials to avoid : Segregate from incompatible substances.
See SDS section 10 - Stability and reactivity.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm 410 mg/m3	NIOSH REL
		TWA	100 ppm	OSHA Z-1

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version 3.0 Revision Date: 03/25/2024 SDS Number: 000000260446 Date of last issue: 03/29/2021
Date of first issue: 08/04/2020

			410 mg/m3	
		TWA	100 ppm 410 mg/m3	OSHA P0
N,N-dimethyl-p-toluidine	99-97-8	TWA	0.5 ppm	US WEEL
2,6-di-tert-butyl-p-cresol	128-37-0	TWA (Inhalable fraction and vapor)	2 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation, especially in confined areas. Exhaust fans should be explosion proof.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.
Antistatic apron

Protective measures : Avoid inhalation of dusts/mists/vapours.
Avoid contact with the skin, eyes and clothing.
Avoid prolonged and/or repeated contact with the skin.
Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : blue

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version 3.0 Revision Date: 03/25/2024 SDS Number: 000000260446 Date of last issue: 03/29/2021
Date of first issue: 08/04/2020

Odor : sweet, ester-like

Odor Threshold : not determined

pH : Not applicable

Melting point/freezing point : -54 °F / -48 °C

Boiling point : 212 °F / 100 °C

Flash point : 48 °F / 9 °C

Evaporation rate : > 1
(Butyl Acetate=1.0)

Flammability (liquids) : Highly flammable liquid and vapor.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : 27.8 hPa (68 °F / 20 °C)

Relative vapor density : 3.1
(Air = 1.0)

Relative density : 0.98

Density : 0.98 g/ml (77 °F / 25 °C)
8.16 lb/gal

Solubility(ies)
Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : 806 °F / 430 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 03/29/2021
3.0	03/25/2024	000000260446	Date of first issue: 08/04/2020

Viscosity, dynamic	:	13 cps (77 °F / 25 °C)
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	Not an oxidizer.
Sublimation point	:	No data available
Molecular weight	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	No hazardous reactions if stored and handled as prescribed/indicated.
Conditions to avoid	:	Avoid all sources of ignition: heat, sparks, open flame. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Incompatible materials	:	Strong bases Acids Oxidizing agents
Hazardous decomposition products	:	Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 03/29/2021
3.0	03/25/2024	000000260446	Date of first issue: 08/04/2020

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

IARC Group 2B: Possibly carcinogenic to humans
N,N-dimethyl-p-toluidine 99-97-8

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 03/29/2021
3.0	03/25/2024	000000260446	Date of first issue: 08/04/2020

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not discharge into drains/surface waters/groundwater. Residues should be disposed of in the same manner as the substance/product.
- Contaminated packaging : Uncleaned empty vessels may contain product gases which can form explosive mixtures with air. Avoid all sources of ignition. Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : II
Labels : 3
Environmentally hazardous : no

IATA-DGR

- UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

- UN number : UN 1866
Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version 3.0 Revision Date: 03/25/2024 SDS Number: 000000260446 Date of last issue: 03/29/2021
Date of first issue: 08/04/2020

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1866
Proper shipping name : Resin solution

Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
ERG Code : 127
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methyl methacrylate	80-62-6	1000	1428

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

methyl methacrylate 80-62-6 >= 70 - < 90 %
late

US State Regulations

Pennsylvania Right To Know

methyl methacrylate 80-62-6

New Jersey Right To Know

methyl methacrylate 80-62-6

California Prop. 65

WARNING: This product can expose you to chemicals including N,N-dimethyl-p-toluidine, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET


according to the OSHA Hazard Communication Standard




Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version 3.0 Revision Date: 03/25/2024 SDS Number: 000000260446 Date of last issue: 03/29/2021
Date of first issue: 08/04/2020

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average
- US WEEL / TWA : 8-hr TWA

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-41 P Pronto Formerly MTop SRS 41P

Version	Revision Date:	SDS Number:	Date of last issue: 03/29/2021
3.0	03/25/2024	000000260446	Date of first issue: 08/04/2020

Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/25/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN