

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

SECTION 1. IDENTIFICATION

Product name : SikaRepair®-223 CA

Manufacturer or supplier's details

Company name : 601, avenue Delmar
Canada
Pointe-Claire, QC H9R 4A9
Sika Canada Inc.
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services' e-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion : Category 1C

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ systemic toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ systemic toxicity - repeated exposure : Category 1 (Lungs)

GHS label elements

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H350i May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
Disposal:

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Portland cement	65997-15-1	>= 15 - < 40
Quartz (SiO ₂) <5µm	14808-60-7	>= 10 - < 30
Quartz (SiO ₂)	14808-60-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

Most important symptoms
and effects, both acute and
delayed

: Health injuries may be delayed.
corrosive effects
irritant effects
sensitizing effects
carcinogenic effects
Cough
Respiratory disorder
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects
and symptoms.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer by inhalation.
Causes damage to organs through prolonged or repeated
exposure.
Causes severe burns.

Notes to physician

: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local
circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This
must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must
be disposed of in accordance with local regulations.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for fire-fighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : Use personal protective equipment.
protective equipment and : Avoid breathing dust.
emergency procedures : Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform
respective authorities.

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Prevent unauthorized access.
Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Portland cement	65997-15-1	TWA	10 mg/m ³	CA AB OEL
		TWAEV (respirable dust)	5 mg/m ³	CA QC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA (Respirable)	1 mg/m ³	CA BC OEL

SAFETY DATA SHEET

SikaRepair®-223 CA

Version
1.2Revision Date:
11/15/2017SDS Number:
10000000308

		TWA (Respirable fraction)	1 mg/m ³	ACGIH
Quartz (SiO ₂) <5µm	14808-60-7	TWA (Respirable fraction)	0.1 mg/m ³	CA ON OEL
		TWA (Respirable particulates)	0.025 mg/m ³	CA AB OEL
		TWAEV (respirable dust)	0.1 mg/m ³	CA QC OEL
		TWA (Respirable)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
calcium sulfate	7778-18-9	TWA (Inhalable)	10 mg/m ³	CA BC OEL
		TWAEV (respirable dust)	5 mg/m ³	CA QC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³	CA AB OEL
		TWA	10 mg/m ³ (Calcium)	CA AB OEL
		TWA	10 mg/m ³ (Calcium)	CA AB OEL
		TWA (Inhalable fraction)	10 mg/m ³ (Calcium)	ACGIH
		TWA (Inhalable fraction)	10 mg/m ³ (Calcium)	ACGIH
fumes, silica	69012-64-2	TWA (Total fume)	4 mg/m ³	CA BC OEL
		TWA (Respirable fume)	1.5 mg/m ³	CA BC OEL
		TWA (Respirable fraction - fume)	2 mg/m ³	CA ON OEL
		TWAEV (Respirable fume)	2 mg/m ³	CA QC OEL
Quartz (SiO ₂)	14808-60-7	TWA	0.1 mg/m ³	CA ON OEL

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
10000000308

		(Respirable fraction)		
		TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.
Avoid breathing dust.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: powder
Color	: gray
Odor	: odorless
Odor Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Density	: ca. 2.7 g/cm ³ (23 °C (73 °F) ())
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

Viscosity, dynamic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.
Chemical stability : The product is chemically stable.
Possibility of hazardous reactions : Stable under recommended storage conditions.
Conditions to avoid : No data available
Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Product:

Remarks: Product contains Portland cement which contains a chromate reducing agent. If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the reducing agent can be diminished prematurely and the product may become skin sensitizing.

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC

Group 1: Carcinogenic to humans

Quartz (SiO₂) <5µm 14808-60-7

Quartz (SiO₂) 14808-60-7

NTP

Known to be human carcinogen

Quartz (SiO₂) <5µm 14808-60-7

Quartz (SiO₂) 14808-60-7

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological
information

: Do not empty into drains; dispose of this material and its
container in a safe way.

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
-

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

TDG (road/train)

Not dangerous goods

International Regulations

IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Revision Date : 11/15/2017
Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current

SAFETY DATA SHEET

SikaRepair®-223 CA



Version
1.2

Revision Date:
11/15/2017

SDS Number:
100000000308

Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Full text of other abbreviations

ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

CA / Z8